



altro

AltroMastic™ 100

Caulking compound

Procedure

1. AltroMastic 100 is a specially formulated sealing compound for use where Altro floors abuts edges, skirtings, wall surfaces or where the flooring is cut around pipes and door frames.
2. AltroMastic 100 is not recommended for where flooring joins drainage channels, access covers, and quarry tiles. Instead a clamping or welding system should be used. Please refer to Altro for detailing sheets.
3. AltroMastic 100 should only be used to seal joints in Altro floors where obstructions prevent the use of a hot air welding gun.

Instructions for use

1. Surfaces to be sealed must be dry and free from dirt, oil or grease.
2. All areas to be sealed should be masked with masking tape.
3. Place tube of sealant into caulking gun.
4. Cut off the end of the tube nipple, fix the nozzle, and apply a bead approximately 3mm in diameter.
5. Once opened the curing process begins, therefore, open tubes may not be reused as the mastic may have cured within the tube.
6. Remove masking tape as soon as possible as AltroMastic 100 is formulated to be fast curing.

Contains no solvent of isocyanate

- Can cause irritation by inhalation, skin contact and ingestion.
- When using, do not eat, drink or smoke.
- Do not empty into drains.
- Keep out of the reach of children.

Specifications

Viscosity	Thixotropic
Density	1.01
Cure time	24 - 48 hours
Skin time	20 minutes
Storage	Store between 40°F to 75°F in cool, dry conditions
Shelf life	12 months, in an airtight container
Coverage	Approx. 130 linear ft (40m) per 3mm bead
Working temperature	Between 40°F to 105°F
Full bond	4 days
Contains	10 ounce (290ml)
Colors	Available in many colors