



# AltroFix™ 31

Fast-acting two-part polyurethane adhesive

## Features and benefits

- Installs in areas up to 90% RH
- Extremely fast curing time—heat welding can be performed the same day
- Outstanding adhesion in areas with heavy traffic and rolling loads
- Excellent for water spray areas, such as produce departments in grocery stores
- Freeze-thaw stability: 5 cycles at 0° F
- Solvent-free
- Low VOCs less than 12 grams/liter
- Complies with South Coast Air Quality Management District #1168

## Applications

AltroFix 31 two-part, fast-acting polyurethane adhesive is recommended for the installation of Altro flooring on clean and dry subfloors, above, on or below grade.

AltroFix 31 is extremely fast acting and is perfect for use in small wet areas — like a bathroom — and allows for heat welding to be performed the same day (approximately 6 hours later).

## Specifications

AltroFix 31 is sold in one gallon units (Part A mixes with Part B). Approximate coverage is 150 square feet per gallon.

For installation instructions, consult the Altro sheet flooring installation guide or adhesive label.

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and subfloor texture and porosity, Altro does not warrant nor guarantee actual adhesive coverages.



<b>LEED facts</b>			
LEED v4		This product may help contribute to the following credits	
AltroFix 31		<b>1</b>	
	Environmental quality	<b>1</b>	
	Low emitting materials, adhesives		

Discover more of our sustainability story and credentials at [altro.com](http://altro.com)

