



Designed for possibilities.
Made for people.

Altro Serenade™

Smooth flooring with enhanced sound reduction and high underfoot comfort



discover [altro.com](https://www.altro.com)

3.9mm
thick

6'7"
width

66'
length


sheet
format




Rhythm SE3907
WR428 / AM200 LRV 50




Cymbal SE3910
WR431 / AM200 LRV 53



Mezzo SE3913
WR434 / AM200 LRV 49



Metronome SE3914
WR435 / AM200 LRV 26



Cadence SE3908
WR429 / AM200 LRV 26




Maestro SE3903
WR424 / AM200 LRV 32




Tambourine SE3911
WR432 / AM200 LRV 26



Finale SE3902
WR423 / AM200 LRV 20



Bridge SE3912
WR433 / AM200 LRV 15



Octave SE3915
WR436 / AM200 LRV 17




Prelude SE3923
WR444 / AM200 LRV 24




Saxophone SE3920
WR441 / AM200 LRV 30



March SE3925
WR446 / AM200 LRV 37



Encore SE3929
WR450 / AM200 LRV 24



Bar SE3931
WR452 / AM200 LRV 17



Specifications			
Type + class		ASTM F1303	Type I, Grade 1, Class C, smooth flooring
Thickness and wear layer		3.9mm .15" / .7mm wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5 2m x 20m	
Weight		5.34 lbs./yd ² 2.9 kg/m ²	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.7 dry, .8 wet
Ramp test		DIN 51130	R10
Static load limit		ASTM F970	500 psi
Indentation		EN 433	≤ 0.20mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		EN ISO 24344	Pass
Light fastness		EN 105-B02	≥ 6
Sound insulation		ISO 10140 IIC rating	19dB 54
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Blown PVC backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Serenade and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2019

LEED facts

LEED v4 This product may help contribute to the following credits

Altro Serenade
5

Materials and resources
Renewable bio-based content

1

Materials and resources - EPD
Environmental product declaration
Type III product specific

1

Materials and resources - HPD
Health product declaration

1

Environmental quality
Low emitting materials, flooring

1

Environmental quality
Low emitting materials, adhesives

1

Discover more of our sustainability story and credentials at altro.com/sustainability