



Designed for possibilities.  
Made for people.

# Altro Walkway™ 20 SD

Static-dissipative slip-resistant flooring for electrically sensitive installations



2mm  
thick

6'7"  
width

66'  
length

sheet  
format

# Altro Walkway 20 SD

Static-dissipative flooring for electrically sensitive installations

## Slip resistance


Static coefficient of friction		ASTM D2047	.78 dry, .80 wet
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976	36+

## Specifications

Thickness	2.0mm   .08"		
Roll dimensions	6'7" x 66'   2.0m x 20m		
Weight	4.79 lbs./yd <sup>2</sup>   2.6 kg/m <sup>2</sup>		
Wear layer	2.0mm, homogeneous construction		
Cleaning technology		Altro Easyclean	
Warranty		10 years	
Static load limit		ASTM F970	1000 psi
Sound insulation		ISO 140-8	5dB
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Surface Resistivity		EN 1081	2x10 <sup>7</sup> Ω
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Recycled content		Contains 10% pre-consumer & 10% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> , training clinic information at <a href="http://altrofloors.com/training">altrofloors.com/training</a> . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, the future is safer with Altro, Altro Walkway 20 SD and Altro Easyclean are all trademarks of Altro Limited. Folder content was correct at time of print. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information. © Copyright Altro USA 2017

Follow us



USA 800 377 5597

CANADA 800 565 4658

support@altrofloors.com

www.altro.com

## LEED facts



LEED v4

This product may help contribute to the following credits


Altro Walkway 20

6

	Materials and resources Contains recycled content	1
	Materials and resources Renewable bio-based content	1
	Materials and resources Environmental product declaration	1
	Materials and resources Health product declaration	1
	Environmental quality Low emitting materials, flooring	1
	Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at [altro.com/sustainability](http://altro.com/sustainability)

## Altro Walkway 20 SD color availability



Fog SD

VM20153SD

WR81 / AM81

LRV 27

Additional colors of Altro Walkway 20 may be ordered in a static dissipative option. Please discuss minimum order quantities and shipping time with your Altro representative.