



Designed for possibilities.  
Made for people.

# Altro Walkway™ 20 SD

Static-dissipative slip-resistant flooring for electrically sensitive installations



2mm  
thick

6'7"  
width

66'  
length

sheet  
format

Specifications			
Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.0mm   .08", homogenous construction	
Roll dimensions		6'7" x 66'   2m x 20m	
Weight		4.79 lbs./yd <sup>2</sup>   2.6 kg/m <sup>2</sup>	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.78 dry, .8 wet
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976 ASTM E303	36+
Static load limit		ASTM F970	1000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 105-B02	≥ 6
Sound insulation		ISO 140-8	5dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Surface Resistivity		EN 1081	2x10 <sup>7</sup> Ω
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		Contains 10% pre-consumer & 10% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> , training clinic information at <a href="http://altrofloors.com/training">altrofloors.com/training</a> . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> . Failure to install, heat weld, and/or maintain correctly could void the warranty.		

## LEED facts



LEED v4

This product may help contribute to the following credits


### Altro Walkway 20

6

	Materials and resources Contains recycled content	1
	Materials and resources Renewable bio-based content	1
	Materials and resources Environmental product declaration	1
	Materials and resources Health product declaration	1
	Environmental quality Low emitting materials, flooring	1
	Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at [altro.com/sustainability](http://altro.com/sustainability)

### Altro Walkway 20 SD color availability



Fog SD

VM20153SD

WR81 / AM81

LRV 27

Additional colors of Altro Walkway 20 may be ordered in a static dissipative option. Please discuss minimum order quantities and shipping time with your Altro representative.

Follow us



USA 800 377 5597

CANADA 800 565 4658

support@altrofloors.com

www.altro.com