



# Altro Walkway™ 20

## Tender text

### PRODUCT DESCRIPTION

- Manufacturer and product reference:
  - **Altro Walkway 20** 2 mm thick safety floor by Altro Limited
- Product specification according to EN 13845
- PVC floor covering with glass fibre reinforced polyester cellulose backing
- **o-Phthalate free: plasticisers based on natural resources**
- **Area of use:**
  - General purpose areas
- Surface protection: **Easyclean PUR**
- EN ISO 10874: **Class 34 / 43**
- Slip potential: Pendulum test value (PTV) (minimum) to BS 7976: **≥ 36 (wet)**
- Recycled content: **10%**
- Surface roughness (Rz) (minimum) to BS 1134: **≥ 20 micron**
- Width: **2000 mm**
- Thickness: **2.00 mm**
- Colour: **TBC**
- Guarantee: **10 years**
- Seam welding: **Hot-welding with matching Altro welding rod**
- The Altro quality and environmental management systems are certified according to ISO 9001:2015 and ISO 14001:2015

| Property               | Standard   | Performance                                   |
|------------------------|--|---|
| Flooring Type          | EN 13845 / EN 13553                                | Resilient safety flooring                     |
| Thickness              | EN ISO 24346                                       | 2 mm  |
| Roll dimensions        | EN ISO 24341                                       | 2.0 m x 20.00 m – 40 m <sup>2</sup>           |
| Weight                 | EN ISO 23997                                       | 2.6 kg/m <sup>2</sup>                         |
| Classification for use | EN ISO 10874                                       | 34 / 43                                       |
| Fire performance       | EN 13501-1<br>EN ISO 9239-1<br>EN ISO 11925-2      | Class Bfl-s1<br>≥ 8 kW/m <sup>2</sup><br>Pass |
| Slip resistance        | BS 7976 / PTV<br>EN 13845<br>EN 13893<br>DIN 51130 | ≥ 36<br>ESf<br>≥ 0.30 / DS<br>R10             |
| Flexibility            | EN ISO 24344                                       | Pass  |
| Light fastness         | EN ISO 105-B02                                     | ≥ 6   |
| Wear resistance        | EN 13845   | ≤ 10% particles lost over 50000 cycles        |
| Castor chair abrasion  | EN 425   | Pass  |
| Residual indentation   | EN 433   | ≤ 0.10 mm                                     |
| Sound insulation       | ISO 140-8  | Ca. 5 dB                                      |
| Chemical resistance    | EN 423   | Good  |
| Under floor heating    | EN 12524   | Suitable 27°C at adhesive line                |
| Electrical behaviours  | EN 1815  | ≤ 2 kV Antistatic                             |
| VOC Emissions          | CDPH 1350 / Floorscore / M1                        | Approved                                      |