



# Altro W157™

Acrylic adhesive for Altro Whiterock wall panels

## Features and benefits

- Altro Whiterock’s most economic adhesive
- Solvent-free wall adhesive
- Easier spread and greater yield per square foot
- Smooth paste application — no more “watery” adhesive!
- Same 100% adhesive coverage
- Complies with South Coast Air Quality Management District #1168 (SCAQMD)
- Low VOCs
- FloorScore certified
- Greater adhesive content

## Applications

Altro W157 adhesive is a single component, acrylic adhesive developed and recommended for the installation of Altro Whiterock wall panels over permanently clean, dry and sound wall substrates.

For use on absorbent surfaces only. Do not use adhesives, paints, or primers near exposed food.

## Specifications

Apply an even coat of Altro W157 adhesive to the entire back of the sheet using a 3/16” square notch trowel. Adhesive spread rate is at least 5 panels per 4 gallon pail.

## Joint options

### Welded joints

Use W165 tape adhesion promoter, double sided foam tape - ALW W157 tape and color-coordinating Weldrod.

### Flexijoint

Use W165 tape adhesion promoter, A815/30 double sided black butyl tape and color-coordinating weldrod.

### Joint system accessories

Use W165 tape adhesion promoter, A815/30 double sided black butyl tape and color-coordinating Altro two-part or one-part joint accessories.



**LEED facts**  

LEED v4 This product may help contribute to the following credits

Altro W157	1
Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at [altro.com/sustainability](http://altro.com/sustainability)

