

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Article
Product name	: Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base
Product code	: SDDS_B____
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Use of the substance/mixture	: Industrial Flooring - Base

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Altro Resin Systems
Unit 3 Station Road Industrial Estate
Station Road
GB- DT2 0AE Maiden Newton Dorchester
T 01300 320620
sds@altro.com - www.altro.com

1.4. Emergency telephone number

Emergency number	: 01462 480480 Monday - Friday 09:00 - 17:00
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Flammable liquids, Category 3	H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



GHS02

GHS07

Signal word (GB CLP)	: Warning
Contains	: 2-METHOXY-1-METHYLETHYL ACETATE
Hazard statements (GB CLP)	: H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness.
Precautionary statements (GB CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof ventilating equipment.
P261 - Avoid breathing fume, vapours.
P271 - Use only outdoors or in a well-ventilated area.

2.3. Other hazards

Results of PBT and vPvB assessment

This substance does not meet the PBT criteria of UK REACH regulation, annex XIII
This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	2-METHOXY-1-METHYLETHYL ACETATE (108-65-6), Trimethylolpropane (77-99-6)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	2-METHOXY-1-METHYLETHYL ACETATE (108-65-6), Trimethylolpropane (77-99-6)

Results of Endocrine Disruptor assessment

The substance is not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP

Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	2-METHOXY-1-METHYLETHYL ACETATE(108-65-6), Trimethylolpropane(77-99-6)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
2-METHOXY-1-METHYLETHYL ACETATE substance with workplace exposure limit(s)	CAS-No.: 108-65-6 EC-No.: 203-603-9 UK Index-No.: 607-195-00-7	≥ 30 – < 50	Flam. Liq. 3, H226 STOT SE 3, H336
Trimethylolpropane	CAS-No.: 77-99-6 EC-No.: 201-074-9	≥ 0.1 – < 1	Repr. 2, H361fd

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after inhalation : IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention if irritation develops and persists.

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

First-aid measures after eye contact	: IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Immediately give plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide (CO ₂). Dry powder. Water fog.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is flammable. Vapours may ignite.
-------------	--

5.3. Advice for firefighters

Firefighting instructions	: Use water to cool exposed containers, cool and disperse vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective clothing. Avoid inhalation of vapours.
Emergency procedures	: Ventilate spillage area. No flames, no sparks. Eliminate all sources of ignition. Take precautionary measures against static discharge.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter sewers, surface or groundwater. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Place in an appropriate container and dispose of the contaminated material at a licensed site.
Methods for cleaning up	: Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Ensure equipment is adequately earthed. Provide adequate ventilation to minimize dust and/or vapour concentrations.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep only in original container. Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight.

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	274 mg/m ³
WEL STEL (OEL STEL)	548 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	550 mg/m ³
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m ³

DNEL/DMEL (General population)

Acute - systemic effects, oral	500 mg/kg bodyweight/day
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m ³
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.0635 mg/l

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
PNEC aqua (intermittent, freshwater)	6.35 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.29 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
Trimethylolpropane (77-99-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.94 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.3 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.34 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.58 mg/m ³
Long-term - systemic effects, dermal	0.34 mg/kg bodyweight/day
ETHYL ACETATE (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m ³
Acute - local effects, inhalation	1468 mg/m ³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m ³
Long-term - local effects, inhalation	734 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m ³
Acute - local effects, inhalation	734 mg/m ³
Long-term - systemic effects, oral	4.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m ³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.24 mg/l
PNEC aqua (marine water)	0.024 mg/l
PNEC aqua (intermittent, freshwater)	1.65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1.15 mg/kg dwt
PNEC sediment (marine water)	0.115 mg/kg dwt

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

ETHYL ACETATE (141-78-6)	
PNEC (Soil)	
PNEC soil	0.148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protective equipment

Personal protective equipment:

Safety glasses. Wear protective gloves. In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Pigmented.
Odour	: characteristic.
Odour threshold	: Not available
pH	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Flash point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: Not available
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not available
Explosive properties	: Not available

9.2. Other information

Particle characteristics : Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapour. If stored for long periods at ambient temperature peroxides may be formed. This will be accelerated at higher temperatures.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Vapours may ignite. formation of explosive air/vapour mixtures are possible. Reacts with : Oxidising agents.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Strong acids. Oxidising substances.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under fire conditions, Carbon oxides maybe produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LD50 oral rat	> 6190 ml/kg Method: OECD Test Guideline 401
LD50 dermal rat	> 5000 mg/kg Method: OECD Test Guideline 402

Trimethylolpropane (77-99-6)

LD50 oral rat	≈ 14700 mg/kg bodyweight Animal: rat, Animal sex: male
---------------	--

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Trimethylolpropane (77-99-6)	
LD50 dermal rabbit	> 10000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 0.85 mg/l air Animal: rat, Animal sex: male
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Trimethylolpropane (77-99-6)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, gas, 90 days)	≈ 3.5 ppm Animal: rat
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): <i>Oryzias latipes</i>
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): <i>Raphidocelis subcapitata</i> (previous names: <i>Pseudokirchneriella subcapitata</i> , <i>Selenastrum capricornutum</i>)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): <i>Oryzias latipes</i> Duration: '14 d'
NOEC chronic crustacea	> 100 mg/l

Trimethylolpropane (77-99-6)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): <i>Alburnus alburnus</i>
LC50 - Fish [2]	> 10 g/l Test organisms (species): <i>Alburnus alburnus</i>
EC50 - Crustacea [1]	13000 mg/l Test organisms (species): <i>Daphnia magna</i>

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Trimethylolpropane (77-99-6)	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	> 1000 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base	
Persistence and degradability	Not rapidly degradable
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
Persistence and degradability	Readily biodegradable.
Trimethylolpropane (77-99-6)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
Partition coefficient n-octanol/water (Log Kow)	1.2
Bioaccumulative potential	Bioaccumulation is insignificant.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base	
This substance does not meet the PBT criteria of UK REACH regulation, annex XIII	
This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII	
Component	
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Trimethylolpropane (77-99-6)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Do not puncture or incinerate, even when empty.
Ecological waste information : Avoid release to the environment.

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet






According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

HP Code : HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1866	UN 1866	UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name				
RESIN SOLUTION (RESIN SOLUTION, flammable)	RESIN SOLUTION (RESIN SOLUTION, flammable)	Resin solution (RESIN SOLUTION, flammable)	RESIN SOLUTION (RESIN SOLUTION, flammable)	RESIN SOLUTION (RESIN SOLUTION, flammable)
Transport document description				
UN 1866 RESIN SOLUTION (RESIN SOLUTION, flammable), 3, III, (D/E)	UN 1866 RESIN SOLUTION (RESIN SOLUTION, flammable), 3, III	UN 1866 Resin solution (RESIN SOLUTION, flammable), 3, III	UN 1866 RESIN SOLUTION (RESIN SOLUTION, flammable), 3, III	UN 1866 RESIN SOLUTION (RESIN SOLUTION, flammable), 3, III
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport


Classification code (ADR) : F1
 Limited quantities (ADR) : 5I
 Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Special packing provisions (ADR) : PP1
 Mixed packing provisions (ADR) : MP19

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According to REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC).

GB PIC Regulation (Prior Informed Consent)

Not applicable.

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (EC 273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Altro Seal Standard Silk Coloured / Altro Seal Vertical Silk Coloured Base

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Full text of H- and EUH-statements:	
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.