



altro

AltroFix™ 30

Two-part polyurethane adhesive

Features and benefits

- Installs in areas up to 90% RH
- Excellent for occupied areas (hospitals, schools)
- Outstanding adhesion in areas with extra heavy traffic and rolling loads or for wet areas.
- Excellent for water spray areas, such as produce departments in grocery stores
- Freeze-thaw stability: 5 cycles at 0° F
- Solvent-free
- Low VOCs less than 12 grams/liter
- Complies with South Coast Air Quality Management District #1168
- FloorScore certified

Applications

AltroFix 30 two-part polyurethane adhesive is recommended for the installation of Altro flooring on clean and dry subfloors, above, on or below grade.

Specifications

AltroFix 30 Part A mixes with Part B to form one gallon of adhesive. Approximate coverage is 150 square feet per gallon depending on porosity of the substrate.

For installation instructions consult the Altro sheet flooring installation guide or adhesive label.

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and subfloor texture and porosity, Altro does not warrant nor guarantee actual adhesive coverages.



LEED facts			
LEED v4	This product may help contribute to the following credits		
AltroFix 30			1
	Environmental quality		1
	Low emitting materials, adhesives		1

Discover more of our sustainability story and credentials at altro.com/sustainability

