

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base
Product code	: SSC_B000
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use, Industrial use
Use of the substance/mixture	: Epoxy Base - Industrial flooring & wall coatings

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Altro Resin Systems
Unit 3 Station Road Industrial Estate
Station Road
GB- DT2 0AE Maiden Newton Dorchester
T 01300 320620
sds@altro.com - www.altro.com

Other

Altro GmbH
Ebertallee 209
06846 Dessau-Roßlau
DE
T +49 (0) 340 6500-0

1.4. Emergency telephone number

Emergency number	: 01462 480480 Monday - Friday 09:00-17:00
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	H319 - Causes serious eye irritation.
	H411 - Toxic to aquatic life with long lasting effects.
	: P261 - Avoid breathing spray, vapours.
	P264 - Wash skin or affected areas. thoroughly after handling.
	P280 - Wear eye protection, protective clothing, protective gloves.
	P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.	
P391 - Collect spillage.	

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700) (25068-38-6)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	≥ 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
BENZYL ALCOHOL	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	$\geq 10 - < 15$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h)
Aerosil R208 substance with national workplace exposure limit(s) (GB)	CAS-No.: 67762-90-7	$\geq 3 - < 5$	Not classified
2-METHOXY-1-METHYLETHYL ACETATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	< 0.1	Flam. Liq. 3, H226 STOT SE 3, H336

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW \leq 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619-26	(5 \leq C \leq 100) Skin Irrit. 2, H315 (5 \leq C \leq 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause redness and soreness of the mouth and throat.

4.3. Indication of any immediate medical attention and special treatment needed

No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing agent suitable for surrounding fire. Use water spray to cool containers.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Fire hazard	: In combustion emits toxic fumes.
-------------	------------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Refer to protective measures listed in Sections 7 and 8.
Emergency procedures	: Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area. Turn leaking containers leak-side up to prevent the escape of liquid.

6.1.2. For emergency responders

No additional information available

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Contain the spilled material by bunding. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect leaking and spilled liquid in sealable containers as far as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid direct contact with the substance. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in a well-ventilated place. Keep cool. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. The floor of the storage room must be impermeable to prevent the escape of liquids.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Skin and body protection:

Avoid contact with skin

8.2.2.3. Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Appearance	: Liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: pH (concentrated solution): 7
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Strong acids. Strong bases. Strong oxidizing agents.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

BENZYL ALCOHOL (100-51-6)	
LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other:
LC50 Inhalation - Rat	> 4178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
LD50 oral rat	> 6190 ml/kg Method: OECD Test Guideline 401
LD50 dermal rat	> 5000 mg/kg Method: OECD Test Guideline 402

Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700) (25068-38-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)

Aerosil R208 (67762-90-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
pH: pH (concentrated solution): 7

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: Causes serious eye irritation. pH: pH (concentrated solution): 7
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

BENZYL ALCOHOL (100-51-6)

NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
----------------------------	---

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

Aspiration hazard : Not classified

BENZYL ALCOHOL (100-51-6)

Viscosity, kinematic	0.005 mm ² /s
----------------------	--------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	

BENZYL ALCOHOL (100-51-6)

LC50 - Fish [1]	460 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76828 mg/l Test organisms (species): other:
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
NOEC chronic crustacea	> 100 mg/l

Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW <= 700) (25068-38-6)

EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
----------------------	--

Aerosil R208 (67762-90-7)

LC50 - Fish [1]	> 10000 mg/l
-----------------	--------------

12.2. Persistence and degradability

BENZYL ALCOHOL (100-51-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

Partition coefficient n-octanol/water (Log Kow)	1.2
Bioaccumulative potential	Bioaccumulation is insignificant.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.
Ecology - waste materials	: Avoid release to the environment.

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code	<p>: HP3 - "Flammable:"</p> <ul style="list-style-type: none"> – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. <p>HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.</p> <p>HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.</p> <p>HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment</p>
---------	---

SECTION 14: Transport information





In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID
14.1. UN number or ID number			
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol))	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol))
Transport document description			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol)), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol)), 9, III, MARINE POLLUTANT	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (Number average MW ≤700), benzyl alcohol)), 9, III
14.3. Transport hazard class(es)			
9	9	9	9

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ADN	RID
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 

Tunnel restriction code (ADR) : -

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

Altro Screed Standard Seal Coat / Altro Screed Slip-resistant Seal Coat Base

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.