

AltroFix™ 75 Spray

California compliant contact adhesive spray

Size: 15 oz (426 g)

Approx. coverage: 32 - 40ft² (9.75 - 12m²) Approx. coverage: 315 lineal ft at 3" band

Product characteristics

AltroFix 75 Spray is a high solids, low VOC, long opentime contact spray adhesive designed to bond Altro Fortis Titantium 15 fire door accessories. It is also to be used on substrates to enhance the bond of double-sided tape used with Altro Whiterock.

Handling and storage

- 2 year shelf life from date of manufacturing.
- Rotate stock to use the oldest material first.
- Freeze/thaw stable; if chilled below 41°F(5°C) agitate well after first warming to 72°F(22°C).
- Store between 50°F(10°C) and 90°F(32°C).
- Keep container tightly closed and store off of the floor when not in use.
- Avoid exposure of canisters to direct sunlight.
- Use at room temperature, 65°F(18°C) or warmer. For best results use above 72°F(21°C).
- Do not apply or make bonds at temperatures below 65°F(18°C).

Advantages

- Low VOC, non-chlorinated California & OTC compliant
- Zero HAPs (Hazardous Air Pollutants)
- · Long open time with aggressive tack
- Outstanding green strength and high heat resistance
- Excellent sprayability
- Portable and convenient

Suitable substrates


The following properly prepared, dry, smooth, flat, dust-free substrates are approved:

- APA grade plywood
- Medium-density fiberboard (MDF)
- Oriented strand board (OSB)
- Metal
- Rigid plastic
- Concrete

Warning: Do not use with unbacked, plasticized vinyls.









Discover more of our sustainability story and credentials at altro.com

