



Altro Wood™ adhesive-free

safety flooring



500 x 100mm

Frosted Oak | AFW280001
WR335 / A1M335 / LRV 52



500x100mm

Timeless Oak | AFW280007
WR347 / A1M347 / LRV 38



Adhesive-free flooring
- swatch shows underside emboss of Altro Wood adhesive-free.
Reusable and recyclable post-use.



WR84 / A1M84 / LRV 23

Champagne Oak | AFW280010
WR338 / A1M338 / LRV 38



500 x 100mm

Summer Oak | AFW280005
WR340 / A1M340 / LRV 37



1000 (550/450) x 100mm

Honey Maple | AFW280011
WR352 / A1M352 / LRV 27



1000 (550/450) x 100mm

Imperial Walnut | AFW280009
WR341 / A1M160 / LRV 15



500 x 100mm

Caramel Oak | AFW280006
WR353 / A1M225 / LRV 25



1000 (550/450) x 100mm

Soft Maple | AFW280002
WR339 / A1M339 / LRV 24



1000 (550/450) x 100mm

Shaded Cherry | AFW280004
WR337 / A1M337 / LRV 17



1000 x 125mm

Vintage Oak | AFW280012
WR322 / A1M239 / LRV 19



1000 (550/450) x 100mm

Dusky Cherry | AFW280003
WR336 / A1M239 / LRV 22



500 x 100mm


Pitch Oak | AFW280008
WR348 / A1M348 / LRV 7



Typical applications

Bedrooms in care homes and hotels. Reception areas in care homes and kindergartens. Corridors, general circulation and public areas in hospitals, care homes, kindergartens and schools. Wards, waiting and treatment rooms in hospitals and care homes. As an alternative to LVTs in student accommodation. Common room / staff rooms in schools. Café / dining areas.

Technical information

	Fire behaviour tested in acc. with Classified in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 4.5 kW/m ² Pass C _{fl} -s1
	Slip resistance	EN 13893 PTV DIN 51130 / BGR 181 EN 13845 Annex C	≥ 0.30 / DS P3 R10 ESf
	Sound insulation	EN ISO 10140	ca. 14 dB
	Flooring type	EN 651	Safety flooring
	Thickness	EN ISO 24346	2.4 mm
	Wear layer thickness	EN ISO 24340	0.7 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m ²
	Weight	EN ISO 23997	2.4 kg/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
	Classification for use	EN ISO 10874	34, 42
	Flexibility	EN ISO 24344	Pass
	Light fastness	EN ISO 105-BO2	≥ 6
	Castor chair abrasion	EN 425	Yes, type W
	Wear resistance	EN 660-2	Group T
	Chemical resistance	EN ISO 26987	Good
	Under floor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore Indoor Air Comfort Gold	Approved Approved



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



20 | debolon dessauer bodenbeläge GmbH & Co. KG,
Ebertallee 209, D-06846 Dessau-Roßlau | EN 651 |
DoP-No. RN-A034 | Reaction to fire: Cfl-s1 | Slip resistance: DS |
Formaldehyde: E1 | Electrical behaviour: EN 1815 < 2 kV |
EN 14041:2004/AC:2006 | 1658 |
Resilient floor covering to be used within a building



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



Sustainability



*A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at www.altro.com

 Altro, Designed for possibilities. Made for people. Altro Wood adhesive-free and Altro Easyclean technology are trademarks of Altro Limited.

United Kingdom

+44 (0) 1462 707 700

enquiries@altro.com

Australia

+61 3 9764 5666

info@asf.com.au