



Designed for possibilities.
Made for people.

Altro Transflor Metris™ Custom

Typical applications:

Executive sedans, coach, shuttle, trolley, specialty vehicles, mobility vehicles, people movers.

Discover Altro Transflor Metris Custom for a difference that's clear.

Altro now offers digitally printed floors for bus and coach. Altro Transflor Metris Custom gives you the widest choice of standard designs available in the transport market, developed in collaboration with industry design experts, or the option to create your own custom design for your vehicle, all printed using our in-house state of the art digital printing technology.

See, hear, and feel the difference: See your design come to life in outstanding high-definition print quality. Staff and passengers alike will feel the luxurious comfort underfoot, giving a private travel luxury feel to your vehicles, and with 15dB acoustic performance, enjoy softened engine and road noise. Altro Transflor Metris Custom is also the lightest acoustic floor available for transport applications, making it easier for operators to reach decarbonization targets.

Altro Transflor Metris Custom is available with our self-adhesive, pre-cut flooring service, and reverse welding services

For more information contact your Altro representative.

*Self-adhesive, reverse welding, and water-resistant laminated logo services for Altro Transflor Metris Custom rendered overseas prior to delivery.

lightweight safety flooring for the transit industry

Altro Transport Division 12648 Clark Street Santa Fe Springs, CA 90670

Altro reserves the right to change any information. Please consult altro.com or your local Sales Representative for the latest product range information.

 USA 800.382.0333  CANADA 800.565.4658  transflor@altro.com  altro.com/us/transport



Arrow 1 (small)
DPSMT0101



Arrow 2 (small)
DPSMT0102



Arrow 3 (larger)
DPSMT0103



Arrow 4 (large)
DPSMT0104



Checker plate 1
DPSMT0105



Checker plate 2
DPSMT01060




Chrome transition
DPSMT382307CH




Geometric 1
DPSMT0109




Geometric 2
DPSMT0110




Glass stripes 1
DPSMT0107




Glass stripes 2
DPSMT0108



Rectangle flash 1
DPSMT0111



Rectangle flash 2
DPSMT0112



Cobbles 1
DPSMT0054




Grass 1
DPSMT0059



Paving 2
DPSMT0056



Pebbles 1
DPSMT0067



Sand 1
DPSMT0052



Water 1
DPSMT0072

Learn more > altro.com/metris-custom



LRV = Light Reflectance Value
AM = Mastic
WR = Weld rod



Color matched Weldrods (WR) and
Mastics (AM) are available. You'll
find their product codes under
product SKUs.



All products available in roll and kit
format. Custom colors are
also available.



Samples
Experience has shown that
printing cannot reproduc
colors accurately.
If color choice is critical please
request a sample of the material.

Dimensions	6'7" x 65'7" / 2 m x 20 m
Thickness	2.85 mm
Weight	2.60 lb/sy
Format	ROLL, PRE-CUT, SELF ADHESIVE, BACK WELDED, LAMINATED LOGOS



Typical applications / Zonas de instalación recomendadas

Autonomous vehicle. City bus. Coach. Light commuter buses. Public service vehicles. Shuttle buses.

Vehículo autónomo. Autobus urbano. Autocares. Vehículos de servicio público. Autobuses lanzadera.

Technical information / Información técnica

	Flooring type	Tipo de pavimento	EN ISO 11638 ASTM F1303	Altro Transflor Metris Heterogeneous floor / Suelo heterogéneo Altro Transflor Metris Type I / Grade 1 / Class A
	Fire performance	Reacción al fuego	ECE R-118 FMVSS 302 / CMVSS 302	Pass / Bestanden / Conforme
	Slip resistance	Resistencia al deslizamiento	EN 13893 PTV ASTM D2047 EN 16165 Annex B / ASR A1.5	DS ≥ 36 ≥ 0.6 R10
	Impact sound insulation	Aislamiento acústico de impactos	EN ISO 10140-3	ca. 15 dB
	Airborne sound insulation	Aislamiento acústico aéreo	EN ISO 10140-2	ca. 23 dB
	Thickness	Espesor total	EN ISO 24346	2.85mm / 0.11"
	Wear layer thickness	Capa de uso	EN ISO 24340	0.7 mm / 0.027"
	Flexibility	Flexibilidad	EN ISO 24344 ASTM F1303	Pass / Conforme
	Thermal conductivity	Conductividad térmica	EN 12667	0.108 W/mK
	Dimensional stability	Estabilidad dimensional	EN ISO 23999	≤ 0.4%
	Weight	Peso	EN ISO 23997	2.6 kg/m² / 4.79 lb/sy
	Roll dimensions	Dimensiones del rollo	EN ISO 24341	2 m x 20 m = 40 m² 6'7" x 65'5"
	Light fastness	Resistencia a la luz	EN ISO 105-B02	≥ 6
	Wear resistance	Abrasión	EN 660-2	Group T / Grupo T
	Residual indentation	Punzonamiento	EN ISO 24343-1 ASTM F970	≤ 0.20 mm
	Chemical resistance	Resistencia a los productos químicos	EN ISO 26987	Good / Buena
	Castor chair abrasion	Huellas de sillas de ruedas	ISO 4918	Yes, type W / Si, tipo W
	Electrical behaviours	Características electroestáticas	EN 1815	≤ 2 kV, antistatic / ≤ 2 kV, antiestáticas



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



Sustainability / Sostenibilidad

Installation and maintenance / Verlegung und Pflege / Instalación y mantenimiento

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance and may affect or invalidate Altro's product guarantee. Technical information on installation and maintenance (including cleaning and staining) can be found at www.altro.com

Consulte las instrucciones de instalación y mantenimiento de Altro. El incumplimiento de estas instrucciones puede afectar al rendimiento del producto y puede afectar o invalidar la garantía del producto de Altro. Encontrará información técnica sobre la instalación y el mantenimiento (incluida la limpieza periódica y específica) en www.altro.com