



altro

Cleaning guide for smooth sheet floors

Altro Symphonia, Altro Cantata, Altro Orchestra, Altro Operetta, Altro Serenade, Altro Wood, Altro Wood Comfort, Altro Wood Acoustic, Altro Wood adhesive-free, Altro Zodiac Smooth

Develop a regular cleaning program suited to the usage and traffic of the area - Heavily trafficked or highly visible areas need to be cleaned more often than areas which are seldom used, or where appearance is less important. The best and most cost effective method of cleaning Altro flooring is by an auto scrubbing machine. Care should be taken to select the correct pad.

Use recommended cleaning chemicals - Use only recommended cleaning products or their equivalent in the correct dilution. Do not mix two different cleaning liquids together, and always follow the manufacturer's instructions. Always check the suitability of cleaners for use on vinyl floors. Do not use cleaner containing pine oil or phenolic sanitizer.

Remove scuff marks regularly - To remove any rubber heel marks by abrasion, use the correct machine pad or scrub by hand. For areas requiring renovation due to neglect or heavy soiling, consult Altro Technical Services.

Protect newly installed floors - All newly installed Altro flooring should be covered and protected from all other trades with a suitable non-staining protective covering, such as Masonite™ or Ram Board®.

Dirt control - 80% of the dirt in a building is carried in on shoes. A suitable dirt excluder outside all entrances and a mat inside just prior to the flooring will protect it. Mats should be regularly cleaned to maintain their effectiveness. Dust control mops are also useful.

Some materials are known to cause staining on vinyl floors. Typical examples include:

- Asphalt and bitumen materials
- Cardboard/Hardboard (wet)
- Fire treatment and maintenance materials used on carpets could transfer to vinyl flooring and cause staining
- Dyes from printed literature or packaging
- Rubber-backed carpets and rubber mats
- Rubber furniture rests and wheels
- Shoe soles not made from non-staining materials
- Heat degradation
- Some chemicals used in cleaners (e.g. pine oil) and disinfectants

Initial maintenance

1. Do not begin any maintenance procedure until all adhesives have set (excluding Altro XpressLay and loose lay floors that do not require the use of adhesive), generally 72 hours after the completion of the installation.
2. Sweep and vacuum floor surface to remove all loose dust and debris.
3. Apply diluted* AltroClean 44™ to the floor. Allow to sit for five minutes to allow the cleaner to attack the surface soil.
4. Alternatively AltroClean 44 Plus can be used for extra heavy cleaning, heavy oil and grease removal, and in cases where stripping is required, consult technical services for additional information
5. Scrub floor with an automatic scrubber (3-in-1 machine) or a standard low-speed swing machine (150rpm to 350rpm) fitted with an Altro Unipad™.
6. If using a standard low-speed swing machine, remove wash water with a wet vac. Ensure the floor is thoroughly rinsed with fresh, clean water. No cleaning residue should remain on the floor.
7. Allow surface to dry before use.

* Dilution rates depend on the condition of the floor. For moderate soiling use a 1:40 dilution ratio. For heavy soiling use 1:10.

Before beginning routine maintenance ensure that the construction process is completed and that initial maintenance has been performed.

Maintenance without finish

Using a low-speed swing machine

1. Sweep or vacuum floor surface to remove all loose dust and debris.
2. Add AltroClean 44 in a 1:40 dilution rate into a mop bucket.
3. Mop the floor with the diluted AltroClean 44 solution and allow a few minutes for the cleaner to attack the surface soil.

4. Scrub with low-speed swing machine using an Altro Unipad or white, fine nylon pad.
5. Remove excess liquid from floor using a wet vac.

Using an auto scrubber

1. Sweep and/or vacuum floor surface to remove all loose dust and debris.
2. Add AltroClean 44 in a 1:40 dilution rate into the auto scrubber.
3. Fit auto scrubber with white, fine, nylon pads and scrub floor.

Maintenance with finish

Follow initial maintenance procedure outlined above.

1. Once floor is dry, apply two coats of Johnson Over & Under®. This will seal the floor and only needs to occur once.
2. Allow floor to dry.
3. Apply two coats of Johnson Carefree Matte™ floor finish for the desired low gloss look. (2,000 square feet per gallon). Allow the finish to become dry to the touch, around 45 - 60 minutes, before applying the second coat.
4. Apply no more than 2 coats within a 24 hour time period.
5. For routine maintenance, sweep/vacuum floor to remove all loose dust and debris then damp mop or machine scrub using Johnson Stride™ according to label instructions.
6. Use an auto scrubber fitted with an Altro Unipad or any standard low-speed swing machine.
7. Be sure to remove all wash water and cleaning residue from floor.
8. Allow surface to dry before use.

* Dilution rates depend on the condition of the floor. For moderate soiling use a 1:40 dilution ratio. For heavy soiling use 1:10.

Recommended maintenance products

Cleaners	
AltroClean 44	altrostore.com

Alternative products can be used that are intended for sheet vinyl flooring. Consult the manufacturer of the product to determine suitability.

Disinfectants	
Virex 128	Floor Guy
PerDiem	Floor Guy
VIROX 5	Floor Guy

Initial Seal (optional)	
Diversey Over & Under	Floor Guy

Alternative products can be used that are intended for sheet vinyl flooring. Consult the manufacturer of the product to determine suitability.

Equipment	
Altro Unipad*	Altro

Alternative equipment can be used that are intended for sheet vinyl flooring. Consult the manufacturer of the equipment to determine suitability.

High quality cleaning chemicals and equipment ensure efficient maintenance and represent only a small proportion of maintenance costs.

Altro Unipads are highly recommended for cleaning Altro flooring and are available for both manual and machine cleaning.

They are offered in two sizes; Manual - 4" x 14" Flat and Machine - 17" Round.

Visit us on altrostore.com to purchase cleaners and maintenance products.