



the future is safer with altro

altro

Altro Nuvola Stratus™


Rubber Flooring / Suelos de caucho / Kautschukbodenbeläge



Pearl ANS2750007
LRV45




Gravel ANS2750008
LRV20




Charcoal ANS2750009
LRV11



Graphite ANS2750010
LRV7




Parsley ANS2750005
LRV12




Chateau ANS2750011
LRV21



Orca ANS2750006
LRV5



Peacock ANS2750004
LRV18



Sapphire ANS2750012
LRV8



Crocus ANS2750013
LRV9



Mustard ANS2750003
LRV37



Orange ANS2750002
LRV26




















Tomato ANS2750001
LRV14

Light Reflectance Values measured in accordance with BS8493:2008. Exact material match with samples cannot be guaranteed. No podemos garantizar que el material del suelo de seguridad coincida exactamente con el de las muestras. Eine exakte Übereinstimmung des materials mit mustern kann nicht garantiert werden.

Codes: **WR** = weld rod, **LRV** = light reflectance value.
Códigos: **WR** = Cordón de soldadura, **LRV** = Valor de reflectancia de la Luz.
Abkürzungen: **WR** = Schweißschnüre, **LRV** = Lichtreflexionswert



A+ BRE generic green fuid
rating for rubber flooring,
full details available at
www.thegreenguide.org.uk

Flooring type Tipo de pavimento Belagsart		EN 12199	Rubber flooring Suelo de caucho Kautschukbodenbeläge
Classification for use Areas de uso Einsatzbereiche		EN 685	23, 32 and 41 23, 32 y 41 23, 32 und 41
Slip resistance Resistencia al deslizamiento Rutsicherheit		EN 13893	DS
Thickness Espesor total Gesamtdicke		EN 428	2.7 mm
Wear layer Capa de uso Nutzschicht		EN 429	2.7 mm
Weight Peso Flächengewicht		EN 430	3.8 kg/m ²
Tile dimensions Loseta dimensiones Fliesenabmessungen		EN 426	500mm x 500mm
Light fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	≥6
Sound insulation Aislamiento acústico Trittschall		EN ISO 10140-3	8 dB
Wear resistance Abrasión Verschleißverhalten		ISO 4649	≤ 250mm ³
Indentation Punzonamiento Resteindruck		EN 433	≤ 0.20mm
Fire performance Reacción al fuego Brandverhalten		EN 13501-1	Class Bfl s1 Clase Bfl s1 Klasse Bfl-s1
Chemical resistance Resistencia a los productos químicos Chemikalieneinwirkung		EN 423	Good Buena Beständig
Castor chair abrasion Huellas de ruedas de sillas Stuhlrollenbeanspruchung		EN 425	Pass Conforme Geeignet
Under floor heating Calefacción por el suelo Fußbodenheizung		DIN 52612	Suitable Apto Geeignet
Electrical behaviours Características eléctricas Elektrisches Verhalten		EN 1815	≤ 2kV Antistatic ≤ 2kV Antiestáticas ≤ 2kV antistatisch
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme Bestanden

Installation and Maintenance

All installations in accordance with code of practice BS 8203:2001, and Altro rubber installation instructions. Subfloor as code of practice, with effective DPM where necessary. Adhesives as recommended in Altro rubber flooring installation instructions, the Altro price list or visit www.altro.com.

N.B. Failure to install and maintain Altro flooring in accordance with Altro's instructions can affect the performance of the product.

Floors should be protected from other trades and thoroughly cleaned before handover. All information is correct at the time of print and is subject to change without prior notice. Visit us at www.altro.com for more information and updates.



Gulvbranchen

Garanti for gode gulve



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.

