



















**Altro Pisces™** Patent No. GB 2 462 167 Patent No. GB 2 496 644

Flooring type		EN 13845 / EN 13553	Safety flooring
Classification for use		EN 685	34 & 43
Slip resistance		PTV EN 13845 EN 13893 DIN 51130	≥ 50 (Slider 96) ESf & ESb DS R11 Class B
Thickness		EN 428	2 mm
Wear layer		EN 429	2 mm
Flexibility		EN 435	Pass
Weight		EN 430	2.6 kg/m <sup>2</sup>
Roll dimensions		EN 426	2.0m x 20.00m - 40m <sup>2</sup>
Light fastness		EN 20105-B02	≥6
Sound insulation		ISO 140-8	5 dB (subject to validation)
Wear resistance		EN 13845	≤10% particles lost over 50000 cycles
Indentation		EN 433	≤ 0.10mm
Fire performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m <sup>2</sup> pass
Chemical resistance		EN 423	Good
Castor chair abrasion		EN 425	Pass
Under floor heating		EN 12667	Suitable
Electrical behaviours		EN 1815	≤ 2kV Antistatic
VOC emissions		Section 01350	Pass