

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 06/07/2023 Revision date: 06/07/2023 Supersedes version of: 19/09/2016 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Altro Seal Standard Clear, Altro Seal Standard Coloured, Altro Seal Slip-resistant and Altro

Seal Vertical Hardener

Product code : SDDH
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

Use of the substance/mixture : Polyurethane Hardener - Industrial floor coating

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SupplierOtherAltro Resin SystemsAltro GmbHUnit 3 Station Road Industrial EstateEbertallee 209Station Road06846 Dessau-Roßlau

GB- DT2 0AE Maiden Newton Dorchester

T 01300 320620 T +49 (0) 340 6500-0

sds@altro.com - www.altro.com

1.4. Emergency telephone number

Emergency number : 01462 480480

Monday - Friday 09:00-17:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3

Acute toxicity (inhalation:dust,mist) Category 4

Skin corrosion/irritation, Category 2

H315
Serious eye damage/eye irritation, Category 2

H319
Skin sensitisation, Category 1

H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Specific target organ toxicity – Repeated exposure, Category 2 H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

307 GHS

Signal word (CLP) : Warning

Contains : hexamethylene-1,6-diisocyanate homopolymer; Reaction mass of ethylbenzene and xylene

Hazard statements (CLP) : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing spray, vapours.

P264 - Wash Skin or affected areas thoroughly after handling.

P280 - Wear protective clothing, eye protection, face protection, protective gloves. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.

P501 - Dispose of contents and container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

: As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Extra phrases

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hexamethylene-1,6-diisocyanate homopolymer	CAS-No.: 28182-81-2 EC-No.: 931-274-8 REACH-no: 01-2119488934- 20	≥ 75	Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Sens. 1, H317 STOT SE 3, H335
2-METHOXY-1-METHYLETHYL ACETATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	≥ 10 – < 15	Flam. Liq. 3, H226 STOT SE 3, H336

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction mass of ethylbenzene and xylene	REACH-no: 01-2119488216- 32	≥ 10 - < 15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Take off all contaminated clothing and wash its before reuse.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek

medical advice.

First-aid measures after skin contact : Take off contaminated clothing. Gently wash with plenty of soap and water. If skin irritation

or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Get medical advice/attention if you feel

unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes eye irritation. redness, itching, tears. Symptoms/effects after ingestion : May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2). Dry powder. Foam. In case of a larger fire, water spray should be

used.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Fire hazard : On burning: release of toxic gases/vapours. Carbon oxides (CO, CO2). Nitrogenous

substances. Isocyanate vapors and traces of hydrogen cyanide. In case of fire and/or

explosion do not breathe fumes.

5.3. Advice for firefighters

Firefighting instructions : Control run-off water by containing and keeping it out of sewers and watercourses.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling)

and collect in suitable container for disposal. This material and its container must be

disposed of in a safe way, and as per local legislation.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide local exhaust or general room ventilation. Avoid contact with skin and eyes.

Contaminated work clothing should not be allowed out of the workplace. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when

leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in original container. Keep cool. Store in

a dry place. Store in a closed container. Store in a well-ventilated place. Keep container

tightly closed.

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	274 mg/m³
WEL STEL (OEL STEL)	548 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, oral	500 mg/kg bodyweight/day	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	33 mg/m³	
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
Long-term - local effects, inhalation	33 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.635 mg/l	
PNEC aqua (marine water)	0.0635 mg/l	
PNEC aqua (intermittent, freshwater)	6.35 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.29 mg/kg dwt	
PNEC sediment (marine water)	0.329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
hexamethylene-1,6-diisocyanate homopolymer (28182-81-2)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	1 mg/m³	
Long-term - local effects, inhalation	0.5 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.127 mg/l	
PNEC aqua (marine water)	0.0127 mg/l	
PNEC aqua (intermittent, freshwater)	1.27 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	266701 mg/kg dwt	
PNEC sediment (marine water)	26670 mg/kg dwt	
PNEC (Soil)		
PNEC soil	53183 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	88 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Skin and body protection:

Avoid contact with skin

Hand protection:

Standard EN 374 - Protective gloves against chemicals.

Other skin protection

Materials for protective clothing:

Keep work clothing separately

8.2.2.3. Respiratory protection

Respiratory protection:

Wear suitable respiratory equipment in case of insufficient ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour Not available Appearance Colourless liquid. Odour : Not available Odour threshold Not available Melting point : Not available Freezing point Not available Boiling point Not available Flammability : Not available **Explosive limits** : Not available Lower explosion limit : Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Upper explosion limit : Not available Flash point : 38 °C Auto-ignition temperature : Not available : Not available Decomposition temperature : Not available : Not available Viscosity, kinematic Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure Vapour pressure at 50°C : Not available Density : Not available Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Not known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Altro Seal Standard Clear, Altro Seal Standard Coloured, Altro Seal Slip-resistant and Altro Seal Vertical Hardener

ATE CLP (dust,mist) 1.714 mg/l/4h

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LD50 oral rat > 6190 ml/kg Method: OECD Test Guideline 401

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

LD50 dermal rat	> 5000 mg/kg Method: OECD Test Guideline 402	
hexamethylene-1,6-diisocyanate homopolymer (28182-81-2)		
LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:	
Reaction mass of ethylbenzene and xylene	е	
LD50 oral rat	3523 mg/kg	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: May cause respiratory irritation.	
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
hexamethylene-1,6-diisocyanate homopol	ymer (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.	
Reaction mass of ethylbenzene and xylene	e	
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.	
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)	
Reaction mass of ethylbenzene and xylene		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard	: Not classified	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

Not rapidly degradable

2-METHOXY-1-METHYLETHYL ACETATE (108	3-65-6)
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes

06/07/2023 (Revision date) GB - en 8/13

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)			
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)		
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'		
NOEC chronic crustacea	> 100 mg/l		
hexamethylene-1,6-diisocyanate homopolyme	hexamethylene-1,6-diisocyanate homopolymer (28182-81-2)		
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): other:		
Reaction mass of ethylbenzene and xylene			
LC50 - Fish [1]	2.6 mg/l Test species:- Rainbow trout		
EC50 - Crustacea [1]	1 mg/l Test Species:- Daphnia magna (24 hrs)		
EC50 72h - Algae [1]	2.2 mg/l Test species:- Green algae		
NOEC chronic fish	> 1.3 mg/l Rainbow Trout (56 days)		
NOEC chronic crustacea	1.17 mg/l Ceriodaphnia dubia (7 day)		
NOEC chronic algae	0.44 mg/l Green algae		

12.2. Persistence and degradability

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
Partition coefficient n-octanol/water (Log Kow) 1.2		
Bioaccumulative potential	Bioaccumulation is insignificant.	
Reaction mass of ethylbenzene and xylene		
BCF - Fish [1]	25.9 Rainbow Trout - COVESTRO MSDS - (V14) 23/08/2022	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Waste treatment methods HP Code

- : Disposal must be done according to official regulations.
- : Must follow special treatment according to local regulation.
- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
 - HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
 - HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
 - HP13 "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.

SECTION 14: Transport information

In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID
4.1. UN number or ID numb	per		
UN 1866	UN 1866	UN 1866	UN 1866
14.2. UN proper shipping na	me		
RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION	RESIN SOLUTION
Transport document description	n		
UN 1866 RESIN	UN 1866 RESIN SOLUTION, 3, III	UN 1866 RESIN	UN 1866 RESIN
SOLUTION, 3, III, (D/E)		SOLUTION, 3, III	SOLUTION, 3, III
14.3. Transport hazard class	s(es)		
3	3	3	3
3	3	3	3
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards	6		
Dangerous for the	Dangerous for the environment: No	Dangerous for the	Dangerous for the
environment: No	Marine pollutant: No	environment: No	environment: No

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions : TP1

(ADR)

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30

Orange plates

30 1866

Tunnel restriction code (ADR) : D/E EAC code : •3Y

Transport by sea

: 223, 955 Special provisions (IMDG) Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : P001, LP01 Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2 Tank special provisions (IMDG) : TP1 : F-E EmS-No. (Fire) : S-E EmS-No. (Spillage) Stowage category (IMDG) : A

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions : TP1

(RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colis express (express parcels) (RID) : CE4 Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H373	May cause damage to organs through prolonged or repeated exposure.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.