

## **Altro Orchestra**

For areas where comfort and sound reduction are important, 2.85mm Altro Orchestra has been engineered to create the ideal environment to heal, learn and live. Low residual indentation facilitates the flexible use of equipment and furniture, including hospital beds. At the same time, the integrated impact sound insulation system cuts impact sound by up to 15dB.

This range offers comfort underfoot, making life easier on the feet of students, patients and hard-working staff who spend countless hours on the move.

With a palette of designs varying from calming neutrals reflecting tones of nature to vibrant shades, Altro Orchestra allows you to create the right atmosphere every time. It coordinates with Altro Operetta and Altro Serenade for a complete look throughout. Altro Orchestra also looks great paired with Altro Wood.

## Typical applications

Healthcare, senior living, education, retail, offices, light gym and recreational areas

#### Features + benefits

- Provides ample comfort underfoot
- 15dB sound reduction
- Resists up to 1,000 psi indentation
- Colors coordinate with Altro Operetta and Altro Serenade ranges for a complete look throughout
- FloorScore Certified / Low VOCs

## Better together

Smooth flooring from Altro gives you what you want - an economical and attractive look that's easy to install and maintain. But, in commercial areas with frequent spillages and hygiene and durability concerns, it's best to let our robust collection of safety flooring, slipresistant flooring and wall cladding join the team!

Install smooth flooring in the dining room and public areas, and bring safety flooring and wall protection into the kitchen, bar and restrooms. You will rest easy knowing your patrons will have an exquisite experience while the most dangerous areas in your facility are well equipped to handle the tolls of the day.

We strongly recommend carrying out a risk assessment in any area in which the installation of smooth flooring is considered, focusing on the potential risk posed by contaminants.

## Altro Easyclean Technology EASYCLEAN



Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance for the lifetime of the product.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention


























# Altro Orchestra special order colors


The following colors of Altro Orchestra are also available by special order only. While we may have inventory of these colors we do not guarantee local stock availability at all times. If a color is not currently stocked in North America, your order must meet minimum material requirements. Contact an Altro representative for details.



Falstaff CH2846U WR493 / A1M493 LRV 9



**Volta** CH2851U WR518 / A1M335 LRV 48



**Porter** CH2854U WR498 / A1M483 LRV 43




 Woodwind
 CH2843U

 WR489 / A1M385
 LRV 45



Musette CH2856U WR515 / A1M136 LRV 49



**Timpani** CH2861U WR504 / A1M417 LRV 20




 Marimba
 CH2863U

 WR505 / A1M390
 LRV 30



 Carlotta
 CH2865U

 WR507 / A1M337
 LRV 26



Fidelio CH2868U WR509 / A1M85 LRV 35



**Elektra** CH2870U WR511 / A1M392 LRV 58



 Bassoon
 CH2831U

 WR452 / A1M84
 LRV 17

Type + class		ASTM F1303	Type I, Grade 1, Class A, smooth flooring
Thickness and wear layer		2.85mm   .11" / .7mm / 28 mil wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5"   2m x 20m	
Weight		4.79 lbs./yd   2.6 kg/m   230 lbs. per roll	
Warranty	10 year reduct sumsets	10 years	
Cleaning technology	das Clean	Altro Easyclean	
Static coefficient of friction	.7	ASTM D2047	.7 dry, .8 wet
Dynamic coefficient of friction	.49 <b>DCOF</b>	ANSI/NFSI B101.3	.49 wet DCOF
Ramp test	<b>R</b> <sub>10</sub>	DIN 51130	R10
Static load limit	A	ASTM F970	1000 psi
Indentation		EN 433	≤ 0.20mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness	7	EN 105-B02	≥ 6
Sound insulation	(((©	ISO 10140	15dB
Electrical behaviors	<b>7</b> 2 Å ≈2.0 kV	EN 1815	≤ 2kV Antistatic
Fire and smoke performance	8	CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions	floor score	CA 01350 FloorScore	Pass Certified
Bio-based content	bio-best content	Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content	d'inoicio/tree	Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing.  Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Slightly blown PVC with black fleece backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures, training clinic information and information on the proper care of our flooring is available at www.altro.com. Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Orchestra and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation.

Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.

© Copyright Altro USA 2023



Discover more of our sustainability story and credentials at altro.com







Order samples 24 hours a day at altro.com and materialbank.com

#### Discover more online!



Maintenance guides



Illus. cleaning guides



Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

### Even more great resources!

- BIM components
- CSI/CSC specifications
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries www.altropics.com
- Solutions by area type ORs, labs and cleanrooms, kitchens, senior living and more!

#### Follow us



- **USA** 800 377 5597
- **♥ CANADA** 800 565 4658
- www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information