



altro

For areas requiring advanced cleaning due to neglect or heavy soiling consult the Altro technical services department or 1877FloorGuy.com

Maintenance guide for LVT floors

Altro Lavencia Plus and Altro Lavencia Click

Recommended cleaners	
AltroClean 44	Altro, Floor Guy
Diversey Stride	Floor Guy
Profi Floor Cleaner	Floor Guy
Recommended cleaner/maintainer	
AltroClean 48W	Altro, Floor Guy
Taski Wiwax	Floor Guy
Recommended finishes	
Diversey Carefree Matte	Floor Guy
Diversey Complete	Floor Guy
Equipment	
Altro Unipad**	Altro, Floor Guy
3M Floor Machine Pads	Floor Guy
Flo-Pac Swivel Scrub	Carlisle, Floor Guy
Deck Brush	Carlisle, Floor Guy
Taski Machines	Diversey, Floor Guy
Auto Scrubbers	Diversey, Floor Guy
Nilfisk	Advance Co., Floor Guy
Where to purchase cleaners / finishes / equipment	
Altro	800.377.5597, altro.com
Floor Guy	877.FLOOR.GUY, 1877floorguy.com
Carlisle	888.654.8210, carlislefsp.com
Diversey	888.352.2249, taskibydiverse.com
Advance Co.	800.989.2235, advance-us.com

**Altro Unipads are highly preferred for cleaning Altro flooring and are available for both manual and machine cleaning.

Manual - 4" x 14" flat, Machine - 17" round

Initial maintenance

1. Do not begin any maintenance procedure for at least 72 hours after installation.
2. Sweep or vacuum floor surface to remove all loose dust and debris.
3. Prepare cleaning dilution with fresh, warm water and AltroClean 44. A dilution rate of 1:40 (or up to 1:10 for heavy soiling) may be used. **DO NOT FLOOD THE FLOOR.**
4. Scrub with an auto scrubber (3 in 1 machine) or a standard low speed swing machine (150rpm to 350rpm) fitted with an Altro Unipad or equivalent pad.
5. If using a standard low-speed swing machine, remove wash water with a wet vac. Ensure the floor is thoroughly rinsed with fresh, clean water. No cleaning residue should remain on the floor.
6. Allow surface to dry thoroughly before use.

Regular maintenance

1. Sweep/vacuum floor to remove all loose dust and debris.
2. Choose a maintenance method below (with finish / without finish)

Routine maintenance with finish

1. Using AltroClean 44 dilution of 1:40 (or up to 1:10 for heavy soiling), hand scrub or machine scrub.

If hand scrubbing - mop the floor with the cleaner and allow a few minutes for the cleaner to attack surface soils before scrubbing.

If machine scrubbing - Ensure that you are following directions outlined by the machine's manufacturer.

2. Remove wash water with a wet vac or dry mop. Ensure the floor is thoroughly rinsed with fresh, clean water. No cleaning residue should remain on the floor.
3. Allow surface to dry thoroughly.
4. Apply up to 2 coats of finish to floor.
5. For additional protection in areas where staining agents are used (salons, labs), for a higher gloss level or for areas maintained with high speed and ultra high speed buffing equipment apply additional

Additional tips can be found on the next page.



coats of finish until desired amount is achieved.

6. Allow finish to become dry to the touch (45-60 minutes) in-between coats. Apply no more than 2 coats within 24 hours.
7. Allow floor to dry thoroughly before trafficking.

Routine maintenance without finish

Using an auto scrubber

1. Add dilution to auto scrubber. Dilution consists of 1 part AltroClean 48W to 40 parts clean, warm water. For heavily soiled floors; Use 1 part AltroClean 48W to 10 parts clean, warm water.
2. Fit auto scrubber with white, fine, nylon pads and scrub floor.
3. If a higher gloss look is desired, wait for the floor to dry thoroughly then apply a fine spray of the AltroClean 48W dilution. Buff to a shine using a low speed swing machine (150rpm to 350rpm) fitted with a white, fine nylon pad.

Using a low speed swing machine

1. Dilute cleaner and place in mop bucket. Dilution consists of 1 part AltroClean 48W to 40 parts clean, warm water. For heavily soiled floors; use 1 part AltroClean 48W to 10 parts clean, warm water.
2. Mop the floor with the solution and allow a few minutes for the cleaner to attack the surface soil.
3. Scrub with low speed swing machine (150rpm to 350rpm) using an Altro Unipad or white, fine nylon pad.
4. Remove wash water with a wet vac. Ensure the floor is thoroughly rinsed with fresh, clean water. No cleaning residue should remain on the floor.
5. If a higher gloss look is desired, wait for the floor to dry thoroughly then apply a fine spray of the AltroClean 48W dilution. Buff to a shine using a white, fine nylon pad.

Maintenance tips

Color selection

The importance of color selection cannot be overstated. Careful consideration must be given before choosing a color.

- Light colors will show more dirt and sole scuffs.
- Dark colors will show more scratching and abrasion.
- Medium tones are best in high traffic areas.
- Maintain light and dark colors using the preferred maintenance with finish protocols.

Protect floors during construction

All newly laid floor surfaces should be covered and protected from other trades during construction with a suitable non-staining, non-taped, protective covering.

Develop a regular cleaning program suited to traffic

Heavily trafficked, high visibility areas, or in areas where staining agents are to be used (salons, labs) your flooring will need to be cleaned more often. It will also perform better, in these areas, using the preferred maintenance with finish program and opting to add additional protective finish coats as needed. Additionally, it is also important to remove rubber sole scuffs regularly, whether by hand or with mechanical scrubber.

Use recommended cleaning chemicals correctly

Use only preferred cleaning liquids. Always follow manufacturer's instructions including the correct dilution ratio. Always spot check the suitability of cleaners on vinyl floors prior to initial maintenance. Do not mix two different cleaning liquids together. Do not use cleaner containing pine oil or phenolic sanitizer.

Scratching and abrasion

Scratching, scuffing, and gouging is a natural occurrence on all floors. It can be reduced with proper and adequate furniture rests and chair feet, proper maintenance, maintaining with finish, adequate dirt control and correct color selection.

Dirt control

A suitable dirt excluder outside all entrances and an entry mat will help protect flooring. Mats should be regularly cleaned to maintain their effectiveness.

Materials known to stain vinyl flooring

- Asphalt and bitumen materials
- Cardboard / hardboard (wet)
- Some fire-retardant treatments used on carpets
- Dyes from printed literature or packaging
- Rubber-backed carpets and rubber mats
- Rubber furniture rests and wheels
- Shoe soles not made from non-staining materials
- Heat degradation
- Chemicals used in cleaners e.g. pine oil and phenolic sanitizer