



altro

EcoFix™ 20E

Acrylic adhesive

Features and benefits

- Installs in areas up to 90% RH
- FloorScore® Certified
- 2 year warranty
- Non-flammable
- Solvent-free
- Outstanding adhesion in areas with extra heavy traffic and rolling loads
- Excellent moisture and alkali resistance
- Excellent plasticizer resistance
- Freeze-thaw stable
- Low odor
- Easy to trowel
- Easy clean up
- 18 month shelf life

Applications

EcoFix 20E is a water dispersed, non-flammable adhesive developed for the installation of vinyl-backed and homogeneous sheet vinyl floor coverings over industry-approved porous substrates where excessive moisture is not a factor. EcoFix 20E can be installed in areas with up to 90% RH per ASTM F2170.

Specifications

EcoFix 20E is available in four-gallon containers. Approximate coverage is 165 square feet per gallon.

For further installation instructions, consult the Altro sheet flooring installation guide or adhesive label.


EcoFix 20E vs. EcoFix 25E

EcoFix 20E is a harder-setting adhesive than EcoFix 25E; they are both water-based acrylic adhesives with the 25E being used primarily as a pressure-sensitive adhesive for the setting of our tile products and the 20E being the adhesive of choice for our sheet goods.



Sustainability

Altro is fully committed to sustainability. Through careful product development, our expert team of technicians and chemists have worked to develop healthy, cost effective adhesives that perform and are compliant with even the most stringent environmental regulations.

LEED facts		 
LEED v4	This product may help contribute to the following credits	
EcoFix 20E		1
	Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at altro.com/sustainability

