

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Altro Flow 3mm Static-dissipative Base  
Product code : STSD\_B\_\_\_\_  
Product group : End product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use  
Use of the substance/mixture : Epoxy Base - Industrial flooring & wall coatings

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Altro Resin Systems  
Unit 3 Station Road Industrial Estate  
Station Road  
GB- DT2 0AE Maiden Newton Dorchester  
T 01300 320620  
[sds@altro.com](mailto:sds@altro.com) - [www.altro.com](http://www.altro.com)

##### Other

Altro GmbH  
Ebertallee 209  
06846 Dessau-Roßlau  
DE  
T +49 (0) 340 6500-0

#### 1.4. Emergency telephone number

Emergency number : 01462 480480  
Monday - Friday 09:00-17:00

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) :

Warning

Contains :

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS; Bisphenol A/F- Epoxy Resins  
MW < 700

Hazard statements (CLP) :

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Precautionary statements (CLP)

H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.  
: P261 - Avoid breathing spray, vapours.  
P264 - Wash skin or affected areas. thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bisphenol A/F- Epoxy Resins MW < 700	CAS-No.: 9003-36-5 EC-No.: 500-006-8 REACH-no: 2119454392-40-0000	$\geq 75$	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS	CAS-No.: 68609-97-2 EC-No.: 271-846-8 EC Index-No.: 603-103-00-4 REACH-no: 01-2119454392-40	$\geq 15 - < 30$	Skin Irrit. 2, H315 Skin Sens. 1, H317
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (Note P)	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119455851-35	$\geq 0.1 - < 3$	Flam. Liq. 2, H225 Aquatic Chronic 2, H411
2-METHOXY-1-METHYLETHYL ACETATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	$< 0.1$	Flam. Liq. 3, H226

Note P: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H- and EUH-statements: see section 16

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause redness and soreness of the mouth and throat.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No specific recommendations.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing agent suitable for surrounding fire. Use water spray to cool containers.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: In combustion emits toxic fumes.
-------------	------------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Refer to protective measures listed in Sections 7 and 8.
Emergency procedures	: Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area. Turn leaking containers leak-side up to prevent the escape of liquid.

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Contain the spilled material by bunding. Do not allow to enter drains or water courses.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Collect leaking and spilled liquid in sealable containers as far as possible.
-------------------------	---

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid direct contact with the substance. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in a well-ventilated place. Keep cool. Store in a dry place. Store in a closed container.

#### 7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	274 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	548 mg/m <sup>3</sup>

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS (68609-97-2)	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.6 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.87 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.1058 mg/l
PNEC aqua (marine water)	0.01058 mg/l
PNEC aqua (intermittent, freshwater)	0.072 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	307.16 mg/kg dwt
PNEC sediment (marine water)	30.72 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	1.234 mg/kg dwt

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS (68609-97-2)</b>	
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l
<b>Bisphenol A/F- Epoxy Resins MW &lt; 700 (9003-36-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, dermal	8.3 ppm
Long-term - systemic effects, dermal	104.15 mg/kg bw/day
Long-term - systemic effects, inhalation	29.39 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	6.25 mg/kg bw/day
Long-term - systemic effects, inhalation	8.7 mg/m <sup>3</sup>
Long-term - local effects, dermal	62.5 mg/kg bw/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	3 mg/l
PNEC aqua (marine water)	0.3 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.5 mg/kg wet weight
PNEC sediment (marine water)	0.5 mg/kg wet weight
<b>2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	550 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, oral	500 mg/kg bodyweight/day
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.29 mg/kg dwt

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)</b>	
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (64742-95-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	1286.4 mg/m <sup>3</sup>
Acute - local effects, inhalation	1066.67 mg/m <sup>3</sup>
Long-term - local effects, inhalation	837.5 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	1152 mg/m <sup>3</sup>
Acute - local effects, inhalation	640 mg/m <sup>3</sup>
Long-term - local effects, inhalation	178.57 mg/m <sup>3</sup>
<b>2,6-di-tert-butyl-p-cresol (128-37-0)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day
Long-term - local effects, dermal	0.5 mg/kg bw/day
Long-term - systemic effects, inhalation	1.76 mg/m <sup>3</sup>
Long-term - local effects, inhalation	3.5 mg/kg bw/day
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.435 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.25 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.199 µg/l
PNEC aqua (marine water)	0.0199 µg/l
PNEC aqua (intermittent, freshwater)	1.99 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.45819 mg/kg dwt
PNEC sediment (marine water)	0.04582 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.0539 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	16.67 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	0.017 mg/l

### 8.1.5. Control banding

No additional information available

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Provide local exhaust or general room ventilation. The floor of the storage room must be impermeable to prevent the escape of liquids.

#### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Gloves. Protective clothing. Safety glasses.

**Personal protective equipment symbol(s):**



##### 8.2.2.1. Eye and face protection

**Eye protection:**

Wear eye protection

##### 8.2.2.2. Skin protection

**Skin and body protection:**

Avoid contact with skin

##### 8.2.2.3. Respiratory protection

**Respiratory protection:**

No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment

##### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Appearance	: Liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 100 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative vapour density at 20°C : Not available  
Particle characteristics : Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with (strong) oxidizers.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

Strong acids. Strong bases. Strong oxidizing agents.

### 10.4. Conditions to avoid

Heat.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

In combustion emits toxic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

OXIRANE, MONO [(C12-14-ALKYLOXY)METHYL] DERIVS (68609-97-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 4500 mg/kg
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
LD50 oral rat	> 5000 ml/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (64742-95-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

Skin corrosion/irritation : Causes skin irritation.



# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Bisphenol A/F- Epoxy Resins MW < 700 (9003-36-5)

pH : Not available.

Serious eye damage/irritation : Causes serious eye irritation.

### Bisphenol A/F- Epoxy Resins MW < 700 (9003-36-5)

pH : Not available.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

### OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS (68609-97-2)

NOAEL (animal/female, F0/P) : 200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)

NOAEL (animal/female, F1) : 200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

### 2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

NOAEL (dermal, rat/rabbit, 90 days) : > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard : Not classified

### SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (64742-95-6)

Viscosity, kinematic : < 1 mm<sup>2</sup>/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm<sup>2</sup>/s)'

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

### OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS (68609-97-2)

LC50 - Fish [1] : 1800 mg/l Test species:- Ochorhyncus mykiss (Rainbow Trout)

EC50 72h - Algae [1] : 844 mg/l Test species:- Selenastrum capricornutum (Green algae)

### 2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LC50 - Fish [1] : > 100 mg/l Test organisms (species): Oryzias latipes

EC50 - Crustacea [1] : > 500 mg/l Test organisms (species): Daphnia magna

EC50 72h - Algae [1] : > 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

NOEC (chronic) : ≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

NOEC chronic fish : 47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

NOEC chronic crustacea : > 100 mg/l

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (64742-95-6)

EC50 - Crustacea [1]	3.2 mg/l
EC50 72h - Algae [1]	2.6 mg/l Test species:- Pseudokirchneriella subcapitata

### 12.2. Persistence and degradability

#### 2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### 2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

Partition coefficient n-octanol/water (Log Kow)	1.2
Bioaccumulative potential	Bioaccumulation is insignificant.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment





# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 14: Transport information

In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID
<b>14.1. UN number or ID number</b>			
UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)
<b>Transport document description</b>			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III, MARINE POLLUTANT	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III
<b>14.3. Transport hazard class(es)</b>			
9	9	9	9
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
Hazard identification number (Kemler No.) : 90  
Orange plates :



Tunnel restriction code (ADR) : -  
EAC code : •3Z

### Transport by sea

Special provisions (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A

### Inland waterway transport

Classification code (ADN) : M6  
Special provisions (ADN) : 274, 335, 375, 601  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP  
Number of blue cones/lights (ADN) : 0

### Rail transport

Classification code (RID) : M6  
Special provisions (RID) : 274, 335, 375, 601  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

###### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

###### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

###### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

###### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

###### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

##### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No additional information available

### SECTION 16: Other information

#### Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

# Altro Flow 3mm Static-dissipative Base

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.