



Designed for possibilities.  
Made for people.

# Altro Wood Comfort™

Realistic wood visuals with enhanced underfoot comfort



discover [altro.com](https://www.altro.com)

2.85mm  
thick

6'7"  
width

66'  
length

sheet  
format



**Castle Oak Comfort** WSMSC2816  
WR335 / AM335 LRV 51



**Farmhouse Oak Comfort** WSMSC2811  
WR338 / AM338 LRV 38



**Blchd. Bamboo Comfort** WSMSC2815  
WR463 / AM392 LRV 42



**Rustic Oak Comfort** WSMSC2805  
WR340 / AM340 LRV 37



**Autumn Maple Comfort** WSMSC2802  
WR339 / AM339 LRV 24



**Urban Cherry Comfort** WSMSC2804  
WR337 / AM337 LRV 17

Wide plank



**Great Oak Comfort** WSMSC2817  
WR339 / AM339 LRV 22



**Antique Walnut Comfort** WSMSC2810  
WR341 / AM160 LRV 15



**Washed Oak Comfort** WSMSC2808  
WR347 / AM347 LRV 38



**Vintage Cherry Comfort** WSMSC2803  
WR336 / AM239 LRV 22

Wide plank



**Tower Oak Comfort** WSMSC2818  
WR322 / AM239 LRV 19

Wide plank




**Sovereign Oak Comfort** WSMSC2820  
WR468 / AM62 LRV 10









Specifications			
Type + class		ASTM F1303	Type I, Grade 1, Class C, smooth flooring
Thickness and wear layer		2.85mm   .11" / .7mm wear layer, heterogeneous construction	
Roll dimensions		6'7" x 66'   2m x 20m	
Weight		4.79 lbs./yd <sup>2</sup>   2.6 kg/m <sup>2</sup>	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.79 dry, .94 wet
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976	36+
Static load limit		ASTM F970	1000 psi
Indentation		EN 433	≤ 0.20mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation		ISO 140-8	15dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Mold resistance		ASTM D3273	Excellent - Score of 10
Fungi resistance		ASTM G21	Passes rating 0* *achieves zero growth after 28 days
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		This product contains 10% post-consumer recycled content.	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Slightly blown PVC with black fleece backing.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> , training clinic information at <a href="http://altrofloors.com/training">altrofloors.com/training</a> . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at <a href="http://altrofloors.com/downloads">altrofloors.com/downloads</a> . Failure to install, heat weld, and/or maintain correctly could void the warranty.		

**LEED facts**  This product may help contribute to the following credits

LEED v4

---

**Altro Wood Comfort** **5**

-  Materials and resources  
Renewable bio-based content **1**
-  Materials and resources  
Environmental product declaration **1**
-  Materials and resources  
Health product declaration **1**
-  Environmental quality  
Low emitting materials, flooring **1**
-  Environmental quality  
Low emitting materials, adhesives **1**

Discover more of our sustainability story and credentials at [altro.com/sustainability](http://altro.com/sustainability)

Film	Plank length	Plank width	Repeat
Bleached Oak	2 x 500mm	100mm	1m
Rustic Oak			
Oak Traditions			
Washed Oak			
Manor Oak			
Farmhouse Oak			
Autumn Maple	1 x 550mm, 1 x 450mm (Alternating)	100mm	1m
Vintage Cherry			
Seasoned Cherry			
Urban Cherry			
Walnut Noir			
Antique Walnut			
Mellow Maple	3 x 333.3mm	62.5mm	1m
Honey Beech			
Castle Oak	1000mm	125mm	1m
Tower Oak			
Great Oak			
Imperial Oak	1000mm	166mm	1m
Sovereign Oak			
Bleached Bamboo	Fine line		1m
Warm Bamboo			

Follow us

