



Altro Operetta™

Tender text

PRODUCT DESCRIPTION

- Manufacturer and product reference:
 - **Altro Operetta** 2.00mm thick resilient Floor by Altro Floors, telephone 8000 444 7649
- Product specification according to EN ISO 10582
- Heterogeneous PVC floor
- **Phthalate free – plasticisers based on natural resources**
- **Area of use:**
 - Corridors and classrooms in schools, kindergartens, universities, student accommodation, hospitals / care home corridors and patient rooms, retail, home adaptations / social housing
- Surface protection – Easyclean PUR
- EN ISO 10874 class 34 / 43
- Width: **2000 mm**
- Thickness: **2.00mm**
- Colour: **TBC**
- **Guarantee – 10 years**
- Seam welding: Hot-welding with matching Altro Welding Rod
- The Altro quality and environmental management systems are certified in accordance with ISO 9001 and ISO 14001

Property	Standard	Performance
Flooring Type	EN IOS 10582	Resilient flooring
Thickness	EN ISO 24346	2.00mm
Wear layer	EN ISO 24340	0.7mm
Roll dimensions	EN ISO 24341	2.0m x 20.00m - 40m ²
Weight	EN ISO 23997	2.66 kg/m ²
Classification for use	EN ISO 10874	34 & 43
Fire performance	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥ 8kW/m ² Pass
Slip resistance	EN 13893 DIN 51130	DS R10
Flexibility	EN ISO 24344	Pass
Light fastness	EN ISO 105-B02	≥ 6
Wear resistance	EN 660-2	T
Castor chair abrasion	EN 425	Pass
Indentation	EN ISO 24343	≤ 0.10mm
Sound insulation	ISO 140-8	Ca. 4dB
Chemical resistance	EN ISO 26987	Good
Under floor heating	EN 12667	Suitable 27°C at adhesive line
Electrical behaviours	EN 1815	≤ 2kV Antistatic
VOC Emissions	Section 01350/Floorscore	Approved