

# Altro approved installation tape

Altro adhesive-free flooring

Technical data sheet

July 2020

**Product:** Altro approved installation tape.

**Product description:** Double sided tape.

**Adhesive:** The adhesive is a pressure-sensitive acrylic adhesive, coated on both sides of a polyester carrier. It provides a permanent bond on key sub-floor types, including plywood, metals, foams, plastics and composite materials subjected to a broad range of environmental conditions including low and elevated temperatures.

**Product structure /** Carrier / support: Polyester film, transparent

**characteristics:** Release liner: Paper

Application temperature: min. 18°C

Usage temperature: min. -27°C  
max. 60°C

Thickness: 0.089mm

Width: 72 mm

Length: 25 LM

**Features & Benefits:** High performance tape product which bonds to multiple surfaces including metals, plastics, plywood and composite materials.

Excellent UV and temperature resistance.

Performs well at high and low temperatures.

Excellent peel, tack and shear.

Excellent moisture resistance in high humidity.

**Recommendations:** Substrates and surfaces to which the tape is applied to must be clean, dry and free of dust, release agents, grease and oil. A primer may be required in some instances.

For information on how to install Altro adhesive-free flooring, please refer to Altro adhesive-free installation guide.

**For further information or technical advice**

**tel: +44 (0) 1462 707600**

**email: [enquiries@altro.com](mailto:enquiries@altro.com) or [www.altro.com](http://www.altro.com)**