

# Altro self-adhesive tape

Technical data sheet

November 2017

<b>Product:</b>	Altro self-adhesive tape.	
<b>Product description:</b>	Double sided tape.	
<b>Adhesive:</b>	The adhesive is a pressure-sensitive acrylic adhesive, coated on both sides of a polyester carrier. It provides a permanent bond on key sub-floor types, including plywood, metals, foams, plastics and composite materials subjected to a broad range of environmental conditions including low and elevated temperatures.	
<b>Product structure / characteristics:</b>	Carrier / support:	Polyester film, transparent
	Release liner:	48 micron clear polyester liner
	Application temperature:	min. -23°C (-10°F)
	Usage temperature:	min. -27°C (-17°F) max. 60°C (140°F)
	Thickness:	0.089mm
<b>Features &amp; Benefits:</b>	High performance tape product which bonds to multiple surfaces including metals, plastics, plywood and composite materials.	
	Excellent UV and temperature resistance.	
	Performs well at high and low temperatures.	
	Excellent peel, tack and shear.	
	Excellent moisture resistance in high humidity.	

For information on how to install Altro self-adhesive, please refer to the Altro transport installation and maintenance guide.

**For further information or technical advice**

**tel: +44 (0) 1462 707600**

**email: [transportenquiries@altro.com](mailto:transportenquiries@altro.com) or [www.altro.com](http://www.altro.com)**