

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 6/25/2024 Revision date: 6/25/2024 Supersedes version of: 10/17/2023 Version: 7.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener
Product code : ST_H; TT_H; HG_KG
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use
Use of the substance/mixture : Amine Epoxy Hardener - Industrial flooring & wall coatings.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Altro Resin Systems
Unit 3 Station Road Industrial Estate
Station Road
GB- DT2 0AE Maiden Newton Dorchester
T 01300 320620
sds@altro.com - www.altro.com

Distributor

Altro Deutschland GmbH & Co. KG
Ebertallee 209
DE- 06846 Dessau-Rosslau
T +49 (0) 340 6500-0
www.altro.com

1.4. Emergency telephone number

Emergency number : 01462 480480
Monday - Friday 09:00 - 17:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) : Danger

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Phenol, styrenated; Phenol, 4,4'-(1-methylethylidene)bis-polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (Chloromethyl)oxirane; BENZYL ALCOHOL; 1,3-Benzenedimethanamine; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine
Hazard statements (CLP)	: H302+H332 - Harmful if swallowed or if inhaled. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing spray, vapours. P264 - Wash skin or affected areas. thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves. P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER, a doctor. P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER, a doctor. P321 - Specific treatment (see supplemental first aid instruction on this label).

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture contains substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Component

Phenol, styrenated(61788-44-1)	The substance is included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
--------------------------------	---

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
BENZYL ALCOHOL	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	$\geq 15 - < 50$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Eye Irrit. 2, H319
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9 REACH-no: 01-2119514687-32	$\geq 15 - < 50$	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317
Phenol, 4,4'-(1-methylethylidene)bis-polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (Chloromethyl)oxirane	CAS-No.: 38294-64-3 EC-No.: 500-101-4 REACH-no: 01-2119965165-33	$\geq 5 - < 30$	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,3-Benzenedimethanamine	CAS-No.: 1477-55-0 EC-No.: 216-032-5 REACH-no: 01-2119480150-50	≥ 3 – < 10	Acute Tox. 4 (Oral), H302 (ATE=930 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=2000 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=2.4 mg/l/4h) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Phenol, styrenated substance identified as having endocrine disrupting properties	CAS-No.: 61788-44-1 EC-No.: 262-975-0	< 5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 926-141-6 REACH-no: 01-2119456620-43	≥ 3 – < 5	Asp. Tox. 1, H304

Specific concentration limits:

Name	Product identifier	Specific concentration limits
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9 REACH-no: 01-2119514687-32	(0.001 ≤C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Drink plenty of water. Go into open air and ventilate suspected area. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Treat symptomatically.
Symptoms/effects after inhalation	: May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Serious effects may be delayed following exposure.
Symptoms/effects after skin contact	: Causes severe burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

The exposed person may need to be kept under medical surveillance for 48 hours.

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Water spray. Water fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition can lead to the release of irritating gases and vapours.

5.3. Advice for firefighters

Firefighting instructions : Do not use water jet to extinguish. Control run-off water by containing and keeping it out of sewers and watercourses.

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter sewers, surface or groundwater.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb remaining liquid with sand or inert absorbent and remove to safe place. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not breathe vapours. Do not handle until all safety precautions have been read and understood. Keep only in original container.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Store in a well-ventilated place. Keep cool. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

BENZYL ALCOHOL (100-51-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	40 mg/kg bw/day
Acute - systemic effects, inhalation	110 mg/m ³
Long-term - local effects, dermal	8 mg/kg bw/day
Long-term - systemic effects, inhalation	22 mg/kg bw/day
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	20 mg/kg bw/day
Acute - systemic effects, inhalation	27 (≥)
Acute - systemic effects, oral	20 mg/m ³
Long-term - systemic effects, oral	4 mg/kg bw/day
Long-term - systemic effects, inhalation	5.4 mg/m ³
Long-term - systemic effects, dermal	4 mg/kg bw/day
PNEC (Water)	
PNEC aqua (freshwater)	≈ 1 mg/l
PNEC aqua (marine water)	≈ 0.1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	5.27 mg/kg dwt
PNEC sediment (marine water)	0.527 mg/kg dwt
PNEC (Soil)	
PNEC soil	≈ 0.456 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	39 mg/l
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	20.1 mg/m ³
Acute - local effects, inhalation	0.073 mg/m ³
Long-term - local effects, inhalation	0.073 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	0.3 mg/kg bodyweight/day
Long-term - systemic effects, oral	0.3 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.06 mg/l
PNEC aqua (marine water)	0.006 mg/l

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
PNEC aqua (intermittent, freshwater)	0.23 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	5.784 mg/kg dwt
PNEC sediment (marine water)	0.578 mg/kg dwt
PNEC (Soil)	
PNEC soil	1.121 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	3.18 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Dustproof clothing. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Skin and body protection:

Avoid contact with skin

Hand protection:

Standard EN 374 - Protective gloves against chemicals.

Other skin protection

Materials for protective clothing:

Keep work clothing separately

8.2.2.3. Respiratory protection

Respiratory protection:

Wear suitable respiratory equipment in case of insufficient ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless to pale yellow.
Odour	: Amine-like.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: $\approx 120\text{ }^{\circ}\text{C}$
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: No specific test data are available.
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.03
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Not relevant.

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

ATE CLP (oral)	504.49 mg/kg bodyweight
ATE CLP (dust,mist)	2.808 mg/l/4h

Phenol, styrenated (61788-44-1)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Remarks on results: other:
LD50 oral	2.5 mg/kg Animal: Rat
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LD50 dermal rabbit	5010 mg/kg Animal: Rabbit
LC50 Inhalation - Rat	> 4.92 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Remarks on results: other:
LC50 Inhalation - Rat (Vapours)	> 2.5 mg/l/4h Animal: rat

Phenol, 4,4'-(1-methylethylidene)bis-polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (Chloromethyl)oxirane (38294-64-3)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
-----------------	--

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 20 mg/l/4h

BENZYL ALCOHOL (100-51-6)

LD50 oral rat	1620 mg/kg
LD50 oral	1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1410 - 1770
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 4.178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

1,3-Benzenedimethanamine (1477-55-0)

LD50 oral rat	930 mg/kg
LD50 dermal rat	> 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	3.89 mg/l
LC50 Inhalation - Rat [ppm]	1700 ppm/1h

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,3-Benzenedimethanamine (1477-55-0)	
LC50 Inhalation - Rat (Dust/Mist)	2.4 mg/l/4h
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
LD50 oral rat	1030 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.01 mg/l/4h
Skin corrosion/irritation	: Causes severe skin burns. pH: No specific test data are available.
Phenol, styrenated (61788-44-1)	
pH	6.85 Temp.: 30 °C Concentration: 1 vol% Remarks on result: 'other:'
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
pH	11.6
Serious eye damage/irritation	: Causes serious eye damage. pH: No specific test data are available.
Phenol, styrenated (61788-44-1)	
pH	6.85 Temp.: 30 °C Concentration: 1 vol% Remarks on result: 'other:'
ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
pH	11.6
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Phenol, styrenated (61788-44-1)	
LOAEL (oral, rat, 90 days)	337 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Remarks on results: other:
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Phenol, 4,4'-(1-methylethylidene)bis-polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (Chloromethyl)oxirane (38294-64-3)	
LOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	10 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
BENZYL ALCOHOL (100-51-6)	
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)

LOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

Aspiration hazard : Not classified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Viscosity, kinematic	2.4 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	---

BENZYL ALCOHOL (100-51-6)

Viscosity, kinematic	4.851 mm ² /s
----------------------	--------------------------

ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)

Viscosity, kinematic	19 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	--

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Component

Phenol, styrenated(61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)
--------------------------------	--

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Not rapidly degradable

Phenol, styrenated (61788-44-1)

LC50 - Fish [1]	1.77 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	1.35 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	0.115 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Phenol, 4,4'-(1-methylethylidene)bis-polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (Chloromethyl)oxirane (38294-64-3)

LC50 - Fish [1]	1.62 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1.59 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	3.13 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	2.5 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

BENZYL ALCOHOL (100-51-6)

LC50 - Fish [1]	460 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	10 mg/l Test organisms (species): Lepomis macrochirus

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BENZYL ALCOHOL (100-51-6)	
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	76.828 mg/l Test organisms (species): other:
NOEC chronic fish	48.897 mg/l Test organisms (species): other: Duration: '30 d'

1,3-Benzenedimethanamine (1477-55-0)	
LC50 - Fish [1]	87.6 mg/l Test organisms (species): Oryzias latipes
LC50 - Fish [2]	10 – 100 mg/l
EC50 - Crustacea [1]	15.2 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	20.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	33.3 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	15 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	4.7 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	4.7 mg/l Test species: Daphnia magna

ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine (2855-13-2)	
LC50 - Fish [1]	110 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	17.4 mg/l Test Species: Daphnia magna
EC50 72h - Algae [1]	37 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 50 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

BENZYL ALCOHOL (100-51-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Component	
Phenol, styrenated(61788-44-1)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Must follow special treatment according to local regulation.
HP Code	: HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP8 - "Corrosive:" waste which on application can cause skin corrosion. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information





In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID
14.1. UN number or ID number			
UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name			
POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.)
Transport document description			
UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.), 8, III, (E)	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.), 8, III	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.), 8, III	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS : BENZYL ALCOHOL; ISOPHORONEDIAMINE / 3-Aminomethyl-3-5,5-trimethylcyclohexylamine.), 8, III
14.3. Transport hazard class(es)			
8	8	8	8

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ADN	RID
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP28
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR) : E

Transport by sea

Special provisions (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Segregation (IMDG)	: SGG18, SG35
Properties and observations (IMDG)	: Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

Inland waterway transport

Classification code (ADN)	: C7
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 5 L

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: C7
Special provisions (RID)	: 274
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP28
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 80

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

Altro Tect Standard / Altro Tect Slip-resistant / Altro Tect Clear Hardener

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.