



Designed for possibilities.
Made for people.

Altro Classic™ 25

Traditional and industrial, Altro Classic 25 has been tried and trusted for over 60 years




2.5mm
thick

6'7"
width

66'
length

sheet
format







Anvil X2594R11
WR101 / AM72 LRV 11




Graphite X2546R11
WR86 / AM86 LRV 21




Truffle X2545R11
WR153 / AM239 LRV 17




Pewter Gray X2539R11
WR81 / AM81 LRV 26




Walnut X2586R11
WR62 / AM62 LRV 10




Blackberry X2547R11
WR100 / AM100 LRV 7




Mushroom X2542R11
WR24 / AM27 LRV 32




Quarry Red X2560R11
WR42 / AM42 LRV 13




Aster X2549R11
WR286
AM286 LRV 17



Blue X2541R11
WR71
AM71 LRV 20



Legend X2544R11
WR231
AM73 LRV 10



Whisper X2548R11
WR354
AM84 LRV 24

Specifications			
Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.5mm .10", homogenous construction	
Roll dimensions		6'7" x 65'5 2m x 20m	
Weight		5.89 lbs./yd ² 3.2 kg/m ²	
Warranty		12 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.9 dry, 1.0 wet
Dynamic coefficient of friction		ANSI/NFSI B101.3	.60 wet DCOF
Ramp test		DIN 51130	R11
TRRL pendulum test		BS 7976 ASTM E303	45+
Static load limit		ASTM F970	1000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation		ISO 140-8	5dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		This product contains 10% post-consumer recycled content.	
Composition	Silicon carbide, aluminum trioxide and colored quartz aggregate throughout thickness of PVC.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Classic 25 and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2019

LEED facts



LEED v4

This product may help contribute to the following credits

Altro Classic 25

6

	Materials and resources Contains recycled content	1
	Materials and resources Renewable bio-based content	1
	Materials and resources - EPD Environmental product declaration Type III product specific	1
	Materials and resources - HPD Health product declaration	1
	Environmental quality Low emitting materials, flooring	1
	Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at altro.com/sustainability