



# altro

## EcoFix™ 35 Spray

This spray adhesive may be used with resilient sheet vinyl flooring.  
Not recommended for wet areas.

Coverage: 150 - 185 ft<sup>2</sup> (14 - 17.2 m<sup>2</sup>)

5 year warranty

Warranted for: 8lbs MVER, 95% RH, 11pH

### Product characteristics

EcoFix 35 Spray is a versatile spray adhesive suited for adhering resilient sheet vinyl flooring products in commercial and residential applications.

- Uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive.
- EcoFix 35 Spray's instant shear strength allows for all traffic without any adhesive indentation, displacement or movement associated with heavy weight-bearing loads.
- Non-toxic, 0.020 g/ml low-VOC product.

### Coverage guide

Covers 150-185 sq ft

Note: Seams and perimeter require double coverage.

**Warning: Not to be used in any wet areas (kitchens, bathrooms, pools, etc.)**

### Advantages

- Uses up to 80% less adhesive
- Same day heat welding
- Allows all traffic immediately
- Low-VOC (0.020 g/ml)
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Cleans up easily while still wet
- Non-flammable
- High moisture and pH resistant
- FloorScore certified

### Suitable substrates

The following properly prepared, smooth, flat, dust-free substrates are approved:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT



### LEED facts

LEED v4 This product may help contribute to the following credits

<b>EcoFix 35 Spray</b>	1
Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at [altro.com/sustainability](http://altro.com/sustainability)

Technical data	Characteristics
Chemical type	Water-based acrylic blend
Appearance	Milky white frost bubbles
Flash point	Will not burn
NFPA 704 flammability rating	0 (Non-flammable)
Shelf life	3 years, if unopened
Open time	3 hours
Dry time	Once adhesive is dry to touch (10-20 minutes)
Foot traffic allowance	Immediately
Heavy machinery allowance	Immediately
Resistance to moisture	Excellent: 8 lbs/1,000 sq ft or 95% RH/11pH
Underfloor heating systems	Yes
Storage	Do not subject to freezing temperatures