

PRODUCT DESCRIPTION

- Manufacturer and product reference:
 - Altro Oceanis** 2.8 mm thick safety floor by Altro Limited
- Product specification according to EN ISO 11638
- PVC floor covering for shoe and barefoot environments
- o-Phthalate free: plasticisers based on natural resources**
- Area of use:**
 - Bathrooms, showers, changing rooms, saunas, spas, wet environments in social care and student accommodation
- Surface protection: **Easyclean PUR**
- EN ISO 10874: **Class 34 / 42**
- Slip potential: Pendulum test value (PTV) (minimum) to EN 16165 Annex C: **≥ 50 (wet – slider 96)**
- Surface roughness (Rz) (minimum) to BS 1134: **≥ 20 micron**
- Width: **2000 mm**
- Thickness: **2.80 mm**
- Colour: **TBC**
- Guarantee: **10 years**
- Seam welding: **Hot-welding with matching Altro welding rod**
- The Altro quality and environmental management systems are certified according to ISO 9001:2015 and ISO 14001:2015
- CE and UKCA approved

Property	Standard	Performance
Flooring type	EN ISO 11638 / EN 13845	Resilient safety flooring
Thickness	EN ISO 24346	2.8 mm
Wear layer thickness	EN ISO 24340	1.0 mm
Roll dimensions	EN ISO 24341	2.0 m x 20.00 m – 40 m ²
Weight	EN ISO 23997	2.9 kg/m ²
Classification for use	EN ISO 10874	34 / 42
Fire performance	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Cfl-s1 ≥ 4.5 kW/m ² Pass
Slip resistance	EN 16165 Annex C / PTV Slider 96 EN 13845 Annex C EN 13893 EN 16165 Annex B / ASR A1.5 (formerly DIN 51130) EN 16165 Annex A	≥ 50 (Slider 96) ESf / ESb ≥ 0.30 / DS R11 B
Flexibility	EN ISO 24344	Pass
Light fastness	EN ISO 105-B02	≥ 6
Wear resistance	EN 13845 Annex D	≤ 10% particles lost over 50000 cycles
Castor chair abrasion	ISO 4918	Pass
Residual indentation	EN ISO 24343-1	≤ 0.20 mm
Sound insulation	ISO 10140-3	Ca. 14 dB
Chemical resistance	EN ISO 26987	Good
Under floor heating	EN 12524	Suitable 27°C at adhesive line
Electrical behaviours	EN 1815	≤ 2 kV Antistatic
VOC Emissions	CDPH 1350 / Floorscore / M1	Approved