



# Altro Wood Acoustic™

## Tender text

### PRODUCT DESCRIPTION

- Manufacturer and product reference:
  - **Altro Wood Acoustic** 3.9mm thick Acoustic Floor by Altro Floors, telephone 8000 444 7649
- Product specification according to BS EN 651
- Heterogeneous PVC floor
- **Phthalate free – plasticisers based on natural resources**
- **Area of use:**
  - Playrooms in kindergarten's, hotel rooms, offices, anywhere where the passage of sound must be reduced between storeys
- Surface protection – Easyclean PUR
- EN ISO 10874 class 34 / 42
- Width: **2000 mm**
- Thickness: **3.9mm**
- Colour: **TBC**
- **Guarantee – 10 years**
- Seam welding: Hot-welding with matching Altro Welding Rod
- The Altro quality and environmental management systems are certified in accordance with ISO 9001 and ISO 14001

Property	Standard	Performance
Flooring Type	EN 651	Resilient flooring / Acoustic Flooring
Thickness	EN ISO 24346	3.9 mm
Wear layer	EN ISO 24340	0.7mm
Roll dimensions	EN ISO 24341	2.0m x 20.00m - 40m <sup>2</sup>
Weight	EN ISO 23997	2.9 kg/m <sup>2</sup>
Classification for use	EN ISO 10874	34 & 43
Fire performance	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Cfl-s1 ≥ 4.5kW/m <sup>2</sup> Pass
Slip resistance	EN 13893 DIN 51130	DS R10
Flexibility	EN ISO 24344	Pass
Light fastness	EN ISO 105-B02	≥ 6
Wear resistance	EN 660-2	T
Castor chair abrasion	EN 425	Pass
Indentation	EN ISO 24343	≤ 0.10mm
Sound insulation	ISO 140-8	Ca. 19dB
Chemical resistance	EN ISO 26987	Good
Under floor heating	EN 12667	Suitable 27°C at adhesive line
Electrical behaviours	EN 1815	≤ 2kV Antistatic
VOC Emissions	Section 01350/Floorscore	Approved