

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 15/06/2023 Revision date: 15/06/2023 Supersedes version of: 17/05/2018 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Altro Prime Standard Base

Product code : PR_B
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use

Use of the substance/mixture : Epoxy Base - Industrial flooring & wall coatings

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier Other

Altro Resin Systems

Altro GmbH

Unit 3 Station Road Industrial Estate

Ebertallee 209

Station Road

06846 Dessau-Roßlau

GB- DT2 0AE Maiden Newton Dorchester

T 01300 320620 T +49 (0) 340 6500-0

sds@altro.com - www.altro.com

1.4. Emergency telephone number

Emergency number : 01462 480480

Monday - Friday 09:00-17:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP) : Warning

Contains : Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)

: P261 - Avoid breathing spray, vapours.

P264 - Wash skin or affected areas. thoroughly after handling.

P280 - Wear eye protection, protective clothing, protective gloves.

P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component

Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)(25068-38-6)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619- 26	≥ 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
BENZYL ALCOHOL	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	≥ 10 – < 15	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h)
2-METHOXY-1-METHYLETHYL ACETATE substance with national workplace exposure limit(s) (GB)	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	< 0.1	Flam. Liq. 3, H226 STOT SE 3, H336

Specific concentration limits:			
Name	Product identifier	Specific concentration limits	
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW ≤ 700)	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119456619- 26	(5 ≤C ≤ 100) Eye Irrit. 2, H319 (5 ≤C ≤ 100) Skin Irrit. 2, H315	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical

advice/attention if you feel unwell.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth out with water. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : May cause skin irritation.

Symptoms/effects after eye contact : May cause eye irritation. redness, itching, tears.

Symptoms/effects after ingestion : May cause redness and soreness of the mouth and throat.

4.3. Indication of any immediate medical attention and special treatment needed

No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing agent suitable for surrounding fire. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Fire hazard : In combustion emits toxic fumes

5.3. Advice for firefighters

Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Refer to protective measures listed in Sections 7 and 8.

Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area. Turn leaking

containers leak-side up to prevent the escape of liquid.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Contain the spilled material by bunding. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Collect

leaking and spilled liquid in sealable containers as far as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

15/06/2023 (Revision date) GB - en 3/13

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Avoid direct contact with the substance. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep container closed when not in use. Store in a well-ventilated place. Keep cool. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1] 274 mg/m³	
WEL STEL (OEL STEL)	548 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

BENZYL ALCOHOL (100-51-6)		
DNEL/DMEL (Workers)		
Long-term - local effects, dermal	≈ 8 mg/kg wet weight	
Long-term - local effects, inhalation	≈ 22 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	≈ 1 mg/l	
PNEC aqua (marine water)	≈ 0.1 mg/l	
PNEC (Soil)		
PNEC soil	≈ 0.456 mg/kg dwt	
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, oral	500 mg/kg bodyweight/day	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)			
Long-term - systemic effects, inhalation	33 mg/m³		
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day		
Long-term - local effects, inhalation	33 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0.635 mg/l		
PNEC aqua (marine water)	0.0635 mg/l		
PNEC aqua (intermittent, freshwater)	6.35 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	3.29 mg/kg dwt		
PNEC sediment (marine water)	0.329 mg/kg dwt		
PNEC (Soil)			
PNEC soil	0.29 mg/kg dwt		
PNEC (STP)			
PNEC sewage treatment plant	100 mg/l		
SOLVENT NAPHTHA (PETROLEUM), LIGHT A	ROM.; LOW BOILING POINT NAPHTHA (64742-95-6)		
DNEL/DMEL (Workers)			
Acute - systemic effects, inhalation	1286.4 mg/m³		
Acute - local effects, inhalation	1066.67 mg/m³		
Long-term - local effects, inhalation	837.5 mg/m³		
DNEL/DMEL (General population)			
Acute - systemic effects, inhalation	1152 mg/m³		
Acute - local effects, inhalation	640 mg/m³		
Long-term - local effects, inhalation	178.57 mg/m³		
2,6-di-tert-butyl-p-cresol (128-37-0)	2,6-di-tert-butyl-p-cresol (128-37-0)		
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day		
Long-term - local effects, dermal	0.5 mg/kg bw/day		
Long-term - systemic effects, inhalation	1.76 mg/m³		
Long-term - local effects, inhalation	3.5 mg/kg bw/day		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.25 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	0.435 mg/m³		
Long-term - systemic effects, dermal	0.25 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	0.199 μg/l		
PNEC aqua (marine water)	0.0199 μg/l		
PNEC aqua (intermittent, freshwater)	1.99 µg/l		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2,6-di-tert-butyl-p-cresol (128-37-0)		
PNEC (Sediment)		
PNEC sediment (freshwater)	0.45819 mg/kg dwt	
PNEC sediment (marine water)	0.04582 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.0539 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	16.67 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	0.017 mg/l	

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. The floor of the storage room must be impermeable to prevent the escape of liquids.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Wear eye protection

8.2.2.2. Skin protection

Skin and body protection:

Avoid contact with skin

8.2.2.3. Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Not available
Appearance : Liquid.
Odour : Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour threshold : Not available Melting point : Not available Not available Freezing point Not available Boiling point Flammability Not available **Explosive limits** Not available Lower explosion limit : Not available Upper explosion limit : Not available : > 100 °C Flash point : Not available Auto-ignition temperature Decomposition temperature : Not available

pH : pH (concentrated solution): 7

Viscosity, kinematic : Not available Solubility Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available : Not available Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Strong acids. Strong bases. Strong oxidizing agents.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1580 mg/kg bodyweight Animal: mouse, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% Ct: 1410 - 1770 D50 dermal rabbit		
Toxicity), 95% CL: 1410 - 1770 D50 dermal rabbit 2 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Remarks on results: other: C50 Inhalation - Rat 2 418 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other: Sisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW <= 700) (25068-38-6) D50 oral rat 2 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	BENZYL ALCOHOL (100-51-6)	
Toxicity), Remarks on results: other: 2 4178 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other: 2 4000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Inhalation Toxicity), Remarks on results: other: 2 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Oral Toxicity - Fixed Dose Method) 2 6190 ml/kg Method: OECD Test Guideline 401 2 6190 ml/kg Method: OECD Test Guideline 401 2 6190 ml/kg Method: OECD Test Guideline 402 3 6190 ml/kg Method: OECD Test Guideline 402 3 6190 ml/kg Method: OECD Test Guideline 402 4 6 6 6 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7	LD50 oral	The second secon
Remarks on results: other: Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW <= 700) (25068-38-6) D50 oral rat	LD50 dermal rabbit	, ,
Description	LC50 Inhalation - Rat	``
420 (Acute Oral Toxicity - Fixed Dose Method) -METHOXY-1-METHYLETHYL ACETATE (108-65-6) D50 oral rat > 6190 ml/kg Method: OECD Test Guideline 401 D50 dermal rat in corrosion/irritation : Causes skin irritation. pH: pH (concentrated solution): 7 reious eye damage/irritation : Causes serious eye irritation. pH: pH (concentrated solution): 7 aspiratory or skin sensitisation : May cause an allergic skin reaction. erm cell mutagenicity : Not classified arcinogenicity : Not classified productive toxicity : Not classified -METHOXY-1-METHYLETHYL ACETATE (108-65-6) TOT-single exposure May cause drowsiness or dizziness. TOT-repeated exposure : Not classified SENZYL ALCOHOL (100-51-6) IOAEL (oral, rat, 90 days) > 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified 1000 mg/kg bodyweight Animal: ratbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) SENZYL ALCOHOL (100-51-6) ISENZYL ALCOHOL (100-51-6)	Bisphenol-A-(epichlorohydrin) EPOXY R	RESIN (Number average MW <= 700) (25068-38-6)
D50 oral rat > 6190 ml/kg Method: OECD Test Guideline 401 D50 dermal rat > 5000 mg/kg Method: OECD Test Guideline 402 chic corrosion/irritation ph: ph (concentrated solution): 7 erious eye damage/irritation ph: ph (concentrated solution): 7 erious eye damage/irritation ph: ph (concentrated solution): 7 espiratory or skin sensitisation em cell mutagenicity : Not classified arcinogenicity : Not classified 3 Not classified TOT-single exposure May cause drowsiness or dizziness. FOT-repeated exposure May cause drowsiness or dizziness. FOT-repeated exposure Not classified SENZYL ALCOHOL (100-51-6) DOAEL (oral, rat, 90 days) 400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified SENZYL ALCOHOL (100-51-6) GENZYL ALCOHOL (100-51-6)	LD50 oral rat	
D50 dermal rat > 5000 mg/kg Method: OECD Test Guideline 402	2-METHOXY-1-METHYLETHYL ACETATI	E (108-65-6)
cin corrosion/irritation : Causes skin irritation. pH: pH (concentrated solution): 7 erious eye damage/irritation : Causes serious eye irritation. pH: pH (concentrated solution): 7 espiratory or skin sensitisation : May cause an allergic skin reaction. erm cell mutagenicity : Not classified erricogenicity : Not classified error-single exposure : Not classified error-repeated	LD50 oral rat	> 6190 ml/kg Method: OECD Test Guideline 401
pH: pH (concentrated solution): 7 causes serious eye damage/irritation pH: pH (concentrated solution): 7 pH: pH (concentrated solution): 7 pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitisation pH: pH (concentrated solution): 7 psepiratory or skin sensitistion. pH: pH (concentrated solution): 7 psepiratory or skin sensitistion. pH: pH (concentrated solution): 7 psepiratory or skin sensitistion. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. pH: pH (concentrated solution): 7 psepiratory or skin sensities. ph: pH: pH (concentrated). ph:	LD50 dermal rat	> 5000 mg/kg Method: OECD Test Guideline 402
pH: pH (concentrated solution): 7 aspiratory or skin sensitisation : May cause an allergic skin reaction. erm cell mutagenicity : Not classified arcinogenicity : Not classified productive toxicity : Not classified Indicated to the control of the control	Skin corrosion/irritation	
erm cell mutagenicity : Not classified arcinogenicity : Not classified aproductive toxicity : Not classified aproductive apposure : Not classified apposur	Serious eye damage/irritation	
arcinogenicity : Not classified productive toxicity : Not classified TOT-single exposure : Not classified I-METHOXY-1-METHYLETHYL ACETATE (108-65-6) ITOT-single exposure	Respiratory or skin sensitisation	
aproductive toxicity : Not classified FOT-single exposure : Not classified FOT-single exposure : Not classified FOT-single exposure	Germ cell mutagenicity	
In the content of the		
-METHOXY-1-METHYLETHYL ACETATE (108-65-6) TOT-repeated exposure	•	
May cause drowsiness or dizziness. FOT-repeated exposure : Not classified BENZYL ALCOHOL (100-51-6) IOAEL (oral, rat, 90 days) 400 mg/kg bodyweight Animal: rat, Guideline: other: -METHOXY-1-METHYLETHYL ACETATE (108-65-6) IOAEL (dermal, rat/rabbit, 90 days) > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) I/iscosity, kinematic 0.005 mm²/s	<u> </u>	
FOT-repeated exposure : Not classified BENZYL ALCOHOL (100-51-6) IOAEL (oral, rat, 90 days) 400 mg/kg bodyweight Animal: rat, Guideline: other: IOAEL (dermal, rat/rabbit, 90 days) > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) Fiscosity, kinematic 0.005 mm²/s		
BENZYL ALCOHOL (100-51-6) IOAEL (oral, rat, 90 days) 400 mg/kg bodyweight Animal: rat, Guideline: other: -METHOXY-1-METHYLETHYL ACETATE (108-65-6) IOAEL (dermal, rat/rabbit, 90 days) > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) //scosity, kinematic 0.005 mm²/s		
-METHOXY-1-METHYLETHYL ACETATE (108-65-6) IOAEL (dermal, rat/rabbit, 90 days) > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) Viscosity, kinematic 0.005 mm²/s	BENZYL ALCOHOL (100-51-6)	
> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) //iscosity, kinematic 0.005 mm²/s	NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: other:
Dose Dermal Toxicity: 21/28-Day Study) spiration hazard : Not classified BENZYL ALCOHOL (100-51-6) //iscosity, kinematic	2-METHOXY-1-METHYLETHYL ACETATI	E (108-65-6)
BENZYL ALCOHOL (100-51-6) Viscosity, kinematic 0.005 mm²/s	NOAEL (dermal, rat/rabbit, 90 days)	()
/iscosity, kinematic 0.005 mm²/s	Aspiration hazard	: Not classified
•	BENZYL ALCOHOL (100-51-6)	
	Viscosity, kinematic	0.005 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

(chronic)

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects.

Not rapidly degradable

BENZYL ALCOHOL (100-51-6)	
LC50 - Fish [1]	460 mg/l Test organisms (species): Pimephales promelas

15/06/2023 (Revision date) GB - en 8/13

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

BENZYL ALCOHOL (100-51-6)		
EC50 - Crustacea [1]	230 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	770 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	500 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	76828 mg/l Test organisms (species): other:	
NOEC chronic fish	48897 mg/l Test organisms (species): other: Duration: '30 d'	
Bisphenol-A-(epichlorohydrin) EPOXY RESIN (Number average MW <= 700) (25068-38-6)		
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna	
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes	
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)	
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'	
NOEC chronic crustacea	> 100 mg/l	

12.2. Persistence and degradability

BENZYL ALCOHOL (100-51-6)		
Persistence and degradability Readily biodegradable.		
2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)		
Persistence and degradability Readily biodegradable.		

12.3. Bioaccumulative potential

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
Partition coefficient n-octanol/water (Log Kow) 1.2	
Bioaccumulative potential	Bioaccumulation is insignificant.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Waste treatment methods Ecology - waste materials HP Code

- : Disposal must be done according to official regulations.
- : Must follow special treatment according to local regulation.
- : Avoid release to the environment.
- : HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- HP13 "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.
- HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID	
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.)	
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III, MARINE POLLUTANT	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.), 9, III	
14.3. Transport hazard class(es)				
9	9	9	9	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ADN	RID
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR)

EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Packing instructions (IMDG) : LP01, P001 Special packing provisions (IMDG) PP1 IBC packing instructions (IMDG) IBC03 Tank instructions (IMDG) T4 TP1, TP29 Tank special provisions (IMDG) EmS-No. (Fire) F-A EmS-No. (Spillage) : S-F Stowage category (IMDG) Α

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.