



# Maintenance guide for walls

For all Altro wall panels

## Initial cleaning

Once all panels and joints are installed, remove the protective film and clean all surfaces with an antistatic solution or anti-static wipes. This is required as the panel may have static build up and any dust in the atmosphere will adhere to the surface of the panel.

Continue with regular maintenance.

## Regular maintenance

- Wall panels can be cleaned with a diluted soap/detergent solution, such as PVC wall cleaner (for stubborn stains) or AltroClean 44 (degreaser).
- Use a lint-free, non-woven wipe or a polyester knit wipe. Both are extremely low in particle generation.
- When cleaning the panels we recommend the temperature of water does not exceed 140°F (60°C).
- Pressure cleaning with hot water may be used with the pressure nozzle a minimum of 2 feet (600mm) away from the surface.

- To reduce the build-up of static, cleaning the panels with an anti-static solution or anti-static wipes is recommended.
- Some cleaning agents may adversely affect wall panels. See Altro's chemical resistance chart for reactions to common chemicals at [www.altro.com/techdocs](http://www.altro.com/techdocs).
- Do not use cleansers containing abrasives or solvents.

## Maintenance for Altro Whiterock Whiteboard

Use of a soft cloth, water and diluted household detergents are recommended. Thoroughly rinse detergents and solvents from surface. For stubborn stains, use diluted AltroClean 44 cleaner or equivalent alkaline cleaner. AltroClean 44 dilution should not be used on a regular basis.

For best results, a thorough cleaning should occur at least once a week.

The following maintenance products are available to purchase



P/N: ASF 44 Cleaner  
AltroClean 44 - 5 Liters  
1.3 Gallons



P/N: ALW A863  
Anti-Static Wipes  
80/Unit



P/N: ALW A859/325  
PVC Cleaner



P/N: ALW A809/05  
Anti-Static Solution  
5 Liters

Labels may indicate that they are exclusively for Altro Whiterock. Please note, cleaning agents may be used for all Altro Wall panels.