



Designed for possibilities.
Made for people.



Altro Wood™ adhesive-free product datasheet

Adhesive-free, smooth commercial flooring

Altro Wood adhesive-free

New Altro Wood adhesive-free creates maximum impact with minimum downtime. With 18 color choices, 14dB sound reduction, a 10-year warranty and our Altro one-in-a-million slip resistance reassurance, Altro Wood adhesive-free offers high levels of comfort underfoot providing a safe, durable and decorative solution for busy spaces.

Using our award-winning adhesive-free installation method, it can be welded and walked on the same day, and at the end of its life can be removed easily, allowing it to be reused or recycled. Using Altro adhesive-free floors, you can halve installation time compared with a traditional adhered installation. It is ideal for busy public spaces where disruption needs to be minimal, plus there are no associated adhesive odors.

Typical applications

Healthcare, temporary installations, senior living, education, retail and offices, hallways, general circulation areas

Features + benefits


- One-in-a-million slip resistance reassurance
- Underfoot comfort and sound reduction - 14dB
- Quickly installs with tape for minimal downtime
- Can be welded and walked on same day
- Install in areas up to 98% relative humidity (A fully intact and efficient sub slab vapor barrier/retardant must be in place)
- Embossed backing allows moisture to dissipate
- No adhesive odors
- Easy removal - uplift, reuse and recycle
- Contains rapidly renewable bio-based content
- Emits low VOCs
- Authentic looking wood-grain visuals
- Has matching looks in 2mm, 2.85mm and 3.9mm
- This product does not contain PFAs

Damp problem? Fresh slab? No problem!

The revolutionary underside emboss allows Altro adhesive-free flooring to sit off the subfloor, allowing damp floors to breathe, resulting in any moisture dissipating.

Equally, they can be used on fresh concrete subfloors up to 98% relative humidity (RH). Allowing you to install flooring quickly and easily without having to wait for the substrate to dry. In some instances, Altro adhesive-free floors can be installed on subfloors that are between 7 - 10 days old.

Enlarged to show construction of Altro Wood adhesive-free



Altro Easyclean Technology



Our most advanced cleaning technology ensures ease of maintenance and enhanced infection control with the reduction of bacterial and mold growth by improved cleanability. Our newly developed technology helps to reduce general dirt pick-up and staining and improves the floor's scuff resistance.

These enhanced features reduce the need to use cleaning products and the effort required to clean the floor where hygiene is critical.

Looks great with

Altro Cantata, Altro Reliance 25, Altro Aquarius, Altro Symphonia, Altro Orchestra, and Altro wall products





Altro Wood adhesive-free shown in Vintage Cherry (rendering)
with Altro Whiterock Digiclad, AW wall designs and Altro Whiterock



AF Bleach. Oak WR335 / AM335
AFW280001 LRV 52



AF Wash. Oak WR347 / AM347
AFW280007 LRV 38



AF Urb. Cherry WR337 / AM337
AFW280004 LRV 17



AF Farm. Oak WR338 / AM338
AFW280010 LRV 38



AF Rustic Oak WR340 / AM340
AFW280005 LRV 37



AF Oak Trad. WR353 / AM225
AFW280006 LRV 25



AF Castle Oak WR335 / AM335
AFW280013 LRV 51



AF Great Oak WR339 / AM339
AFW280014 LRV 22



AF Bav. Oak WR514 / AM514
AFW280015 LRV 21

Always approve a physical sample before placing a material order. Image quality can vary and small swatches may not show the full pattern.



AF Vint. Cherry WR336 / AM239
AFW280003 LRV 22



AF Worn Oak WR322 / AM239
AFW280012 LRV 19



AF Manor Oak WR348 / AM348
AFW280008 LRV 7



AF Aut. Maple WR339 / AM339
AFW280002 LRV 24



AF Spg. Maple WR352 / AM352
AFW280011 LRV 27



AF Ant. Walnut WR341 / AM160
AFW280009 LRV 15



AF Sessile Oak WR350 / AM483
AFW280016 LRV 30



AF Honey Oak WR352 / AM352
AFW280017 LRV 21



AF Slate Oak WR478 / AM390
AFW280018 LRV 26

Always approve a physical sample before placing a material order. Image quality can vary and small swatches may not show the full pattern.



Type + class		ASTM F1303	Type I, Grade 1, Class C, smooth flooring
Thickness and wear layer		2.4mm .09" / .7mm / 28 mil wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.42 lbs./yd ² 2.4 kg/m ²	
Warranty		10 years	
Life expectancy		15 years	
Cleaning technology		Altro Easyclean	
Dynamic coefficient of friction		ANSI/NFSI B101.3	.49 wet DCoF
Static coefficient of friction		ASTM D2047	.79 dry, .94 wet SCoF
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976	36+
Static load limit		ASTM F970	1000 psi
Residual indentation		EN ISO24343-1	≤ 0.20mm
Wear (abrasion) resistance		EN 660	Group T
Castor chair abrasion		EN 425	Pass
Flexibility		EN ISO 24344	Pass
Light fastness		EN ISO 105-B02	≥ 6
Sound insulation		EN ISO 10140-3	14dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		EN ISO 26987	Good
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Embossed PVC backing.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Cantata, Altro Wood adhesive-free, Altro Adhesive-free and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information. © Copyright Altro USA 2024

LEED v4

This product may help contribute to the following credits

Altro Wood adhesive-free **4**

- Materials and resources
Renewable bio-based content **1**
- Materials and resources
Environmental product declaration **1**
- Materials and resources
Health product declaration **1**
- Environmental quality
Low emitting materials, flooring **1**

Discover more of our sustainability story and credentials at altro.com



Order samples 24 hours a day at altro.com and materialbank.com

Discover more online!



Maintenance guides




Illus. cleaning guides



Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- Specifications
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries - www.altropics.com
- Solutions by area type - ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



Front cover: Altro Wood adhesive-free shown in Vintage Cherry

📞 USA 800 377 5597

📞 CANADA 800 565 4658

✉ support@altro.com

🌐 www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information.