





# Altro Aquarius™



Cygnet | AQ2004  
WR287 / A1M79 / LRV 46




Sea Snail | AQI2024  
WR370 / A1M370 / LRV 50



Iguana | AQ2021  
WR297 / A1M20 / LRV 41



Swan | AQI2012  
WR291 / A1M01 / LRV 75




Puffin | AQI2005  
WR287 / A1M79 / LRV 46



Dragonfly | AQ2001  
WR292 / A1M292 / LRV 33



Vole | AQ2010  
WR289 / A1M265 / LRV 43



Treefrog | AQI2003  
WR293 / A1M271 / LRV 33



Walrus | AQ2007  
WR261 / A1M81 / LRV 29



Blue Penguin | AQI2002  
WR288 / A1M71 / LRV 24




Terrapin | AQI2009  
WR289 / A1M265 / LRV 40



Gosling | AQI2023  
WR369 / A1M369 / LRV 59



Tern | AQI2008  
WR261 / A1M81 / LRV 31




Newt | AQ2022  
WR368 / A1M368 / LRV 10



Otter | AQI2006  
WR290 / A1M239 / LRV 26




Salamander | AQI2011  
WR294 / A1M294 / LRV 41



Hippo | AQI2013  
WR301 / A1M82 / LRV 11



Mallard | AQI2015  
WR302 / A1M302 / LRV 13



Coral Crab | AQI2014  
WR300 / A1M42 / LRV 14





















Spoonbill | AQI2016  
WR303 / A1M303 / LRV 11



## Typical applications

Bathrooms, showers, changing rooms\*, saunas, spas, student accommodation, wet environments in social care: home adaptations, social housing.  
 \*In changing rooms where spikes and studs are used, we recommend Altro Atlas™ 40.

## Technical information

	Fire behaviour tested in acc. with Classified in acc. with	EN ISO 9239-1 EN ISO 11925-2 EN 13501-1	≥ 8 kW/m <sup>2</sup> Pass B <sub>fl</sub> -s1
	Slip resistance	EN 13893 PTV DIN 51130 / BGR 181 EN 13845 Annex C DIN 51097	≥ 0.30 / DS ≥ 50 (slider 96) R11 ESf / ESb B
	Sound insulation	EN ISO 140-8	ca. 5 dB
	Flooring type	EN 13845	Safety flooring
	Thickness	EN ISO 24346	2 mm
	Wear layer thickness	EN ISO 24340	2 mm
	Roll dimensions	EN ISO 24341	2 m x 20 m = 40 m <sup>2</sup>
	Weight	EN ISO 23997	2.6 kg/m <sup>2</sup>
	Residual indentation	EN ISO 24343-1	≤ 0.10 mm
	Classification for use	EN ISO 10874	34, 43
	Flexibility	EN ISO 24344	Pass
	Light fastness	EN ISO 105-B02	≥ 6
	Castor chair abrasion	EN 425	Yes, type W
	Wear resistance	EN 13845 Annex D	≤ 10% / 50000 cycles
	Chemical resistance	EN ISO 26987	Good
	Underfloor heating	EN 12524	Suitable
	Electrical behaviours	EN 1815	≤ 2 kV, antistatic
	VOC emissions	CDPH 1350 / Floorscore	Approved



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



1029  
EN 14041



0120  
EN 14041



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



## Sustainability



1A+ BRE generic green guide rating for resilient flooring, full details available at [www.thegreenguide.org.uk](http://www.thegreenguide.org.uk)



## Installation and maintenance

Please refer to Altro installation and maintenance instructions. Failure to follow these instructions can affect product performance. Technical information on installation and staining can be found at [www.altro.com](http://www.altro.com)

Light Reflectance Values measured in accordance with BS 8493:2008. Exact material match with samples cannot be guaranteed.  
 Codes: WR = weld rod, A1M = mastic, LRV = light reflectance value



Altro, Designed for possibilities. Made for people. Altro Aquarius, Altro Atlas and Altro Easyclean Technology are trademarks of Altro Limited.

United Kingdom

+44 (0) 1462 707 700

[enquiries@altro.com](mailto:enquiries@altro.com)

Australia

+61 3 9764 5666

[info@asf.com.au](mailto:info@asf.com.au)

Subject to alteration.