



Designed for possibilities.
Made for people.

NEW AND IMPROVED

Enhancements focused on the road ahead

Altro bus floors have been re-engineered for up to 20% weight savings, but it doesn't end there. We've also introduced a Heavy Duty Plus variant and added a range of other benefits to make the industry's first-choice safety flooring even better.

- Lighter
- Stronger
- Enhanced durability
- Naturally hygienic
- Even better to install

Build quality from the ground up with the lightest 2.7mm safety floor.

The next step in safety flooring



Altro Transflor Meta™

Typical applications:

Bus, coach, shuttle, emergency vehicles, recreational, specialty vehicles, mobility vehicles, mobile medical units, mobile food, delivery trucks, utility vehicles, people movers, and non-restricted rail.




The new and improved Altro Transflor Meta is available in 2.7mm Heavy Duty Plus and 2.2mm Heavy Duty thicknesses. Enhanced with a range of new benefits, Altro Transflor Meta is now stronger and more durable than ever. Backed up by an industry leading warranty and the assurance of sustained slip resistance to mitigate slip risks to one in a million, Altro Transflor Meta is the hard-wearing floor for hard working vehicles.

Why not streamline your installation by using our kit cutting service or self-adhesive options?


lightweight safety flooring for the transportation industry

Altro Transport Division 12648 Clark Street Santa Fe Springs, CA 90670


Altro reserves the right to change any information. Please consult altro.com or your local Sales Representative for the latest product range information.

 USA 800.382.0333  CANADA 800.565.4658  transflor@altro.com  altro.com/transport


© Copyright Altro 2022




Pewter Gray
TFM2289 (2.2 mm)
TFM2789 (2.7 mm)
WR81 / A1M81 / LRV 25




Storm
TFM22903 (2.2 mm)
TFM27903 (2.7 mm)
WR82 / A1M82 / LRV 16




Midnight
TFM22421 (2.2 mm)
TFM27421 (2.7 mm)
WR72 / A1M72 / LRV 8




Genome
TFM22202 (2.2 mm)
TFM27202 (2.7 mm)
WR83 / A1M83 / LRV15




Supra
TFM22913 (2.2 mm)
TFM27913 (2.7 mm)
WR102 / A1M200 / LRV 9




Radial
TFM22206 (2.2 mm)
TFM27206 (2.7 mm)
WR39 / A1M73 / LRV 7



Torino
TFM22274 (2.2 mm)
TFM27274 (2.7 mm)
WR248 / A1M238 / LRV 10



Black
TFM22892 (2.2 mm)
TFM27892 (2.7 mm)
WR100 / A1M00 / LRV 7



Diablo
TFM22275 (2.2 mm)
TFM27275 (2.7 mm)
WR249 / A1M249 / LRV 9

Accent and safety colors



Safety Yellow
TFM22229 (2.2 mm)
TFM27229 (2.7 mm)
WR08 / A1M200 / LRV 46



Safety White
TFM22200 (2.2 mm)
TFM27200 (2.7 mm)
WR01 / A1M01 / LRV 58

i LRV = Light Reflectance Value
A1M = Mastic
WR = Weld rod

i Color matched Weldrods (WR) and Mastics (AM) are available. You'll find their product codes under product SKUs.

i All products available in roll and kit format. Custom colors are also available.

S Samples Experience has shown that printing cannot reproduce colors accurately. If color choice is critical please request a sample of the material.

Dimensions	6'7" x 65'7" / 2 m x 20 m	
Thickness	2.2 mm	2.7 mm
Weight	4.05 lb/yd ²	4.98 lb/yd ²
Format	ROLL and KIT	

