



Altro Walkway™ 20 product datasheet

Multi-purpose slip-resistant flooring in modern and traditional looks

Altro Walkway 20

Altro Walkway 20 is our hugely popular hard-wearing 2mm slip-resistant flooring. The range shares its palette with Altro XpressLay. This enables you to combine both ranges when you need traditionally-adhered and adhesive-free flooring in adjacent areas while maintaining a consistent look.

What's even better is Altro Walkway 20 offers you two distinct looks; traditional and modern. Both looks come with Altro Easyclean technology for superior cleanability and stain resistance.

A static-dissipative version is available, specifically designed for locations where static buildup must be avoided.

Altro Walkway 20 also looks great when paired with Altro XpressLay, Altro Aquarius, Altro Wood, Altro Orchestra or even Altro Zodiac Smooth.

Typical applications

General purpose

Features + benefits

- Hard-wearing 2mm slip-resistant flooring
- Shares some colors with Altro XpressLay and Altro Aquarius for cross-product coordination
- Static-dissipative version available*
- Achieves high slip resistance ratings
- Exceeds 1000 psi
- Excellent chemical and stain resistance
- FloorScore Certified / Low VOCs

Slip resistance



It is designers, specifiers and end-users' responsibility to ensure flooring is fit for purpose, and it's part of our role here at Altro to help make this process easy. Our flooring is separated into three categories: safety, slip-resistant and smooth.

Altro Walkway 20 is a slip-resistant flooring. It's a perfect choice for many commercial areas in which your slip risk is not as high as a commercial kitchen or other wet environments, but your patrons, patients, students and employees still deserve to be secure on their feet. Slip-resistant flooring from Altro will reduce the risk of slips, give you peace of mind and look good doing so.



Altro Easyclean

Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products' slip-resistant properties to shine through.

Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention


2.0mm
thick

6'7"
width


65'5"
length

sheet
format







Swan
WR291
VMI2012P
LRV 75




Winter
WR105
VMI2053
LRV 61




Blizzard
WR79
VMI2055
LRV 44




Streetlight
WR287
VMI2005P
LRV 45




Temple
WR261
VMI2009P
LRV 27



Rock
WR84
VMI2004P
LRV 23




Fog
WR81
VMI20153
LRV 27




Nickel
WR81
VMI2019P
LRV 29


Fog available in static dissipative
through special order.
VM20153SD




Dolphin
WR86
VM2010
LRV 21




Whale
WR86
VMI2054
LRV 20



Pavement
WR83
VMI2007P
LRV 14




Skyline
WR52
VMI20332
LRV 24




Midnight
WR72
VMI20421
LRV 11




Black
WR100
VMI20892
LRV 6



Coal
WR100
VMI2058
LRV 6




River
WR71
VMI2057
LRV 22




Minster
WR289

VM2018P
LRV 40




Sand
WR20

VMI2051
LRV 40




Rodeo
WR363

VMI2020P
LRV 37




Tango
WR42

VM2031
LRV 14



Bone
WR20

VM20215
LRV 37




Biscuit
WR146

VM20907
LRV 30



Tundra
WR153

VM20910
LRV 17



Savannah
WR153

VMI2050
LRV 19



Light reflectance values (LRV)

Please keep LRVs in mind when selecting walling for areas with dementia and Alzheimer's patients, seniors or individuals with poor vision.



Color matched weldrods (WR) and mastics are available. You'll find weldrod product codes under product SKUs. Mastics can be found by scanning this QR code.





Specifications			
Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.0mm .08", homogenous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.79 lbs./yd ² 2.6 kg/m ² 220 lbs. per roll	
Warranty		10 years	
Life expectancy		15 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.8 dry, .8 wet
Dynamic coefficient of friction		ANSI/NFSI B101.3	.66 wet DCOF
Ramp test		EN 16165	R10
TRRL pendulum test		BS 7976 ASTM E303	36+
Static load limit		ASTM F970	1000 psi
Residual indentation		EN ISO 24343	≤ 0.10mm
Wear (abrasion) resistance		EN 13845 Annex D	≤ 10% 50,000 cycles
Castor chair abrasion		ISO 4918	Yes, type W
Flexibility		ASTM F137	Pass
Light fastness		EN ISO 105-BO2	≥ 6
Sound insulation		ISO 140-8	5dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Electrical behaviors (only for Altro Walkway 20 SD)		ASTM F150 EN 1081	> 10 Megaohms 10 ⁹ ≤ R ≤ 10 ⁹ Ω (VM20 SD)
Chemical resistance		ASTM F925	Tested
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Mold resistance		ASTM D3273	Tested
Fungi resistance		ASTM G21	Tested
Minimum operating temperature		-4°F (-20°C)	
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		Contains 10% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Walkway 20 and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation. Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2026

LEED facts



LEED v5

This product may help contribute to the following credits

Altro Walkway 20

Quantify and assess embodied carbon

Materials and resources, MRp2

Reduce embodied carbon

Materials and resources, MRc2

Low-emitting materials

Materials and resources, MRc3

Building product select and procurement

Materials and resources, MRc4


Discover more of our sustainability story and credentials at altro.com



material
bank

Order samples 24 hours a day at
altro.com and materialbank.com

Discover more online!



Maintenance guides




Illus. cleaning guides




Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries - www.altropics.com
- Solutions by area type - ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



 USA 800 377 5597

 **CANADA** 800 565 4658

 support@altro.com

 www.altro.com