

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Product name : Altro Solve XY
Product code : SVX5
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Industrial Solvent
Cleaning agent

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Altro Resin Systems
Unit 3 Station Road Industrial Estate
Station Road
GB– DT2 0AE Maiden Newton Dorchester
T 01300 320620
sds@altro.com - www.altro.com

1.4. Emergency telephone number

Emergency number : 01462 480480
Monday - Friday 09:00 - 17:00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Flammable liquids, Category 3	H226
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP) :



Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

	GHS02	GHS07	GHS08
Signal word (GB CLP)	: Danger		
Contains	: Xylene; Ethylbenzene; Toluene		
Hazard statements (GB CLP)	: H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H312+H332 - Harmful in contact with skin or if inhaled. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H373 - May cause damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects.		
Precautionary statements (GB CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof ventilating equipment. P260 - Do not breathe fume, vapours. P264 - Wash hands thoroughly after handling.		

2.3. Other hazards

Results of PBT and vPvB assessment

This substance does not meet the PBT criteria of UK REACH regulation, annex XIII

This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Xylene (1330-20-7), Ethylbenzene (100-41-4), Toluene (108-88-3)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Xylene (1330-20-7), Ethylbenzene (100-41-4), Toluene (108-88-3)

Results of Endocrine Disruptor assessment

The substance is not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP

Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Xylene(1330-20-7), Ethylbenzene(100-41-4), Toluene(108-88-3)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Xylene substance with workplace exposure limit(s)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 UK Index-No.: 601-022-00-9	≥0 – ≤100	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Ethylbenzene substance with workplace exposure limit(s)	CAS-No.: 100-41-4 EC-No.: 202-849-4 UK Index-No.: 601-023-00-4	< 30	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Toluene substance with workplace exposure limit(s)	CAS-No.: 108-88-3 EC-No.: 203-625-9 UK Index-No.: 601-021-00-3	< 3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after inhalation	: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. Get medical attention if irritation develops and persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Immediately give plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.
Symptoms/effects after skin contact	: May cause skin irritation.
Symptoms/effects after eye contact	: May cause eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO2). Dry powder. Water fog.
Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is flammable. Vapours may ignite.

5.3. Advice for firefighters

- Firefighting instructions : Use water to cool exposed containers, cool and disperse vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective clothing. Avoid inhalation of vapours.
Emergency procedures : Ventilate spillage area. No flames, no sparks. Eliminate all sources of ignition. Take precautionary measures against static discharge.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter sewers, surface or groundwater. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

6.3. Methods and material for containment and cleaning up

- For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Place in an appropriate container and dispose of the contaminated material at a licensed site.
Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Ensure equipment is adequately earthed. Provide adequate ventilation to minimize dust and/or vapour concentrations.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight.
Incompatible products : Oxidizing agent.

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

7.3. Specific end use(s)

1.2. Relevant identified uses of the substance or mixture and uses advised against.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Altro Solve XY	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	100 ppm
Xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	220 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
	< 100 ppm
Ethylbenzene (100-41-4)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	441 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m ³
	125 ppm
Toluene (108-88-3)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Altro Solve XY	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	289 mg/m ³
Acute - local effects, inhalation	289 mg/m ³

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Altro Solve XY	
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	174 mg/m ³
Acute - local effects, inhalation	174 mg/m ³
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m ³
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6.58 mg/l
Xylene (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	442 mg/m ³
Acute - local effects, inhalation	442 mg/m ³
Long-term - systemic effects, dermal	212 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	221 mg/m ³
Long-term - local effects, inhalation	221 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	260 mg/m ³
Acute - local effects, inhalation	260 mg/m ³
Long-term - systemic effects, oral	12.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	65.3 mg/m ³
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	12.46 mg/kg dwt

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Xylene (1330-20-7)	
PNEC sediment (marine water)	12.46 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.31 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	6.58 mg/l
Ethylbenzene (100-41-4)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	293 mg/m ³
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	15 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (marine water)	0.01 mg/l
PNEC aqua (intermittent, freshwater)	0.1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	13.7 mg/kg dwt
PNEC sediment (marine water)	1.37 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.68 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0.02 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	9.6 mg/l
Toluene (108-88-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	384 mg/m ³
Acute - local effects, inhalation	384 mg/m ³
Long-term - systemic effects, dermal	384 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	192 mg/m ³
Long-term - local effects, inhalation	192 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	226 mg/m ³
Acute - local effects, inhalation	226 mg/m ³
Long-term - systemic effects, oral	8.13 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	56.5 mg/m ³

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Toluene (108-88-3)	
Long-term - systemic effects, dermal	226 mg/kg bodyweight/day
Long-term - local effects, inhalation	56.5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.68 mg/l
PNEC aqua (marine water)	0.68 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	16.39 mg/kg wet weight
PNEC sediment (marine water)	16.39 mg/kg wet weight
PNEC (Soil)	
PNEC soil	2.89 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	13.61 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Safety glasses. Wear protective gloves. In case of inadequate ventilation, wear respiratory protection.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colourless liquid.
Odour	: aromatic.
Odour threshold	: Not available
pH	: Not available
Melting point	: -95 – 13 °C
Freezing point	: Not available
Boiling point	: 136 – 152 °C
Flash point	: > 23 °C
Flammability	: Not available
Explosive limits	: Not available
Vapour pressure	: 8 mbar @ 20°C
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 0.87 g/cm ³ @ 20°C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: > 432 °C
Decomposition temperature	: Not available
Viscosity, kinematic	: < 0.9 mm ² /s
Viscosity, dynamic	: 0.61 mPa·s
Explosive properties	: Not available

9.2. Other information

Particle characteristics	: Not applicable
--------------------------	------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapour. If stored for long periods at ambient temperature peroxides may be formed. This will be accelerated at higher temperatures.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Vapours may ignite. formation of explosive air/vapour mixtures are possible. Reacts with : Oxidising agents.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Strong acids. Oxidising substances.

10.5. Incompatible materials

Strong acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under fire conditions, Carbon oxides maybe produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
-----------------------	---

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

Altro Solve XY	
ATE UK (Dermal)	1100 mg/kg bodyweight
ATE UK (dust, mist)	1.5 mg/l/4h
Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27.124 mg/l/4h
Ethylbenzene (100-41-4)	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	28.1 mg/l/4h (OECD 403 method)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.
Xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Toluene (108-88-3)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Altro Solve XY

Viscosity, kinematic < 0.9 mm²/s

Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Xylene (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Test species:- Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (Green algae) Biomass; OECD Test Guideline 201
EC50 72h - Algae [2]	4.36 mg/l Test organisms (species): Pseudokirchneriella subcapitata (Green algae) Growth rate; OECD Test Guideline 201
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
NOEC chronic algae	0.44 mg/l Pseudokirchneriella subcapitata (Green algae) (OECD Test Guideline 201)

Ethylbenzene (100-41-4)

LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

Toluene (108-88-3)

LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
EC50 - Crustacea [1]	3.78 mg/l
EC50 72h - Algae [1]	10 mg/l
ErC50 algae	134 mg/l 3h
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Toluene (108-88-3)	
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
NOEC chronic crustacea	0.74 mg/l Ceriodaphnia dubai
NOEC chronic algae	10 mg/l Skeletonema costatum

12.2. Persistence and degradability

Altro Solve XY	
Persistence and degradability	Not rapidly degradable

Xylene (1330-20-7)	
Persistence and degradability	Not rapidly degradable

Ethylbenzene (100-41-4)	
Persistence and degradability	Not rapidly degradable

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.23 g O ₂ /g substance
Biodegradation	100 %

12.3. Bioaccumulative potential

Toluene (108-88-3)	
Bioaccumulative potential	Bioaccumulation unlikely.

12.4. Mobility in soil

Toluene (108-88-3)	
Ecology - soil	Product adsorbs onto the soil.

12.5. Results of PBT and vPvB assessment

Altro Solve XY	
This substance does not meet the PBT criteria of UK REACH regulation, annex XIII	
This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII	

Component	
Xylene (1330-20-7)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Ethylbenzene (100-41-4)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Toluene (108-88-3)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended





SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Must follow special treatment according to local regulation.
Product/Packaging disposal recommendations	: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Do not puncture or incinerate, even when empty.
Ecological waste information	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1307	UN 1307	Not regulated	UN 1307	UN 1307
14.2. UN proper shipping name				
XYLENES (XYLENES)	XYLENES (XYLENES)	Not regulated	XYLENES (XYLENES)	XYLENES (XYLENES)
Transport document description				
UN 1307 XYLENES (XYLENES), 3, III, (D/E)	UN 1307 XYLENES (XYLENES), 3, III (23°C c.c.)	Not regulated	UN 1307 XYLENES (XYLENES), 3, III	UN 1307 XYLENES (XYLENES), 3, III
14.3. Transport hazard class(es)				
3	3	Not regulated	3	3
		Not regulated		
14.4. Packing group				
III	III	Not regulated	III	III

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Not regulated	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: 3Y

Transport by sea

Special provisions (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A
Flash point (IMDG)	: 23°C to 30°C c.c.
Properties and observations (IMDG)	: Colourless liquids. Flashpoint: 23°C to 30°C c.c. Explosive limits: 1.1% to 7%. Immiscible with water.

Air transport

Not regulated

Inland waterway transport

Classification code (ADN)	: F1
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: F1
---------------------------	------

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC).

GB PIC Regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (EC 273/2004)

This product contains substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure (Toluene - 108-88-3)

15.1.2. Other Information

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
-----------------------	-------------------------------------

Altro Solve XY

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.