

Altro Wood™ Safety

Flooring type	Slip resistance	Thickness	Wear layer	Weight	Roll dimensions	Fire performance	Sound Insulation
EN 13845	PTV EN 13845 EN 13893 DIN 51130	EN ISO 24346	EN ISO 24340	EN ISO 23997	EN ISO 24341	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	EN ISO 10140
Safety flooring	≥ 36 ESf DS R10	2mm	0.7mm	2.66kg/m ²	2m x 20m = 40m ²	Bfl s1	Approx 4dB

CE 13 | Debolon Dessauer Bodenbeläge GmbH & Co. KG, Ebertallee 209, 06846 Dessau-Roßlau |
 DIN EN 13845 | DoP-No. Altro Wood Safety-RN-A025 | Reaction to fire: Bfl s1 | Slip resistance: DS | Formaldehyde: E1 |
 Electrical behaviour: < 2 kV | DIN EN 14041:2008 | 1658 | Resilient floor covering to be used within a building

Altro Wood™ Safety Comfort

Flooring type	Slip resistance	Thickness	Wear layer	Weight	Roll dimensions	Fire performance	Sound Insulation
EN 651	PTV EN 651 EN 13893 DIN 51130	EN ISO 24346	EN ISO 24340	EN ISO 23997	EN ISO 24341	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	EN ISO 10140
Safety flooring	≥ 36 ESf DS R10	2.85mm	0.7mm	2.6kg/m ²	2m x 20m = 40m ²	Cfl s1	Approx 14dB

CE 17 | Debolon Dessauer Bodenbeläge GmbH & Co. KG, Ebertallee 209, 06846 Dessau-Roßlau |
 DIN EN 651 | Reaction to fire: Cfl s1 | Slip resistance: DS | Formaldehyde: E1 | Electrical behaviour: < 2 kV |
 DIN EN 14041:2008 | 1658 | Resilient floor covering to be used within a building

Sustainability



Indication of the level of emissions of volatile substances in the ambient air that are posing a toxic hazard on being inhaled, rated on a scale from A+ (very low emissions) to C (high emissions).

†A+ BRE generic green guide rating for resilient flooring, full details available at www.thegreenguide.org.uk

i Installation and Maintenance

Install according to installation instructions and codes of practice. Refer to cleaning card. Failure to install and maintain flooring according to installation instructions can affect performance and slip resistance. Protect from other trades. Oil residue, certain cleaning agents, asphalt and anti-oxidants in some rubber can cause traffic stain. Caution, Ketone / aromatic solvents. For further technical information please visit www.altro.com

Altro, Designed for possibilities. Made for people. Altro Wood Safety, Altro Wood Safety Comfort and Altro EasyClean technology are trademarks of Altro Limited.



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.

+44 (0) 1462 707 700

www.altro.com

enquiries@altro.com

+61 3 9764 5666

www.asf.com.au

info@asf.com.au