

Capabilities brochure

Lightweight safety flooring for the global bus and rail industry

altro.com

Introduction

Altro has been creating and manufacturing high quality transport flooring for over 60 years. Driven to transform everyday spaces for the people who use them, design-led innovation is at the heart of everything we do.

We help create environments for passengers which are both inviting and safe by partnering with the industry's leading bus, coach, and rail builders globally.

Altro's unique perspective considers how our floors can perform at their best, both in service and at installation.

We partner with manufacturers and operators to provide solutions designed to enhance passenger experience and add efficiencies to assembly and maintenance.

Our collaborative approach allows customers to create vehicle interiors that tick all the performance boxes: safety, durability, comfort, and an attractive environment for passengers.

We share our customers' vision of making vehicles and fleets a more appealing, convenient and environmentally-conscious way to travel, so you can deliver the on board experience modern passengers expect.





The lightest 2.2mm and 2.7mm bus floors available

We have reduced the weight of Altro Transflor Meta[™], Altro Transflor Chroma[™] and Altro Transflor Figura[™] by 20%* and you now have a choice for the lightest 2.2mm or 2.7mm heavy duty safety floor. We've also made sure they remain as safe as ever with uncompromised slip resistance.

As a business Altro is driven by a philosophy of continuous improvement. Our products are engineered to solve real world problems in interior spaces and enhance passengers' overall travel experience.

With environmental factors such as the growing need to increase public transport usage and the transition to alternative fuels at the forefront of operators' minds, we've taken the industry's most highly regarded floor coverings and made them even better for a brighter future.

Lighter weight vehicle components contribute to greater fuel economy and facilitate the uptake of zero-carbon fuels, making for a more environmentally-conscious mode of transport.

Better still, we have achieved this remarkable weight saving with no compromise on safety with all products mitigating slip risks to an industry best one in a million. No other product offers comparable weight savings and slip resistance in a high durability, heavy duty variant.

Calculations based on new product weight in comparison to 2017/2018 product weight.

Performance

Like any interior component, Altro transport floors are designed to work in harmony to support a vehicle's overall interior design. All of our transport floors are intelligently engineered to provide maximum performance which is sustained even when subjected to the most challenging service demands.

Slip-resistant

Our bus flooring portfolio is designed to cater to a range of applications. A variety of product constructions are used across our safety and design-led products to provide the right level of protection for your vehicle, no matter the usage.

Durable

Transport vehicles incur extremely high levels of concentrated foot traffic, so hardwearing durability is a necessity of any floor. Altro is constantly working to engineer the most highly resilient transport floors which are designed to withstand the most demanding service programs – a quality backed up by warranties that cover the life expectancy of the vehicle. For our highest level of protection, ask about our 2.7mm Heavy Duty Plus products.

Lightweight construction

Our bus and rail floors are specifically engineered to offer a lightweight solution without compromising on any other performance qualities. Choose an Altro floor to support the move away from fossil fuelled vehicles while maintaining excellent slip-resistance and design options on board.

Impermeable

Even if contaminants are brought on board a vehicle, Altro transport floors continue to perform. The construction of our products, combined with heat welded installation techniques, makes them impervious to the ingress of water and dirt, protecting vehicle subfloors from damage and preventing the need for costly repairs.

Services

Altro offers a range of installation services to streamline the installation process and enhance performance in service. Save time, weight and waste, and enjoy a more reliable build on your vehicles with our range of services:



Pre-cut flooring


) Did you know?

We have reduced the weight of our products by 20% since 2017/2018.

Different constructions across the portfolio provide durability and slip resistance by maintaining contact between the floor and shoe, no matter what the contaminant.

18 - 1 - S. 1

When Altro transport floors are correctly heat welded they are completely impervious to water for long-term subfloor protection.





Introducing Heavy Duty Plus

Why compromise on weight or durability when you can enjoy the benefits of both? Altro's Heavy Duty Plus (HD⁺) range of 2.7mm safety floors are engineered for heavy bus applications.

Choose HD+ for:

- Robust surface resilience
- Excellent slip resistance
- Exclusive aggregates
- Comfort underfoot
- Naturally hygienic
- Strongest ever construction
- Our best ever lightweight technology

Specifically engineered to meet the diverse challenges of the modern heavy bus market, our new lighter weight 2.7mm Heavy Duty Plus (HD⁺) and 2.2mm Heavy Duty flooring variants deliver enhanced durability with a reduction in weight.

Developed to offer the optimum balance of lightweight technology, surface resilience, slip resistance and comfort underfoot, our HD⁺ ranges let you take the next step in safety flooring.

Available across our trusted collection of Altro Transflor Meta, Altro Transflor Chroma, and Altro Transflor Figura products and supported by a 15-year non-prorated warranty, the HD⁺ ranges are our hardest working floors for the hardest working vehicles.

Your fleet deserves the best - put a plus on your bus.





Longer lasting looks

Altro floors have always been known for their hard wearing durability, but with the latest improvements, they are now even stronger than ever.

With significant improvements made to strength and an up to 110% increase in scratch resistance, Altro floors are now even better at retaining their long term visual appearance to better support ease of maintenance. This ensures that - with proper cleaning - floors stay looking great to provide the on board environment contemporary passengers expect.

With on board cleaning and hygiene now a bigger concern than ever, it's reassuring to know that Altro bus floors are equipped to support the most rigorous cleaning programs. In addition to the benefits achieved through improved durability, vinyl floors are also naturally hygienic – in line with the latest industry demands.

As an inert material, vinyl does not encourage the growth of bacteria in the same way other materials do. Furthermore, as a non-porous material with high impact resistance it prevents cracks and chipping which can trap bacteria.







Greater performance

- Tensile strength increased by up to 15%
- Elongation strength increased by up to 20%
- Weight reduced by up to 20%
- Scratch resistance improved by up to 110%
- Tear propagation strength improved by up to 40%

Making the difference

Improvements made throughout the entire thickness of Altro floors provide improved strength and durability, while maintaining outstanding slip resistance.

The results of these advancements mean that our floors are now stronger than ever before, enabling our floors to withstand even greater service wear.

The collective advancements have been achieved through a combination of enhanced raw materials and manufacturing innovation. This means that Altro floors still look as good as ever, but beneath the surface they're performing even better.

They can now withstand even greater punishment from both foot and wheel traffic and general wear and tear. In addition to this, the newly enhanced material - when correctly welded - will also facilitate a greater level of fusion between floors and weld rods to contribute to stronger seams.

Safety without compromise

What are the chances of a passenger slipping on a moving vehicle?

With Altro safety floors for transport, it's as small as one in a million.*

As the inventors of safety flooring, Altro creates specific products that directly address the costly risks presented by potential slips and falls.

Our safety floors for transport are specifically engineered to meet the world's most stringent safety standards.

*CIRIA, Safer Surfaces to Walk on

Maintaining contact

The presence of surface contaminants – in even the smallest amounts – can reduce contact between the floor and the sole of passengers' shoes. When subjected to the downward pressure of passengers' feet, the aggregates in Altro safety floors are able to penetrate surface contaminants to maintain the contact between the floor and the shoe.

How it works:

Exclusive aggregates in the floor, aided by the floor's unique emboss, maintain contact with passengers' shoes even when contaminants are present, whether they're wet or dry. No matter what is tracked inside a vehicle, your passengers and staff are protected from slips.

Sustained performance

Our safety products are engineered to meet the most stringent safety recommendations worldwide, including London's Bus Safety Standard. All Altro safety bus flooring products are created with effective and sustained slip resistance, achieving an ex-factory pendulum test value of \geq 36, rising to \geq 40 after six months, without the need for any surface additives.



10



Did you know?

Altro's safety range for transport is engineered to meet the world's strictest safety standards.



10060

000


Э

20.00



Altro Transflor Meta[™]

A lightweight, chip-free bus floor with excellent sustained slip resistance engineered for resilience and top performance, with simplicity and practicality.



Pewter Grey TFM2289 (2.2 mm) TFM2789 (2.7 mm) WR81 / AM81 / LRV 25



Genome TFM2202 (2.2 mm) TFM2702 (2.7 mm) WR83 / AM83 / LRV 15




Torino TFM2274 (2.2 mm) TFM2774 (2.7 mm) WR248 / AM238 / LRV 10

Accent and safety colors



Safety yellow TFM2229 (2.2 mm) WR08 / AM200 / LRV 46



TFM22903 (2.2 mm) TFM27903 (2.7 mm) WR82 / AM82 / LRV 16



Supra TFM22913 (2.2 mm) TFM27913 (2.7 mm) WR102 / AM200 / LRV 9



Black TFM22892 (2.2 mm) TFM27892 (2.7 mm) WR100 / AM100 / LRV

Safety white


WR01 / AM01 / LRV 58



Midnight TFM22421 (2.2 mm) TFM27421 (2.7mm) WR72 / AM72 / LRV 8



Radial TFM2206 (2.2 mm) TFM2706 (2.7 mm) WR39 / AM73 / LRV 7



Diablo TFM2275 (2.2 mm) TFM2775 (2.7 mm) WR249 / AM249 / LRV 9





LRV = Light Reflectance Value AM = Mastic WR = Weld rod











Altro Transflor Chroma[™]


A lightweight, chipped bus floor with excellent sustained slip resistance engineered for resilience and top performance, with simplicity and practicality.




WR81 / AM81 / LRV 26




Viper WR83 / AM83 / LRV 14




TFCR2233 (2.2 mm) TFCR2733 (2.7 mm) WR83 / AM83 / LRV 15






WR83 / AM83 / LRV 14




TFCR2702 (2.7 mm) WR83 / AM83 / LRV 14



Patriot



WR62 / AM62 / LRV 10



WR83 / AM83 / LRV 16



WR72 / AM72 / LRV 8

TFCR2275 (2.2 mm) TFCR2775 (2.7 mm) WR249 / AM249 / LRV 15

WR83 / AM83 / LRV 14

Gene




Forester WR474 / AM308 / LRV 12


WR83 / AM83 / LRV 14




TFCR22914 (2.2 mm) TFCR27914 (2.7 mm)



Sprint TFCR2274 (2.2 mm) TFCR2774 (2.7 mm) WR248 / AM238 / LRV 12



Sigma TFCR2282 (2.2 mm) WR83 / AM83 / LRV 14



Compatible with:





LRV = Light Reflectance Value AM = Mastic









1atinum in Charge ltro Transflo Chroma™ Pl




Altro Transflor Chroma Platinum[™]

A lightweight, metallic-look chipped bus floor with excellent sustained slip resistance engineered for resilience and top performance, with simplicity and practicality.










TFCRP27007 (2.7 mm) WR101 / AM72 / LRV 13


Chroma Platinum is available in 2.2mm as a special order only with minimum quantity 624 SY.









WR101 / AM72 / LRV 13



TFCRP27003 (2.7 mm) WR249 / AM249 / LRV 16



WR83 / AM83 / LRV 15



TFCRP27002 (2.7 mm) WR83 / AM83 / LRV 15





LRV = Light Reflectance Value









Altro Transflor Figura[™]

2.7mm lightweight chipped bus floor with excellent sustained slip resistance engineered for resilience and top performance, with simplicity and practicality.


Firework design



Boom | TFFG2701F WR63 / AM239 / LRV 21



Sparkler | TFFG2702F WR81 / AM81 / LRV 25




Crackle | TFFG2706F WR83 / AM83 / LRV 15




Laser | TFFG2703F WR231 / AM73 / LRV 11



Rocket | TFFG2704F WR72 / AM72 / LRV 8



Pinwheel | TFFG2705F WR100 / AM100 / LRV 7



Scaled-down example of pattern


Windmill design




Titan | TFCR27402 WR63 / AM239 / LRV 21




Orion | TFCR27401 WR83 / AM83 / LRV 14



Eros | TFCR27403 WR100 / AM100 / LRV 7



Saturn | TFCR27406 WR249 / AM249 / LRV 15



Pluto | TFCR27404 WR83 / AM83 / LRV 15



Neptune | TFCR27405 WR231 / AM73 / LRV 11



Scaled-down example of pattern





LRV = Light Reflectance Value AM = Mastic WR = Weld rod







Altro Transflor Figura[™] in Laser

Altro Transflor Wood[™] in Century Oak and Antique Walnut

- Ban - 20

BBK

emerald

Altro Transflor Wood[™]

A resilient wood-look bus floor with assured slip resistance and comfort underfoot.



Oak Traditions TFWSA2213F WR353 / AM225 / LRV 25



Seasoned Cherry TFWSA2209F WR343 / AM246 / LRV 1



Urban Cherry TFWSA2203F WR337 / AM337 / LRV 17



Spiced Bamboo TFWSA2219F WR342 / AM224 / LRV 21



Antique Walnut TFWSA2207F WR341 / AM160 / LRV 15



Vintage Cherry TFWSA2202F WR336 / AM239 / LRV 22



TFWSA2223F WR471 / AM337 / LRV 16



Oak Riche TFWSA2214F WR227 / AM227 / LRV 10



Manor Oak TFWSA2216F WR348 / AM348 / LRV 7



Jacobean Oak TFWSA2222F WR470 / AM83 / LRV 11



Century Oak TFWSA2212F WR346 / AM62 / LRV 3



TFWSA2226F WR232 / AM100 / LRV 14








Altro Transflor Artis[™]

A resilient natural mineral-inspired design flooring for bus with a quality finish and comfort underfoot.




Kala TFAR22002 WR482 / AM482 / LRV 13




Halite TFAR22003 WR418 / AM239 / LRV 2




Lazulite TFAR22011 WR493 / AM493 / LRV 9




Maras TFAR22004 WR391 / AM82 / LRV 18




Adelite TFAR22001 WR41 / AM41 / LRV 1




Fleur TFAR22008 WR481 / AM83 / LRV 15




Trapani TFAR22005 WR314 / AM82 / LRV 1



Ruby TFAR22007 WR41 / AM41 / LR\




Palladium TFAR22009 WR301 / AM82 / LRV 11



TFAR22006 WR485 / AM485 / LRV



Pyrite TFAR22012 WR62 / AM62 / LRV 9



Onyx TFAR22010 WR485 / AM485 / LRV 8





LRV = Light Reflectance Value AM = Mastic WR = Weld rod









Altro Transflor Tungsten[™]


A high performance NFPA 130 compliant rail product with easy maintenance and wide design options.



Whirlwind TUN20910 (2.0 mm) WR79 / AM191 / LRV 3



Fog TUN203001 (2.0 mm) WR 81/ AM81 LRV 27



Gust TUN20908 (2.0 mm) WR81 / AM81 LRV 23




Storm TUN203009 (2.0 mm) WR 82/ AM82 LRV 16




Supercell TUN20912 (2.0 mm) WR 473/ AM308 LRV15



Breeze TUN20909 (2.0 mm) WR 86/ AM86 LRV 18



Azure TUN203007 (2.0 mm) WR 249/ AM249 LRV 15




Sleet TUN20907 (2.0 mm) WR 231/ AM73 LRV 10




Arcus TUN20906 (2.0 mm) WR 101/ AM72 LRV 11



Midnight TUN203005 (2.0 mm) WR 72/ AM72 LRV 11



Sprite TUN20911 (2.0 mm) WR 248/ AM238 LRV 11



Vortex TUN20905 (2.0 mm) WR 277/ AM100 LRV 6



Firestorm TUN20904 (2.0 mm) WR 100/ AM100 LRV 5



RV = Light Reflectance Valu M = Mastic R = Weld rod



Technical table

Bus

		Altro Transflor Meta / Chroma / Platinum 2.2 mm	Altro Transflor Meta / Chroma / Platinum 2.7 mm
Flooring type	EN 13845 ASTM F1303	Safety flooring	Safety flooring
Slip resistance	BAM EN 13893 EN 13845 PTV ASTM D2047 DIN 51130	Dry - very slip resistant Wet - slip resistant - - ≥ 36 ≥ 0.6 R10	Dry - very slip resistant Wet - slip resistant - - ≥ 36 ≥ 0.6 R10
Thickness	EN ISO 24346	2.2 mm / 0.088"	2.7 mm / 0.108"
Wear layer thickness	EN ISO 24340	1.2 mm / 0.047"	1.4 mm / 0.055"
Flexibility	EN ISO 24344 ASTM F1303	Pass	Pass
Weight	EN ISO 23997	4.05lb/sy / 2.2 kg/m2 ±10%	4.98lb/sy / 2.7 kg/m2 ±10%
Roll dimensions	EN ISO 24341	2 m x 20 m - 40 m2 6'7" x 65'7"	2 m x 20 m - 40 m2 6'7" x 65'7"
Light fastness	EN ISO 105-B02 ASTM F1515	≥ 6	≥ 6
Wear resistance	EN 13845 ASTM C501	≤ 10% particles lost over 50,000 cycles	≤ 10% particles lost over 50,000 cycles
Residual indentation	EN ISO 24343 ASTM F970	≤ 0.10 mm	≤ 0.10 mm
Fire performance	DIN 5510 ECE-R118 UIC 564-2 FMVSS 302 / CMVSS 302 ASTM E648 NFPA 130	SF3 Pass Class A Pass Class 1 -	SF3 Pass Class A Pass Class 1 -
Chemical resistance*	EN ISO 26987	Good	Good
Castor chair abrasion	EN 425	Pass	Pass
Electrical behaviours	EN 1815	≤ 2kV antistatic	≤ 2kV antistatic
Sound insulation	ISO 140-8	5dB	5dB

Altro Transflor Figura 2.7 mm

Altro Transflor Wood

Altro Transflor Artis

Altro Transflor Tungsten

		÷	
Safety flooring	Safety flooring	Heterogeneous floor	Safety flooring
Dry - very slip resistant Wet - slip resistant - - ≥ 36	Dry - very slip resistant Wet - slip resistant - - ≥ 36	- - DS -	-Dry - very slip resistant -Wet- slip resistant DS ESf ≥ 40
≥ 0.6	≥ 0.6	≥ 0.6	≥ 40 ≥ 0.6
R10	2 0.0 R10	2 0.0 R10	2 0.0 R11
2.7 mm / 0.108"	2.2 mm / 0.088"	2.2 mm / 0.088"	2.0 mm / 0.08"
1.4 mm / 0.055"	0.7 mm / 0.027"	0.7 mm / 0.027"	1 mm / 0.08"
Pass	Pass	Pass	Pass
4.98lb/sy / 2.7 kg/m2 ±10%	4.93lb/sy / 2.68 kg/m2	4.93lb/sy / 2.68 kg/m2	4.98lb/sy / 2.7 kg/m2
2 m x 20 m - 40 m2 6'7" x 65'7"	2 m x 20 m - 40 m2 6'7" x 65'7"	2 m x 20 m - 40 m2 6'7" x 65'7"	2 m x 20 m - 40 m2 6'7" x 65'7"
≥ 6	≥ 6	≥ 6	≥ 6
≤ 10% particles lost over 50,000 cycles	≤ 10% particles lost over 50,000 cycles	Group T	≤ 10% particles lost over 50,000 cycles
≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm	
SF3 Pass -	- Pass -	- Pass -	SF3 Pass
Pass	Pass	Pass	Pass
Class 1	-	-	Class 1
	-	-	Pass
Good	Good	Good	
Pass	Pass	Yes, type W	Pass
≤ 2kV antistatic	≤ 2kV antistatic	≤ 2kV antistatic	≤ 2kV antistatic
5dB	5dB	5dB	4dB

Logos and pre-cut flooring service

Logos and signage

The accuracy of our cutting technology also enables us to offer the production of intricate detailing that can be inlaid directly into the floor. From universal signage and wayfinding solutions through to exact recreations of your company logo, precision-cut icons and sign designs will save you time and make your vehicles stand out.

Pre-cut flooring kits

With time pressure being a constant challenge to builders and operators alike, we offer our pre-cut flooring service to enhance installation efficiencies. Altro's pre-cut floors minimize installation time and waste, simplify the process of fitting a floor, and reduce interior assembly and maintenance time. Using a floorplan of your vehicle, we use our inhouse cutting technology to prepare your order to the exact dimensions required before delivering convenient lighter, smaller pre-cut rolls, saving you time and effort. Especially useful for those tricky confined areas with turns, twists and undulations, Altro's pre-cut floors provide the most direct route to installation success.



Logo designs are cut for desired requirements.



Sections can be moved easily into place.

Once affixed the flooring is ready for installation.

Wheelchair logo using Altro Transflor Meta™ in safety colors

Self-adhesive floors

Installation advantages

Designed specifically to remove the need for manual adhesive application and curing times, Altro self-adhesive flooring provides further time-saving possibilities. The pressure-sensitive backing is available for all our bus flooring products and completely cuts adhesive application and curing time. Once positioned and bonded, self-adhesive flooring can be welded and walked on immediately, allowing interior assembly and refurbishment to continue without delay. The solution works with all commonly used subfloors, providing consistent results every time. It can also be used with pre-cut kits to achieve even greater efficiencies. Altro is the only manufacturer with the capability to offer both solutions in-house for consistent quality control.



The intuitive system is easy to use, requires no specialist tools, and by removing the need for adhesive mixing and application, reduces mess. Better still, the lack of traditional adhesives ensures a cleaner interior air quality for your installation team, removing almost all harmful VOC emissions. Meanwhile, the uniform application of adhesive applied to the backing results in an adhesive weight saving of 60% per m² compared to the recommended applications of polyurethane and contact adhesives.



Did you know?

Using Altro's self-adhesive solution will save you 60% adhesive weight per $\ensuremath{\mathsf{m}}^2$





"With Altro's self-adhesive service we can save an estimated 4 hours on installation time. This has huge implications for savings on labor costs as well as increasing the efficiency of our output of vehicles."

Cheyne Rauber,

Charles I m

Vice President / General Manager, Matthews Specialty Vehicles, US

the life of the

All Altro bus floors are available in a self-adhesive format

Expert advice ensures optimum installations

Technical support

Installation guidance

To gain the best possible performance from your Altro flooring, it's important that it's installed correctly. Our highly-skilled technical services team can offer free expert advice to help ensure installers know how to achieve the best possible results. This not only means that your team develop their own working knowledge and efficiency, but also that any potential failures arising from installation issues are reduced to an absolute minimum.

Continued support

When you invest in Altro flooring, you enter into a partnership that we take seriously. We're available to advise and instruct on technical areas to provide guidance and facilitate product longevity. Whether you have a situation with a subfloor, a question on cleaning or you're wondering about a weld, if you require advice we're here to listen and here to help.

The Altro Transflor Virtual Training Center is available to all Altro Transport customers for personal, live, fully-interactive instruction and installation questions tailored to your specific needs. See the back cover for more information.



Did you know?

Altro offers a wide range of weld rods in different colors and profiles to help you achieve the best possible finish.

Cleaning and maintenance

Keep up performance

All Altro bus floors are engineered to ensure an easy and fast cleaning and maintenance program. Gone are the days where safety floors meant a maintenance nightmare – all of our floors, regardless of construction, offer improved ease of cleaning and superior scuff and stain resistance.

In order to keep our floors looking great and performing well, Altro recommends a robust cleaning program incorporating both routine and deep cleaning, as needed on each individual vehicle.

Maintain appearance

Cleaning programs can be further complemented by the random scatter patterns of flooring aggregates and by the different patterned designs available across the portfolio. Aside from enhancing slip resistance, our aggregates also distract the eye to break up the appearance of common dirt deposits. This ultimately means that standard daily cleaning programs are sufficient to ensure the floor retains its appearance between incremental maintenance deep cleans.

For the best results on bus floors, Altro recommends the use of AltroClean 44^{TM} .



Cleaning instructions available online at altro.com



Altro Transflor Chroma[™] in Strada

1.1





Sustainability

Living a more sustainable lifestyle is one of the biggest draws for passengers to choose public transport over their own private cars, so we believe that fitting your vehicles with sustainably conscious components shows a strong commitment to a greener environment.

Raw materials

At Altro, sustainability drives the choices we make. It starts with the environmentally friendly raw materials we choose to go into our products which enable us to produce ortho-phthalate-free vinyl floors containing bio-plasticisers.

Recycling

Our commitment to sustainability has also enabled us to become the first manufacturer to recycle traditional safety flooring in-house. Altro flooring even contains recycled particulates including postconsumer recycled glass, which would otherwise be destined for landfill.

Since 2014 we've achieved 0% waste-to-landfill, an achievement to be proud of.

Passing on the benefits

To further support our ongoing vision – and those of our customers – we offer a range of services which aid in the sustainability of your project.

Save on waste with our pre-cut flooring, meaning no flooring goes to landfill.

Reduce harmful VOCs with our self-adhesive installation method, meaning cleaner air.

Operate on better fuel efficiency with our lightweight product construction.


Accessories, tools, and maintenance products

Altro can supply a wide range of accessories to ensure a complete engineered system for your transportation flooring project. We have a full range of trims and finishing details, stair nosings, adhesives, color matched sealants, weldrods, maintenance supplies and all of the tools you need to ensure a professional installation.





Tools



Flooring accessories

- 1 Watch your step tread and riser / ASF STEPKIT
- 2 Weldrod HB type / ASF WR###HB
- 3 Altromastic sealant / ASF AM###
- 4 Aluminum nosing w/insert / ASF T36T w/yellow
- 5 Vinyl stepedge white / ASF STEPEDGEW9
- 6 Vinyl stepedge yellow / ASF STEPEDGEY9
- 7 Trim black / ASF TRIMEDGEB
- 8 Trim gray / ASF TRIMEDGEG
- 9 Covestick .75" x 79" / ASF CF20R
- 10 Covestick 1" x 60" / ASF COVESTICK
- 11 Aluminum nosing w/insert / ASF T36T w/white
- 12 Covestick 1.50" x 79" / ASF CF38R
- 13 Weldrod / AST WR###
- 14 ADA logo / ASF WCL12x12



Cleaning accessories

Maintenance guide / TFL MAINTLAM
AltroClean[™] 44, 5 liters / ASF 44CLEANER
AltroClean[™] 44, 1 liter / ASF 44CLEANER1.0
Installation and maintenance CD / TFL INSTALLCD
Microfiber mop head / OTH MOPMF
Deck brush / OTH SWIVEL

Proper care and maintenance of Altro safety flooring is critical for transportation applications. Not only will it keep your vehicle looking great, it will last longer and provide premium slip resistance. Altro recommends following our detailed care plan as well as using specified cleaning products.



Adhesive accessories

- 1 Altro Ecofix+™, 1 gallon / ADH ECP1.0
- 2 Altro Ecofix[™] 25E, 2 gallon / ADH EC25E2.0
- 3 Contact adhesive / ADH 81651.0
- 4 Altrofix[™] 30 polyurethane adhesive / ADH AL301.0
- 5 Trowel handle / AST TH
- 6 Trowel blade / AST TBFFA

Samples

If color choice is critical, please request a sample of the material.

800.382.0333

🖻 samples@altro.com



<image><image>

- · Personal, live, fully-interactive instruction tailored to your specific needs
- No cost
- Quick appointments and booking times
- Available exclusively to Altro customers
- Call today to schedule an appointment 800.382.0333 x3530

Altro USA - Transport Division 12648 Clark Street, Santa Fe Springs, CA 90670 USA 800.382.0333 CANADA 800.565.4658 transport@altro.com

Content correct at time of going to print. Altro reserves the right to change any detail. © Copyright Altro 2023

altro.com