



**altro**

# Altro QuickFix 3042 usage instructions

updated 11/15/18

## Usage instructions

- Areas to receive Altro QuickFix 3042 adhesive must be free from water, concrete silt and any other contaminants that could compromise adhesive adhesion.
- The saw cut that the gulley angle/edge is going to be fit into, and the surface of the concrete where it will be applied, and all other areas that the Altro QuickFix 3042 adhesive will be bonding to, must be completely and permanently dry before adhesive application can take place.
- Altro QuickFix 3042 adhesive may also be used for certain small area gluing.
- All gulley angle and/or gulley edge must be precut to ensure proper fit prior to the beginning of adhesive application.
- Apply the Altro QuickFix 3042 adhesive on the top edge and in the saw cut of the gulley angle and/or gulley edge installation area.
- Install the gulley angle and/or gulley edge into the saw cut making certain it is completely embedded into the adhesive. Firmly roll gulley with hand roller/seam roller making certain that the gulley is fitted tightly to the substrate.
- Using a small scraper or putty knife, remove any excess adhesive. If adhesive is on the surface of the gulley, remove using a small amount of isopropyl alcohol (IPA), mineral spirits or acetone to remove excess wet adhesive. These chemicals must be thoroughly cleaned and rinsed off immediately after use as they will cause damage to the flooring or gulley edge/angle.
- It may also be necessary to weigh down the gulley until the adhesive has a chance to setup. This will ensure that the gulley is fully seated into the adhesive with no voids.
- Always allow the adhesive to setup completely (typically 30 to 60 minutes) prior to cutting and fitting the Altro safety floor into the gulley. Note: The flooring material should be scribed or trace cut into the gulley to ensure a net fit.



Example by COX

Photo credit: [www.cox-applicators.com](http://www.cox-applicators.com)

Note: Altro QuickFix 3042 adhesive requires that it be applied with a dual plunger 400 ml cartridge gun.