



Altro W39™

Two-part polyurethane adhesive for Altro wall panels

Features and benefits

- Solvent-free wall adhesive
- Contains low Vocs
- Freeze-thaw stability: 5 cycles at 0° F
- Complies with South Coast Air Quality Management District #116 (SCAQMD)
- 2 year shelf life

Applications

Altro W39 adhesive is a two-part, solvent-free, polyurethane adhesive developed and recommended for the installation of Altro wall panels over permanently clean, dry and sound wall surfaces.

Altrofix W39 is recommended for use when heat-welding is specified. It is for use with both absorbent and non-absorbent/non-porous substrates, for use in wet and high humidity environments as well as dry use environments. When in doubt, use this adhesive.

Specifications

Altro W39 Part A mixes with Part B to form a one gallon pail of adhesive. Approximate adhesive spread rate using a 3/16th square notch trowel is 32 s/f per gallon.

For installation instructions, please consult the Altro Whiterock installation guide or adhesive label.

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and substrate texture and porosity. Altro does not warrant nor guarantee actual adhesive coverages.



LEED facts

LEED v4

This product may help contribute to the following credits

Altro W39

1



Environmental quality
Low emitting materials, adhesives

1

Discover more of our sustainability story and credentials at altro.com