



Designed for possibilities.
Made for people.



Altro Walkway™ 20 SD product datasheet

Static-dissipative slip-resistant flooring for electrically sensitive installations

Type + class		ASTM F1303	Type II, Grade 1, Class A, safety flooring
Thickness and wear layer		2.0mm .08", homogenous construction	
Roll dimensions		6'7" x 65'5 2m x 20m	
Weight		4.79 lbs./yd ² 2.6 kg/m ²	
Warranty		10 years	
Cleaning technology		Altro Easyclean	
Static coefficient of friction		ASTM D2047	.78 dry, .8 wet
Dynamic coefficient of friction		ANSI/NFSI B101.3	.66 wet DCOF
Ramp test		DIN 51130	R10
TRRL pendulum test		BS 7976 ASTM E303	36+
Static load limit		ASTM F970	1000 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 105-B02	≥ 6
Sound insulation		ISO 140-8	5dB
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Surface Resistivity		EN 1081	2x10 ⁷ Ω
Minimum operating temperature		-4°F (-20°C)	
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350 FloorScore	Pass Certified
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		Contains 10% pre-consumer & 10% post-consumer recycled content.	
Composition	Aluminum trioxide and colored quartz aggregate throughout thickness. Silicon carbide also present on traditional "sparkly" hues. Altro Easyclean incorporated for exceptional cleanability.		
Backing	Non-woven polyester/cellulose glass fiber reinforcement scrim.		

LEED facts

This product may help contribute to the following credits

Altro Walkway 20 6

- Materials and resources

Contains recycled content

1
- Materials and resources

Renewable bio-based content

1
- Materials and resources - EPD

Environmental product declaration

Type III product specific

1
- Materials and resources - HPD

Health product declaration

1
- Environmental quality

Low emitting materials, flooring


1
- Environmental quality

Low emitting materials, adhesives

1

Discover more of our sustainability story and credentials at altro.com/sustainability

Altro Walkway 20 SD color availability



Fog SD VM20153SD
WR81 / AM81 LRV 27

Additional colors of Altro Walkway 20 may be ordered in a static dissipative option. Please discuss minimum order quantities and shipping time with your Altro representative.

2mm
thick

6'7"
width

65'5"
length

sheet
format

Follow us



USA 800 377 5597

CANADA 800 565 4658

support@altrofloors.com

www.altro.com