



A great, multi-purpose, flooring adhesive for many jobs — tile, lvt, carpet tile and more!

EcoFix™ 25E

Environmentally friendly, pressure sensitive, acrylic adhesive

Features and benefits

- Installs in areas up to 90% RH
- FloorScore® Certified
- 2 year warranty
- Non-flammable
- Solvent-free
- Excellent moisture and alkali resistance
- Excellent plasticizer resistance
- Freeze-thaw stability: 5 cycles at 0° F
- Low odor
- Easy to trowel
- Easy clean up
- 18 month shelf life

Applications

EcoFix 25E is an environmentally friendly water dispersed, non-flammable, pressure-sensitive adhesive developed for the installation of tile and lvt. EcoFix 25E is to be used over industry-approved absorbent and non-absorbent substrates where excessive surface moisture is not a factor. EcoFix 25E can be installed in areas with up to 90% RH per ASTM F2170.

Specifications

Approximate coverage for EcoFix 25E is 145 square feet per gallon.

For installation instructions, consult the Altro tile flooring installation guides or adhesive label.

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and subfloor texture and porosity, Altro does not warrant nor guarantee actual adhesive coverages.

EcoFix 20E vs. EcoFix 25E

EcoFix 20E is a harder-setting adhesive than EcoFix 25E; they are both water-based acrylic adhesives with the 25E being used primarily as a pressure-sensitive adhesive for the setting of our tile products and the 20E being the adhesive of choice for our sheet goods.



Sustainability

Altro is fully committed to sustainability. Through careful product development, our expert team of technicians and chemists have worked to develop healthy, cost effective adhesives that perform and are compliant with even the most stringent environmental regulations.

LEED facts



LEED v4 This product may help contribute to the following credits

EcoFix 25E	1
 Environmental quality Low emitting materials, adhesives	1

Discover more of our sustainability story and credentials at altro.com

