

Altro Whiterock™ hygienic doors

specification details

JULY 2021



A range of top quality timber door and frame sets encapsulated in Altro Whiterock PVCu cladding. Designed for use on their own, or as part of the Altro Walls complete system, with Altro Whiterock walls and ceilings. All doorsets have the Altro 10 year product warranty.

Standard specification

Core:	40mm thickness solid timber construction
Facing:	2.5 thick EU Grade Altro Whiterock™ PVCu cladding. Top and bottom are sealed.
Door:	Standard door has formed leading edges finished to centre joint incorporating intumescent seals.
Frame:	40mm thick joinery grade timber faced with 2.5 mm Altro Whiterock™ PVCu cladding. The depth varies based on throat size.
Door stops:	20mm thick solid timber faced with 2.5 mm Altro Whiterock™ PVCu cladding.
Hardware:	Customisable.
Sizes:	Bespoke
Manufacturing:	Hardware fully fitted as standard. Client own hardware can be incorporated into the door manufacturing process. Ask for details.
Optional extras:	Customisable.
Vision panels:	600mmx600mm and 600mmx200mm standard size. Other dimensions available as non standard within the manufacturer limitation.
Colours & patterns:	White, Satins and Decorative ranges.
Miscellaneous:	Pull handle and overhead closure Closure Sliding doors Double action doors

for further information or technical advice
 tel: 03 9764 7000 e-mail info@asf.com.au or explore asf.com.au

Altro APAC Pty Ltd - 3 St Andrews Court, Rowville, Vic, 3178

