



Designed for possibilities.
Made for people.

Altro Dolce™ Tile

Decorative tile with enhanced vinyl content



3mm
thick

18"
width

18"
length

tile
format



Dia
AD501

LRV 68



Piedra
AD502

LRV 52



Madrid
AD505

LRV 51



Leche
AD512

LRV 65



Porcelana
AD525

LRV 59



Marmol
AD507

LRV 52



Torta
AD529

LRV 61



Pastel
AD527

LRV 57



Granito
AD509

LRV 49



Aceituna
AD506

LRV 41



Cemento
AD503

LRV 28



Noche
AD504

LRV 10



Churro
AD601

LRV 40



Barcelona
AD508

LRV 56



Playa
AD526

LRV 60



Mostaza
AD519

LRV 38



Tierra
AD514

LRV 36



Tabaco
AD515

LRV 19



Paella
AD520

LRV 45



Ladrillo
AD511

LRV 19



Naranja
AD606

LRV 31




Sangria
AD611

LRV 13



Uva
AD608

LRV 8



Rio
AD524

LRV 15



Oceano
AD609

LRV 30



Agua
AD523

LRV 35



Cielo
AD532

LRV 59



Limon
AD521

LRV 50



Cilantro
AD605

LRV 38



Lago
AD522

LRV 20



Light reflectance value (LRV)

Please keep LRVs in mind when selecting flooring for areas with dementia and Alzheimer's patients, seniors or individuals with poor vision.



Request a sample at altro.com/samples
or 800.377.5597 (USA) 800.565.4658 (CAN)

Specifications			
Type + class		ASTM F1303	Type A, Grade 1, Class A, smooth tile flooring
Thickness and wear layer		3.0mm .12" wear layer, homogeneous construction	
Tile dimensions	18" x 18" 45.7cm x 45.7cm		
Weight		44.35 lbs/carton 20.12kg/carton (15 tiles/carton)	
Warranty		10 years	
Cleaning technology	Factory finished PU coating		
Static coefficient of friction		ASTM D2047	Greater than .6
TRRL pendulum test		BS 7976	Less than or equal to 36
Static load limit		ASTM F970	2500 psi
Indentation		EN 433	≤ 0.10mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility		ASTM F137	Pass
Light fastness		EN 20105-B02	≥ 6
Sound insulation		IIC rating	54, with Hush underlayment 64
Electrical behaviors		EN 1815	≤ 2kV Antistatic
Fire and smoke performance		CAN/ULC - S102.2 ASTM E648 ASTM E662	Tested Class I < 450
Chemical resistance		ASTM F925	Tested
VOC emissions		CA 01350	Pass
Bio-based content		Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content		Ortho-phthalate-free	
Recycled content		Contains 72% pre-consumer recycled content.	
Composition	Homogeneous vinyl with through pattern construction		
Vinyl content	Vinyl content varies by color but is always greater than 10%		
Installation and maintenance	Altro flooring must be installed by a professional flooring installer that has attended an Altro training clinic. Installation procedures available at altrofloors.com/downloads , training clinic information at altrofloors.com/training . Proper care of Altro flooring is critical. Please consult our cleaning procedures available at altrofloors.com/downloads . Failure to install, heat weld, and/or maintain correctly could void the warranty.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro and Altro Dolce are all trademarks of Altro Limited. Content was correct at time of creation.
Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.
© Copyright Altro USA 2019

LEED facts 

LEED v4 This product may help contribute to the following credits

Altro Dolce Tile 3

-  Materials and resources
Contains recycled content **1**
-  Environmental quality
Low emitting materials, flooring **1**
-  Environmental quality
Low emitting materials, adhesives **1**

Discover more of our sustainability story and credentials at altro.com/sustainability