

Altro Whiterock Satins

BPIR Declaration

Version: Whiterock Satins v1

Designated building product: Class 1

Declaration

Altro APAC Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Altro Whiterock Satins
Line	Altro Wall Linings
Identifier	Whiterock Satins

Description

- Intended use: Impervious wall and ceiling solution in wet areas and wall protection in dry areas
 - Type of product: Extruded semi-rigid PVC sheet
 - Fire Group Number 1
 - Surface finish: Smooth
 - Thickness: 2.5mm
 - Size 2500 x 1220mm (W136) or 3000 x 1220mm (W137)
 - No. of colours: 26
 - Thermoformed Corners: Heated and bent corners
 - Thermo-welded Joints: Heat welded wall joints
 - Full System Solution: Waterproof adhesive, tapes, primers, matching weld-rods, silicones etc
 - Weight: 3.6kg/m²
 - Maximum service temp 60°C
-

Scope of use

- Whiterock Satins walling: Can be used as an internal lining on walls and ceilings.
- Whiterock Satins has a fire material group number 1, making it suitable for use in areas where a fire group number of 1 is required.
- It is installed using a waterproof walling adhesive.
- Has a high impact resistance making it suitable for use in areas where high impact or wall protection is required.(e.g. in public reception areas, hospital and school corridors etc).
- Whiterock Satins is suitable for use in wet areas such as bathrooms, changing rooms, ensuites and laundries.
- Whiterock Satins is suitable for use in food preparation areas such as commercial kitchens.
- Whiterock Satins is not acoustically rated, and may not be suitable to form part of an intertenancy wall.
- Not intended to provide structural bracing to the building.
- It is recommended that Whiterock Satins be installed at least 30cm from a heat source.

Conditions of use

- Whiterock Satins must be installed in accordance with our latest published Whiterock Wall Cladding Installation Guide and we recommend it be installed by an Altro Accredited Installer. Refer to our Whiterock Wall Cladding Installation Instructions referenced under documentation and our NZ website for Accredited Installers.
- Whiterock Satins is designed for internal use only and must not be installed directly adjacent to a heat source. A minimum distance of 30cm from a heat source is recommended.
- Whiterock Satins must be maintained and cleaned in accordance with our Walls and Doorsets Cleaning Guide referred to in documents.

Relevant building code clauses

B1 Structure – B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4

C3 Fire affecting areas beyond the fire source – C3.4 (a)

E3 Internal moisture – E3.3.4, E3.3.5, E3.3.6

F2 Hazardous building materials – F2.3.1

G3 Food preparation and prevention of contamination – G3.3.2 (a)

Contributions to compliance

- B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4: Whiterock Satins has a durability of at least 30 years. Refer to our Wall Cladding Installation Guide referenced under documentation.
- C3.4: Whiterock Satins achieves a Material Group Number 1 when tested to EN 13501-1. E-mail shaun@altro.com for a copy of the latest Fire Test Report.
- E3.3.4, E3.3.5, E3.3.6: Whiterock Satins is impervious and easily cleaned. Refer to our Wall Cladding Installation and Walls and Doorsets Cleaning Guides referenced under documentation.
- F2.3.1: Whiterock Satins is safe when handled. There are no requirements for this product in order to comply with F2/AS1, First Edition Amendment 3, 2017. Refer to Whiterock and Fortis materials safety datasheet referenced in documentation.
- G3.3.2 (a) Whiterock Satins is impervious and easily cleaned. Refer to our Wall Cladding Installation and Walls and Doorsets Cleaning Guides referenced under documentation.
- G3.3.2 (b) Whiterock Satins is free from hazardous substances which could cause contamination. Refer to Whiterock and Fortis material safety datasheet and Walls HACCP Certification reference under documentation.

Supporting documentation

The following additional documentation supports the above statements:

Altro Whiterock and Altro Fortis MSDS	31 Jan 2019	https://www.altro.com/nz/technical-documents/altro-whiterock-and-altro-fortis-sds
Altro Walls and Doorsets Cleaning Guide	August 2021	https://www.altro.com/nz/technical-documents/altro-walls-and-doorsets-cleaning-guide
Altro Wall Cladding Installation Guide		https://www.altro.com/nz/technical-documents/altro-wall-cladding-installation-guide
HACCP Walls Certification		https://admin.altro.com/getmedia/c8a570ff-2e6f-4cfe-8b3a-61d0c2489087/Altro-Wall-Cert-Stat-e-2023.pdf

For further information supporting Altro Whiterock Satins claims refer to our website.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Altro PLC
Legal and trading name of importer	Altro APAC Ltd
Importer address for service	88 Logis Boulevard DANDENONG SOUTH VIC 3175
Importer website	www.altro.nz
Importer NZBN	
Importer email	shaun@altro.com
Importer phone number	0279701696

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Altro Whiterock Satins is not subject to a warning on ban under [s26 of the Building Act](#).

Signed for and on behalf of **Altro APAC Ltd**:

Shaun Armstrong

Shaun Armstrong
NZ Sales Manager
December 2023

ALTRO APAC LTD

88 Logis Boulevard DANDENONG SOUTH VIC 3175 New Zealand

0279701696 | www.altro.nz

Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

BPIR Ready selections

Category: Internal linings

	Yes	No
Use to provide structural bracing		x
Use in wet areas	x	
Use in food preparation areas	x	
Part of an intertenancy / abutting occupancy wall system		x
Use in areas with surface fire obligations	x	
Part of a fire protected boundary or fire wall		x
Use in areas with near to sources of heat		x

Building code performance clauses

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements* and *sitework*, including:

- (j) impact

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the *building*,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of *buildings*

C3 Fire affecting areas beyond the fire source

C3.4

Surface Linings

- (a) materials used as internal surface linings in the following areas of buildings must meet the performance criteria specified below: Area of building Performance determined under conditions described in ISO 9705: 1993 Buildings not protected with an automatic fire sprinkler system Buildings protected with an automatic fire[glossary] sprinkler system Wall/ceiling materials in sleeping areas where care or detention is provided Material Group Number 1-S Material Group Number 1 or 2 Wall/ceiling materials in exitways Material Group Number 1-S Material Group Number 1 or 2 Wall/ceiling materials in all occupied spaces in importance level 4 buildings Material Group Number 1-S Material Group Number 1 or 2 Internal surfaces of ducts for HVAC systems Material Group Number 1-S Material Group Number 1 or 2 Ceiling materials in crowd and sleeping uses except household units and where care or detention is provided Material Group Number 1-S or 2-S Material Group Number 1 or 2 Wall materials in crowd and sleeping uses except household units and where care or detention is provided Material Group Number 1-S or 2-S Material Group Number 1, 2, or 3 Wall/ceiling materials in occupied spaces in all other locations in buildings, including household units Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3 External surfaces of ducts for HVAC systems Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3 Acoustic treatment and pipe insulation within airhandling plenums in sleeping uses Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3

E3 Internal moisture

E3.3.4

Wall surfaces adjacent to *sanitary fixtures* or *sanitary appliances* must be impervious and easily cleaned.

E3.3.5

Surfaces of *building elements* likely to be splashed or become contaminated in the course of the *intended use* of the building, must be *impervious* and easily cleaned.

E3.3.6

Surfaces of *building elements* likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into *concealed spaces*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3 Food preparation and prevention of contamination

G3.3.2

Spaces for food preparation and utensil washing shall have:

- (a) interior linings and work surfaces shall be impervious and easily cleaned