

Altro Whiterock White

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Altro APAC Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Altro Whiterock White
Line	Whiterock Walling
Identifier	Whiterock White

Description

- Intended use: Impervious wall and ceiling solution in wet areas and wall protection in dry areas
- Type of product: Extruded semi-rigid PVC sheet
- Fire Group Number 1
- Surface finish: Smooth
- Thickness: 2.5mm Size 2500 x 1220mm (W103) or 3000 x 1220mm (W104)
- No. of colours: White.
- Thermoformed Corners: Heated and bent corners
- Thermo-welded Joints: Heat welded wall joints
- Full System Solution: Waterproof adhesive, tapes, primers, matching weld-rods, silicones etc
- Weight: 3.6kg/m²
- Maximum service temp 60°C

Scope of use

- Whiterock White walling: Can be used as an internal lining on walls and ceilings.

- Whiterock White has a fire material group number 1, making it suitable for use in areas where a fire group number of 1 is required. It is installed using a waterproof walling adhesive.
- It has a high impact resistance making it suitable for use in areas where high impact or wall protection is required.(e.g. in public reception areas, hospital and school corridors etc).
- Whiterock White is suitable for use in wet areas such as bathrooms, changing rooms, ensuites and laundries.
- Whiterock White is suitable for use in food preparation areas such as commercial kitchens.
- Whiterock White is not acoustically rated, and may not be suitable to form part of an intertenancy wall.
- Not intended to provide structural bracing to the building.
- It is recommended that Whiterock White be installed a minimum of 30cm from a heat source.

Conditions of use

- Whiterock White must be installed in accordance with our latest published Whiterock Wall Cladding Installation Guide and we recommend it be installed by an Altro Accredited Installer. Refer to our Wall Cladding Installation referenced under documentation and our NZ website for Accredited Installers.
- Whiterock White is designed for internal use only and must not be installed directly adjacent to a heat source.
- Whiterock White must be maintained and cleaned in accordance with our Walls and Doorsets Cleaning Guide referred to in documents.

Relevant building code clauses

B1 Structure – B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4

C2 Prevention of fire occurring – C2.2

C3 Fire affecting areas beyond the fire source – C3.4 (a)

E3 Internal moisture – E3.3.4, E3.3.5, E3.3.6

F2 Hazardous building materials – F2.3.1

G3 Food preparation and prevention of contamination – G3.3.2 (a)

G6 Airborne and impact sound – G6.3.1

Contributions to compliance

- B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4: Whiterock White has a durability of at least 30 years. Refer to our Wall Cladding Installation Guide referenced under documentation.
- C3.4: Whiterock White achieves a Material Group Number 1 when tested to EN 13501-1. Email shaun@altro.com for a copy of the latest Fire Test Certificate.
- E3.3.4, E3.3.5, E3.3.6: Whiterock White is impervious and easily cleaned. Refer to our Wall Cladding Installation Guide referenced under documentation. Refer to our Walls and Doorsets Cleaning Guide referenced under documentation.
- F2.3.1: Whiterock White is safe when handled. There are no requirements for this product in order to comply with F2/AS1, First Edition Amendment 3, 2017. Refer to Whiterock and Fortis materials safety datasheet referenced under documentation.
- G3.3.2 (a) Whiterock White is impervious and easily cleaned. Refer to our Wall Cladding Installation Guide referenced under documentation. Refer to our Walls and Doorsets Cleaning Guide referenced under documentation.
- G3.3.2 (b) Whiterock White is free from hazardous substances which could cause contamination to the building contents. Refer to Whiterock and Fortis material safety datasheet and Walls HACCP Certification reference under documentation.

Supporting documentation

The following additional documentation supports the above statements:

Altro Whiterock and Altro Fortis MSDS	Version 8	https://www.altro.com/nz/technical-documents/altro-whiterock-and-altro-fortis-sds
Altro Walls and Doorsets Cleaning Guide	August 2021	https://www.altro.com/nz/technical-documents/altro-walls-and-doorsets-cleaning-guide
Altro Wall Cladding Installation Guide		https://www.altro.com/nz/technical-documents/altro-wall-cladding-installation-guide
HACCP Walls Certification		https://admin.altro.com/getmedia/c8a570ff-2e6f-4cfe-8b3a-61d0c2489087/Altro-Wall-Cert-Stat-e-2023.pdf

For further information supporting Altro Whiterock White claims refer to our website.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Altro PLC
Legal and trading name of importer	Altro APAC Ltd
Importer address for service	88 Logis Boulevard DANDENONG SOUTH VIC 3175
Importer website	www.altro.nz
Importer NZBN	
Importer email	shaun@altro.com
Importer phone number	0279701696

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Altro Whiterock White is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of **Altro APAC Ltd**:

Shaun Armstrong

Shaun Armstrong
NZ Sales Manager
December 2023

ALTRO APAC LTD

88 Logis Boulevard DANDENONG SOUTH VIC 3175 New Zealand

0279701696 | www.altro.nz

Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

BPIR Ready selections

Category: Internal linings

	Yes	No
Use to provide structural bracing		x
Use in wet areas	x	
Use in food preparation areas	x	
Part of an intertenancy / abutting occupancy wall system	x	
Use in areas with surface fire obligations	x	
Part of a fire protected boundary or fire wall		x
Use in areas with near to sources of heat	x	

Building code performance clauses

B1 Structure

B1.3.1

Buildings, building elements and sitework shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements* and *sitework*, including:

- (j) impact

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the *building*,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of *buildings*

C2 Prevention of fire occurring

C2.2

The maximum surface temperature of *combustible building materials* close to fixed appliances using controlled combustion and other fixed equipment when operating at their design level must not exceed 90°C.

C3 Fire affecting areas beyond the fire source

C3.4

Surface Linings

- (a) materials used as internal surface linings in the following areas of buildings must meet the performance criteria specified below: Area of building Performance determined under conditions described in ISO 9705: 1993 Buildings not protected with an automatic fire sprinkler system Buildings protected with an automatic fire[glossary] sprinkler system Wall/ceiling materials in sleeping areas where care or detention is provided Material Group Number 1-S Material Group Number 1 or 2 Wall/ceiling materials in exitways Material Group Number 1-S Material Group Number 1 or 2 Wall/ceiling materials in all occupied spaces in importance level 4 buildings Material Group Number 1-S Material Group Number 1 or 2 Internal surfaces of ducts for HVAC systems Material Group Number 1-S Material Group Number 1 or 2 Ceiling materials in crowd and sleeping uses except household units and where care or detention is provided Material Group Number 1-S or 2-S Material Group Number 1 or 2 Wall materials in crowd and sleeping uses except household units and where care or detention is provided Material Group Number 1-S or 2-S Material Group Number 1, 2, or 3 Wall/ceiling materials in occupied spaces in all other locations in buildings, including household units Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3 External

surfaces of ducts for HVAC systems Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3 Acoustic treatment and pipe insulation within airhandling plenums in sleeping uses Material Group Number 1, 2, or 3 Material Group Number 1, 2, or 3

E3 Internal moisture

E3.3.4

Wall surfaces adjacent to *sanitary fixtures* or *sanitary appliances* must be impervious and easily cleaned.

E3.3.5

Surfaces of *building elements* likely to be splashed or become contaminated in the course of the *intended use* of the building, must be *impervious* and easily cleaned.

E3.3.6

Surfaces of *building elements* likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into *concealed spaces*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3 Food preparation and prevention of contamination

G3.3.2

Spaces for food preparation and utensil washing shall have:

- (a) interior linings and work surfaces shall be impervious and easily cleaned

G6 Airborne and impact sound

G6.3.1

The *Sound Transmission Class* of walls, floors and ceilings, shall be no less than 55.