



Please see next page for Altro Whiterock Whiteboard

Cleaning guide for Altro wall panels

For Altro Whiterock, Altro Whiterock Matte, Altro Whiterock Chameleon, Altro Whiterock wall designs, Altro Tegulis, Altro Puraguard, Altro Fortis Titanium 15 and Altro Puresentials

Initial cleaning

Once all panels and joints are installed, remove the protective film and clean all surfaces with an antistatic solution. This is required as the panel will have static build up and any dust in the atmosphere will adhere to the surface of the panel.

Continue with regular maintenance.

Regular maintenance

- Wall panels can be cleaned with a diluted soap/detergent solution or AltroClean 44.
- Use a lint-free, non-woven wipe or a polyester knit wipe. Both are extremely low in particle generation.
- When cleaning the panels we recommend the temperature of water does not exceed 140°F (60°C).
- Pressure cleaning with hot water may be used with the pressure nozzle a minimum of 2 feet (600mm) away from the surface. **Note:** Pressure washing not recommended on Altro Fortis Titanium 15.

- To reduce the build-up of static, cleaning the panels with an anti-static solution or a diluted soap/detergent solution is recommended.
- Some cleaning agents may adversely affect wall panels. See Altro's chemical resistance chart for reactions to common chemicals at www.altro.com/techdocs.
- Do not use cleansers containing abrasives or solvents.

The following maintenance products are available to purchase



P/N: FC445L
AltroClean 44 - 5 Liters
1.3 Gallons



P/N: A809
Anti-Static Solution in spray bottle
500ml



P/N: A809/05
Anti-Static Solution
5 Liters

Labels may indicate that they are exclusively for Altro Whiterock. Please note, cleaning agents may be used for all Altro wall panels named above.



Cleaning guide for printed + film walls

For Altro Whiterock Whiteboard

These products are created by combining Altro Whiterock wall panels with either an applied graphic or protective surface treatment. As a result, any product limitations specific to Altro Whiterock apply to both of these ranges as well. This should be observed for routine surface cleaning and maintenance to best preserve the panels and avoid any potential damage.

For a list of common staining agents and their affects on this product, please reference our stain and chemical resistance chart.

General maintenance

Use of a soft cloth, water and diluted household detergents are recommended. Thoroughly rinse detergents and solvents from surface. For stubborn stains, use diluted AltroClean 44 cleaner or equivalent alkaline cleaner. AltroClean 44 dilution should not be used on a regular basis.

For best results, a thorough cleaning should occur at least once a week.

Recommendations

- Do not use strong solvents such as acetone, MEK or toluene.
- Do not use strongly acidic or alkaline cleaning agents.
- Use a soft cloth, brush or sponge with water and minimal amount of mild soap.
- If edges are not sealed, take care to avoid exposure to liquid which could lead to edge lifting.
- Avoid any abrasive agents that can scratch the film.
- Dry the film after cleaning.

We provide this product information based on our current knowledge and experience. We can neither give any warranty nor assume any responsibility for factors outside our control or knowledge.