

Altro Wood Comfort

Altro Wood Comfort is an ideal choice for areas that need to look good while providing comfort underfoot. This 2.85mm thick option offers 15dB sound reduction, which is great for noisy environments such as healthcare and education settings. For an acoustic option, please see Altro Wood Acoustic.

With matching design and color options across this range and two other wood-look ranges, you can achieve a consistent look in different areas and have the ability to choose between ranges for the right technical performance according to the area.

Altro Wood Comfort also looks great paired with Altro Wood, Altro Wood Acoustic, Altro Wood adhesive-free, Altro Symphonia or even Altro Orchestra.

Typical applications

Healthcare, senior living, education, retail, offices, light gym and recreational areas

Features + benefits

- 2.85mm thick
- Provides ample comfort underfoot
- 15dB sound reduction, ideal for noisy environments such as healthcare and educational settings
- Allows coordination with Altro Wood, Altro Wood Acoustic and Altro Wood adhesivefree ranges for smooth transition between areas requiring different levels of slip resistance and sound absorption
- Resists up to 1,000 psi indentation
- FloorScore Certified / Low VOCs

Better together

Smooth flooring from Altro gives you what you want - an economical and attractive look that's easy to install and maintain. But, in commercial areas with frequent spillages and hygiene and durability concerns, it's best to let our robust collection of safety flooring, slip-resistant flooring and wall cladding join the team!

Install smooth flooring in the dining room and public areas, and bring safety flooring and wall protection into the kitchen, bar and restrooms. You will rest easy knowing your patrons will have an exquisite experience while the most dangerous areas in your facility are well equipped to handle the tolls of the day.

We strongly recommend carrying out a risk assessment in any area in which the installation of smooth flooring is considered, focusing on the potential risk posed by contaminants.

Altro Easyclean Technology



Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products' slip-resistant properties to shine through.

Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention















Autumn Maple Comfort WSMSC2802 WR339 / AM339 LRV 24



Antique Walnut Comfort WSMSC2810 WR341 / AM160 **LRV 15**



Farmhouse Oak Comfort WSMSC2811 WR338 / AM338 LRV 38



Urban Cherry Comfort WSMSC2804 WR337 / AM337 LRV 17



Washed Oak Comfort WSMSC2808 WR347 / AM347 LRV 38



Rustic Oak Comfort WR340 / AM340





Great Oak Comfort WR339 / AM339

WSMSC2817 LRV 22



Vintage Cherry Comfort WSMSC2803 WR336 / AM239 LRV 22





Type + class		ASTM F1303	Type I, Grade 1, Class A, smooth flooring
Thickness and wear layer		2.85mm .11" / .7mm / 28 mil wear layer, heterogeneous construction	
Roll dimensions		6'7" x 65'5" 2m x 20m	
Weight		4.79 lbs./yd 2.6 kg/m 230 lbs. per roll	
Warranty	10 year product warranty	10 years	
Life expectancy	15 year	15 years	
Cleaning technology	EASYCLEAN"	Altro Easyclean	
Static coefficient of friction	.79D .94W SCOF	ASTM D2047	.79 dry, .94 wet
Dynamic coefficient of friction	.49 DCOF	ANSI/NFSI B101.3	.49 wet DCOF
Ramp test	R ₁₀	DIN 51130	R10
TRRL pendulum test	PTV ≥36	BS 7976	36+
Static load limit	A	ASTM F970	1000 psi
Indentation		EN 433	≤ 0.20mm
Wear (abrasion) resistance		EN 660	≤ 10% 50,000 cycles
Castor chair abrasion		EN 425	Pass
Flexibility	5	ASTM F137	Pass
Light fastness	7	EN 20105-B02	≥ 6
Sound insulation	(((©	ISO 140-8	15dB
Electrical behaviors	₹ \$\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	EN 1815	≤ 2kV Antistatic
Fire and smoke	8	CAN/ULC - S102.2 ASTM E648	Tested Class I
performance Mold resistance		ASTM E662 ASTM D3273	< 450 Excellent - Score of 10
Fungi resistance		ASTM G21	Passes rating 0*
Chemical resistance			*achieves zero growth after 28 days
Chemical resistance	floor	ASTM F925	Tested
VOC emissions	score /	CA 01350 FloorScore	Pass Certified
Bio-based content	bio-based content	Manufactured with rapidly renewable bio-based content.	
Ortho-phthalate content	all moiotel-free	Ortho-phthalate-free	
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.		
Backing	Slightly blown PVC with black fleece backing.		
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.		

Altro, Altro Wood Comfort and Altro Easyclean are all trademarks of Altro Limited. Content was correct at time of creation.

Altro reserves the right to change any detail. Please consult your sales representative for the latest product information.

© Copyright Altro USA 2024



Discover more of our sustainability story and credentials at altro.com





Order samples 24 hours a day at altro.com and materialbank.com

Discover more online!



Maintenance guides



Illus. cleaning guides



Warranty forms



Literature



LEED forms



Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries www.altropics.com
- Solutions by area type ORs, labs and cleanrooms, kitchens, senior living and more!

Follow us



- **USA** 800 377 5597
- © CANADA 800 565 4658
- www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information