

Designed for possibilities. Made for people.

Altro Wood Acoustic[™] product datasheet

Realistic wood visuals with enhanced underfoot comfort and sound reduction

Altro Wood Acoustic

Altro Wood Acoustic provides a warm and homey aesthetic with the additional benefit of 19dB sound reduction and an IIC rating of 52, ideal for multi-level construction. At 3.9mm thick, it can tolerate medium to heavy duty traffic and is perfect for environments where people are on their feet a lot and need comfort underfoot.

With matching design and color options across this range and two other wood-look ranges, you can achieve a consistent look in different areas and have the ability to choose between ranges for the right technical performance according to the area.

Altro Wood Acoustic also looks great paired with Altro Wood, Altro Wood Comfort, Altro Symphonia and Altro Serenade.

Typical applications

Healthcare, senior living, education, retail, offices, light gym and recreational areas

Features + benefits

- 3.9mm thick
- Offers excellent sound reduction and an IIC rating of 52
- Ideal for multi-level construction with medium to heavy traffic between floors
- Allows coordination with Altro Wood and Altro Wood Comfort ranges for smooth transition between areas requiring different levels of slip resistance and sound absorption
- FloorScore Certified / Low VOCs
- This product does not contain PFAs

Better together

Smooth flooring from Altro gives you what you want an economical and attractive look that's easy to install and maintain. But, in commercial areas with frequent spillages and hygiene and durability concerns, it's best to let our robust collection of safety flooring, slipresistant flooring and wall cladding join the team!

Install smooth flooring in the dining room and public areas, and bring safety flooring and wall protection into the kitchen, bar and restrooms. You will rest easy knowing your patrons will have an exquisite experience while the most dangerous areas in your facility are well equipped to handle the tolls of the day.

We strongly recommend carrying out a risk assessment in any area in which the installation of smooth flooring is considered, focusing on the potential risk posed by contaminants.

Altro Easyclean Technology



Rather than using a superficial surface coat, Altro Easyclean Technology is incorporated into the flooring while it is manufactured. This allows Altro flooring to benefit from enhanced cleaning and maintenance while still allowing our products' slip-resistant properties to shine through.

Smooth flooring will have a higher level of Altro Easyclean than a slip-resistant or safety floor.

- Industry-leading ease of cleaning
- Enhanced long-term cleanability
- Cleaning and maintenance cost savings
- Sustained long-term slip resistance
- Exceptional long-term durability
- Low dirt pick-up qualities
- Improved color retention









WR335 / AM335

LRV 51



Slate Oak Acoustic WR478 / AM390

WSMA37108 LRV 26



Antique Walnut Acoustic WSMA3782 WR341 / AM160 LRV 15

Farmhouse Oak Acoustic WSMA3781 WR338 / AM338 LRV 38

Bavarian Oak Acoustic WSMA37104 WR514 / AM514

LRV 21

Colors shown: Antique Walnut and Farmhouse Oak



Thickness and wear layer				
Roll dimensions		3.9mm .15" / .7mm / 28 mil wear layer, heterogeneous construction		
		6'7" x 65'5" 2m x 20m		
Veight		5.34 lbs./yd ² 2.9 kg/m ² 265 lbs. per roll		
Warranty		10 years		
_ife expectancy	15 year	15 years		
Cleaning technology	EASYCLEAN	Altro Easyclean		
Static coefficient of friction	.79D .94W SCOF	ASTM D2047	.79 dry, .94 wet	
Dynamic coefficient of friction	.49 DCOF	ANSI/NFSI B101.3	.49 wet DCOF	
Ramp test	R ₁₀	DIN 51130	R10	
RRL pendulum test	PTV ≥36	BS 7976	36+	
Static load limit		ASTM F970	500 psi	
ndentation		EN 433	≤ 0.20mm	
Near (abrasion) resistance		EN 660	≤ 10% 50,000 cycles	
Castor chair abrasion		EN 425	Pass	
Flexibility	52	ASTM F137	Pass	
ight fastness		EN 20105-B02	≥ 6	
		ISO 140-8	19dB	
Sound insulation	((1)?)	ASTM E492 Impact insulation test	Concrete slab STC 52 / IIC 52 Suspended ceiling STC 62 / IIC 65	
Electrical behaviors	52 Å \$2.0 kV	EN 1815	≤ 2kV Antistatic	
Fire and smoke performance	3	CAN/ULC - S102.2 ASTM E648	Tested Class I	
		ASTM E662	< 450	
Mold resistance	*	ASTM D3273	Excellent - Score of 10	
Fungi resistance	f	ASTM G21	Passes rating 0* *achieves zero growth after 28 days	
Chemical resistance		ASTM F925	Tested	
/OC emissions	floor	CA 01350 FloorScore	Pass Certified	
Bio-based content	birsaad content	Manufactured with rapidly renewable bio-based content.		
Ortho-phthalate content	attractor-tree	Ortho-phthalate-free		
Composition	Heterogeneous PVC with glass fiber reinforcement scrim between the film print and backing. Altro Easyclean incorporated into top layer for exceptional cleanability.			
Backing	Blown PVC backing.			
Staining	Certain chemicals may cause staining of vinyl flooring. Traffic stains may be caused by asphalt and rubber products, like rubber mats. Please conduct stain test before installation.			

LEED facts (1) LEED v4				
Altro Wood Acoustic 5				
	Materials and resources Renewable bio-based content	1		
	Materials and resources - EPD Environmental product declaration Type III product specific	1		
	Materials and resources - HPD Health product declaration	1		
6	Environmental quality Low emitting materials, flooring	1		
6	Environmental quality Low emitting materials, adhesives	1		

Discover more of our sustainability story and credentials at altro.com





Order samples 24 hours a day at altro.com and materialbank.com

Discover more online!



Maintenance guides



Illus. cleaning guides

æ



Warranty forms



Literature



LEED forms

Attraction of the second of th

Installation guides



Installation quickfacts

Even more great resources!

- BIM components
- SDS sheets
- Detail drawings and CAD files
- High-resolution swatch downloads
- Photo galleries www.altropics.com
- Solutions by area type ORs, labs and cleanrooms, kitchens, senior living and more!



♥ USA 800 377 5597

- **◊ CANADA** 800 565 4658
- www.altro.com

Content was correct at time of print. Altro reserves the right to change any detail. Please consult www.altro.com or your local Sales Representative for the latest product information.